Old Company Name in Catalogs and Other Documents

On April 1st, 2010, NEC Electronics Corporation merged with Renesas Technology Corporation, and Renesas Electronics Corporation took over all the business of both companies. Therefore, although the old company name remains in this document, it is a valid Renesas Electronics document. We appreciate your understanding.

Renesas Electronics website: http://www.renesas.com

April 1st, 2010 Renesas Electronics Corporation

Issued by: Renesas Electronics Corporation (http://www.renesas.com)

Send any inquiries to http://www.renesas.com/inquiry.



Mask ROM number	
-----------------	--

740 FAMILY MASK ROM CONFIRMATION FORM SINGLE-CHIP MICROCOMPUTER M37542M2V-XXXFP/GP RENESAS TECHNOLOGY

	Date :	
	Section head	Supervisor
ei d	signature	signature
Receipt		
~		

Note: Please fill in all items markedx.

		Company name		ŢEL	,	ce	Submitted by	Supervisor
*	Customer	Date	Date:	(suan gnatu		
		issued	Date.			Issi sigi		

×1. Confirmation

Specify the name of the product being ordered.

Three EPROMs are required for each pattern if this order is performed by EPROMs.

One floppy disk is required for each pattern if this order is performed by a floppy disk.

Microcomputer name: M37542M2V-XXXFP M37542M2V-XXXGP

☐ Ordering by EPROMs

Specify the type of EPROMs submitted.

If at least two of the three sets of EPROMs submitted contain identical data, we will produce masks based on this data. We shall assume the responsibility for errors only if the mask ROM data on the products we produce differs from this data. Thus, extreme care must be taken to verify the data in the submitted EPROMs.

Checksum code for entire EPROM (hexadecimal notation)

EPROM type (indicate the type used)

	27C256		27C512
EPROM a	address	EPROM a	address
000016 000F16 001016 607F16 608016 7FFD16 7FFF16	Area for ASCII codes of the name of the product 'M37542M2V-' Data ROM (8K-130) bytes	000016 000F16 001016 E07F16 E08016 FFFD16 FFFF16	Area for ASCII codes of the name of the product 'M37542M2V-' Data ROM (8K-130) bytes

In the address space of the microcomputer, the internal ROM area is from address E08016 to FFFD16. The reset vector is stored in addresses FFFC16 and FFFD16.

- (1) Set the data in the unused area (the shaded area of the diagram) to "FF16".
- (2) The ASCII codes of the product name "M37542M2V-" must be entered in addresses 000016 to 000816. And set the data "FF16" in addresses 000916 to 000F16. The ASCII codes and addresses are listed to the right in

hexadecimal notation.

Address		Address	
000016	'M'=4D16	000816	'V' = 5616
000116	'3'=33 ₁₆	000916	'-' = 2D16
000216	'7'=37 ₁₆	000A16	FF16
000316	'5'=35 ₁₆	000B16	FF16
000416	'4'=34 ₁₆	000 C 16	FF16
000516	'2'=32 ₁₆	000D16	FF16
000616	'M'=4D16	000E16	FF16
000716	'2'=32 ₁₆	000F16	FF16

Mask ROM number	
Mask ROM Humber	

740 FAMILY MASK ROM CONFIRMATION FORM SINGLE-CHIP MICROCOMPUTER M37542M2V-XXXFP/GP **RENESAS TECHNOLOGY**

We recommend the use of the following pseudo-command to set the start address of the assembler source program because ASCII codes of the product name are written to addresses 000016 to 000816 of EPROM.

EPROM type	27C256	27C512
The pseudo-command	△*=△\$8000 △.BYTE△ 'M37542M2V-'	△ * =△\$0000 △.BYTE△ 'M37542M2V-'

Note: If the name of the product written to the EPROMs does not match the name of the mask confirmation form, the ROM will not be processed.

responsibility for errors only if extreme care must be taken to	the mask ROM data on the produverify the mask file in the submitted	e mask file generating utility. We shall assume the ucts we produce differs from this mask file. Thus, floppy disk. format. And the number of the mask files must be 1
Microcomputer name:	☐ M37542M2V-XXXFP	☐ M37542M2V-XXXGP
File code		(hexadecimal notation)
Mask file name		.MSK (equal or less than eight characters)
000016 to 00	• • • • • • • • • • • • • • • • • • • •	write data to the product name area (addresses

Write data to only ROM data area (addresses E08016 to FFFD16).

*2. Mark specification

Mark specification must be submitted using the correct form for the package being ordered. Fill out the appropriate mark specification form (36P2R-A for M37542M2V-XXXFP, 32P6U-A for M37542M2V-XXXGP) and attach it to the mask ROM confirmation form.

you

Maal DOM number	
Mask ROM number	

740 FAMILY MASK ROM CONFIRMATION FORM SINGLE-CHIP MICROCOMPUTER M37542M2V-XXXFP/GP RENESAS TECHNOLOGY

*3. Usage conditions
For our reference of new products, please reply to the following questions about the usage of the products ordered.
(1) Which operation source clock you use? Ceramic resonator RC oscillation External clock input Quartz-crystal oscillation Other(On-chip oscillator
(2) What is the voltage of power supply (VDD) you use? Typ.= V Min.= V Max.= V
(3) What is the ambient temperature you use? Typ.= °C
(4) Which clock division ratio you use? Double-speed mode $(f(\phi)=F(XIN))$ High-speed mode $(f(\phi)=F(XIN)/2)$ Middle-speed mode $(f(\phi)=F(XIN)/8)$ Applied from on-chip oscillator
(5) Please reply to the following questions about timer function.
(i) Which timer you use?
☐ Timer1 ☐ TimerX ☐ TimerA ☐ TimerB
(ii) Which count source of timer you use?
• Timer X
Timer B
(iii) Which operating mode you use?
• Timer X ☐ Timer mode ☐ Pulse output mode ☐ Event counter mode ☐ Pulse width measurement mode ☐
(iv) Do you use the Output compare? ☐ Use ()channel ☐ Not use
☐ Use ()channel ☐ Not use (v) Do you use the Input capture? ☐ Use ()channel ☐ Not use
(6) Do you use the Serial I/O?
Use Not use [Serial I/O1 (Clock synchronous Serial I/O1 mode Asynchronous Serial I/O1(UART1) mode) Serial I/O2 (Clock synchronous Serial I/O2 mode Asynchronous Serial I/O2(UART2) mode)
(7) Do you use the A/D converter? Use Not use
(8) Do you use the Watchdog timer? Use Not use
(9) Do you use the oscillation stop detection circuit? Use Not use
Thank you cooperation.
×4. Comments