



DRILL CHART: TOP to BOTTOM			
ALL UNITS ARE IN MILS			
FIGURE	SIZE	PLATED	QTY
□	12.0	PLATED	27
●	40.0	PLATED	4



- NOTES:
1. THIS BOARD IS RoHS COMPLIANT.
 2. PRINTED WIRING BOARD DESIGN AND ACCEPTANCE CRITERIA SHALL BE IAW WITH THE REQUIREMENTS OF IPC-D-275 AND IPC-A-600.
 3. MATERIAL: FR4 (RoHS COMPLIANT), 2 OZ COPPER.
 4. APPLY SOLDER MASK, BOTH SIDES OVER BARE COPPER IAW IPC-SM-840, CLASS 2 (LPI) (BLUE MASK).
 5. ALL PATTERNS ARE VIEWED FROM THE PRIMARY SIDE LOOKING THROUGH THE BOARD.
 6. UNLESS OTHERWISE SPECIFIED ALL HOLE DIAMETERS ARE AFTER PLATING.
 7. APPLY SILKSCREEN USING WHITE NON-CONDUCTIVE EPOXY BASED INK.
 8. PWB MUST BE 100% ELECTRICALLY TESTED FOR SHORTS AND CONTINUITY. USE NETLIST PROVIDED RTKA214401DR0000BU IPC356,IPC IAW IPC-D-356.
 9. MARK DATE CODE AND MANUFACTURES IDENTIFICATION ON SOLDER SIDE PER IPC-6011 AND IPC-6012.
 10. TOLERANCE ON ALL DRILL HOLES SHALL BE IAW IPC-D-2221 & 2222 UNLESS OTHERWISE SPECIFIED.

Drawn By: RICHARD KOVACS	Date Drawn: 08/12/2020	Engineer: Xiuge Yang
Released By:	Date Released:	RAA214040 Engineering Board Layout
Updated By:	Date Updated:	MASK: DRAW ID: REV: A
RENEASAS		FILENAME: RTKA214401DR0000BU SHEET 1 of 1