# Old Company Name in Catalogs and Other Documents

On April 1<sup>st</sup>, 2010, NEC Electronics Corporation merged with Renesas Technology Corporation, and Renesas Electronics Corporation took over all the business of both companies. Therefore, although the old company name remains in this document, it is a valid Renesas Electronics document. We appreciate your understanding.

Renesas Electronics website: http://www.renesas.com

April 1<sup>st</sup>, 2010 Renesas Electronics Corporation

Issued by: Renesas Electronics Corporation (http://www.renesas.com)

Send any inquiries to http://www.renesas.com/inquiry.

Mask ROM number

# RENESAS SINGLE-CHIP 16-BIT MICROCOMPUTER M306NNMG-XXXGP MASK ROM CONFIRMATION FORM

	Date :	
¥	Section head signature	Supervisor signature
eip	signature	Signature
Receipt		
Ř		

Note : Please complete all items marked \* .

* Cı	Customer	Company		TEL (    )		ance		Submitted by	Supervisor
		name			)				
	Customer	Date issued	Date :			lssu			

### \* 1. Confirmation

We will produce masks based on the mask files generated by the mask file generating utility. We shall assume the responsibility for errors only if the mask ROM data on the products we produce differs from this mask file. Thus, extreme care must be taken to verify the mask file inthe submitted floppy disk.

The submitted floppy disk must be 3.5-inch 2HD type and IBM format. And the number of mask files must be 1 in a floppy disk.

File code :					(hex)
Mask file name :					.MSK (alpha-numeric 8-digit)

#### \* 2. Mark specification

Mark specification must be submitted using the correct form for the package being ordered. Fill out the appropriate mark specification form (128P6Q) and attach it to the mask ROM confirmation form.

#### # 3.Usage conditions

For our reference to test the part, please fill out the following questions about the usage of the products you ordered.

## (1) Type of XIN-XOUT oscillation circuit

Ceramic resonator	Quartz-crystal oscillator
External clock input	Other ()
Frequency	
f(XIN) = MHz	

EJ19B0289-0100	Mask ROM number
RENESAS SINGLE-CHIP 16-BIT MICROCOMPUTER M306NNMG-XXXGP MASK ROM CONFIRMATION FORM	
(2) Type of XCIN-XCOUT oscillation circuit Ceramic resonator Quartz-crystal oscillator External clock input Other () Frequency f(XCIN) =kHz	Not Used
<ul> <li>(3) Operation modes</li> <li>Single-chip mode</li> <li>Microprocessor mode</li> </ul>	
(4) Operating supply voltage 3.0 3.4 3.8 4.2 4.6 5.0 5.4 ↓ ↓ ↓ ↓ ↓ ↓ ↓ ↓ ↓ ↓ ↓ ↓ ↓ ↓ ↓ ↓ ↓ ↓ ↓	5.8 (V) 
(6) CAN controller setting CAN0 □ Not used □ Used Transmission rate □ bps Synchronization Jump Width(SJW) □ Tq Propagation Time Segment(PTS) □ Tq Phase Buffer Segment1(PBS1) □ Tq Phase Buffer Segment2(PBS2) □ Tq (7) I <sup>2</sup> C (Inter IC) bus function □ Not use □ Use	
(8)IE (Inter Equipment) bus function	

#4. Comments (Indicate none if there is no specific)