## Old Company Name in Catalogs and Other Documents

On April 1<sup>st</sup>, 2010, NEC Electronics Corporation merged with Renesas Technology Corporation, and Renesas Electronics Corporation took over all the business of both companies. Therefore, although the old company name remains in this document, it is a valid Renesas Electronics document. We appreciate your understanding.

Renesas Electronics website: <a href="http://www.renesas.com">http://www.renesas.com</a>

April 1<sup>st</sup>, 2010 Renesas Electronics Corporation

Issued by: Renesas Electronics Corporation (<a href="http://www.renesas.com">http://www.renesas.com</a>)

Send any inquiries to http://www.renesas.com/inquiry.



REJ19B0286-0100

Mask ROM number	
-----------------	--

## RENESAS SINGLE-CHIP 16-BIT MICROCOMPUTER M306NLME-XXXGP MASK ROM CONFIRMATION FORM

	Date :	
<del>_</del>	Section head signature	Supervisor signature
ei ei	Signature	Signature
Receipt		
œ		

									Not	e : Please	co	mpl	ete all items	marked * .	
	Customer	Company name Date issued		TEL			بو	e ا	Submitted by	Supervisor					
*								(	)		Issuance	atur			
A.	Customer		Date :								Issn	signature			
<b>* 1</b>	. Confirmation	on													
	We will prod		nased on th	ne mag	sk filo	s aer	herat	ed h	v the	mask file	ne.	ners	ating utility	We shall	
	assume the					-			•		-				
	this mask file	•		-						•			•		
	The submitte	ed floppy dis	k must be	3.5-in	ch 2H	D typ	oe ar	nd IB	M fo	rmat. And	the	e nu	mber of mas	sk files	
	must be 1 in	a floppy dis	k.												
										1					
	File code :									(hex)					
										l <b>.</b>					
	Mask file name :									i .MSK (a	alpha-numeric 8-digit)				
<b>∦ 2</b>	Mark specii. Mark speci		t be submi	itted u	sina t	he c	orred	ct for	m fo	r the pack	age	be	ing ordered.	Fill out the	
													nfirmation fo		
you ordered.															
	(1) Type of XIN-XOUT oscillation circuit														
		Ceramic res	onator			)uart	z-cry	/stal	oscill	lator					
		External clo	ck input			ther	(			)					
	Freque	ency													
		f(XIN) =	]	MHz											

119B0286-01	$\cap \cap$

Mask ROM number

## RENESAS SINGLE-CHIP 16-BIT MICROCOMPUTER M306NLME-XXXGP MASK ROM CONFIRMATION FORM

(2) Type of XCIN-XCOUT oscillation ci	rcuit	
Ceramic resonator	cillator Not Used	
External clock input	Other (	)
Frequency		
f(XCIN) = kHz	2	
(3) Operation modes		
Single-chip mode	Memory expansio	n mode
☐ Microprocessor mode		
(4) Operating supply voltage		
3.0 3.4 3.8 4.2	2 4.6 5.0	5.4 5.8 (V)
(5) Operating ambient temperature		
-40 -20 0 20	40 60	80 100 (°C)
(6) CAN controller setting		
CAN0 Not used	Used	
Transmission rate	bps	
Synchronization Jump Wid	Ith(SJW)	Tq
Propagation Time Segmer	nt(PTS)	Tq
Phase Buffer Segment1(P	BS1)	Tq
Phase Buffer Segment2(P	BS2)	Tq
(7) I <sup>2</sup> C (Inter IC) bus function		
☐ Not use	Use	
	_	
(8)IE (Inter Equipment) bus function	<b>П</b> и	
☐ Not use	Use	
Thank you for your cooperation.		
4. Comments (Indicate none if there is	no specific)	

(2/2)