Old Company Name in Catalogs and Other Documents

On April 1st, 2010, NEC Electronics Corporation merged with Renesas Technology Corporation, and Renesas Electronics Corporation took over all the business of both companies. Therefore, although the old company name remains in this document, it is a valid Renesas Electronics document. We appreciate your understanding.

Renesas Electronics website: http://www.renesas.com

April 1st, 2010 Renesas Electronics Corporation

Issued by: Renesas Electronics Corporation (http://www.renesas.com)

Send any inquiries to http://www.renesas.com/inquiry.



HITACHI MICROCOMPUTER TECHNICAL UPDATE

THEME SH7751 Correction of sentences concerned with specification of outside pins during the boundary-scan. CLASSIFICATION Spec change Supplement of Documents PRODUCTNAME HD6417751 Lot Lot#:All REFERENCE DOCUMENTS SH7751 Hardware Manual Rev. Effective Date Rev.1 Eternity The SH7751 Hardware Manual "21.3.5 Boundary Scan (EXTEST, SAMPLE/PRELOAD) " is changed.	DATE	14 September 2000	No.	TN-SH7-260A/E
CLASSIFICATION Supplement of Documents PRODUCTNAME HD6417751 REFERENCE DOCUMENTS SH7751 Hardware Manual The SH7751 Hardware Manual "21.3.5 Boundary Scan (EXTEST, SAMPLE/PRELOAD) " is changed. <current> 4. During the boundary scan, permanently negate the CA pin (High) and assert the RESET# pin</current>		SH7751 Correction of sentences concerned with specification of outside pins		
REFERENCE DOCUMENTS SH7751 Hardware Manual The SH7751 Hardware Manual "21.3.5 Boundary Scan (EXTEST, SAMPLE/PRELOAD) " is changed. <current> 4. During the boundary scan, permanently negate the CA pin (High) and assert the RESET# pin</current>	CLASSIFICATION	☐ Spec change ☐ Limitation on Use		
The SH7751 Hardware Manual "21.3.5 Boundary Scan (EXTEST, SAMPLE/PRELOAD) " is changed. <current> 4. During the boundary scan, permanently negate the CA pin (High) and assert the RESET# pin</current>	PRODUCTNAME	HD6417751		Lot Lot#:All
The SH7751 Hardware Manual "21.3.5 Boundary Scan (EXTEST, SAMPLE/PRELOAD) " is changed. <current> 4. During the boundary scan, permanently negate the CA pin (High) and assert the RESET# pin</current>	REFERENCE	SH7751 Hardware Manual	Rev.	Effective Date
<ur>changed.<current></current>4. During the boundary scan, permanently negate the CA pin (High) and assert the RESET# pin</ur>	DOCUMENTS		Rev.1	Eternity
<revised> 4. During EXTEST, permanently assert MRESET# pin (Low), negate RESET# pin (High), and assert CA pin (High). During SAMPLE/PRELOAD, assert CA pin (High).</revised>	changed. <current> 4. During the b (Low). <revised> 4. During EXT</revised></current>	oundary scan, permanently negate the scanness of the scanness	ne CA pin (High) and "# pin (Low), negate	assert the RESET# pin RESET# pin (High), and