

お客様各位

カタログ等資料中の旧社名の扱いについて

2010年4月1日を以ってNECエレクトロニクス株式会社及び株式会社ルネサステクノロジが合併し、両社の全ての事業が当社に承継されております。従いまして、本資料中には旧社名での表記が残っておりますが、当社の資料として有効ですので、ご理解の程宜しくお願い申し上げます。

ルネサスエレクトロニクス ホームページ (<http://www.renesas.com>)

2010年4月1日
ルネサスエレクトロニクス株式会社

【発行】ルネサスエレクトロニクス株式会社 (<http://www.renesas.com>)

【問い合わせ先】 <http://japan.renesas.com/inquiry>

RENESAS TECHNICAL UPDATE

Nippon Bldg., 2-6-2, Ohte-machi, Chiyoda-ku, Tokyo 100-0004, Japan
Renesas Technology Corp.

Product Category	MPU&MCU		Document No.	TN-SH7-A669B/J	Rev.	2.00
Title	Turning on and off power supply of SH7785		Information Category	Technical Notification		
Applicable Product	SH7785	Lot No.	Reference Document	SH7785 Hardware Manual Rev.1.0 (REJ09B0261-0100)		
		All lots				

"D3. Turning On and Off Between the Same Power Supply Series" within the Renesas technical update (TN-SH7-A669A/E) of "Turning On and Off Power Supply" will be revised as follows. The additional restriction regarding both VDDQ-PLL1 and VDDQ-PLL2 which are VDD33 are pointed out by the bold characters.


D. Turning On and Off Power Supply

D.1 Turning On and Off Between Each Power Supply Series

The order of the power supply between the 1.0V series power supply (VDD10: VDD and VDD-PLL1 to 2 and VDDA-PLL1), the 1.8V series power supply (VDD18: VDD-DDR) and the 3.3V series power supply (VDD33: VDDQ and VDDQ-PLL1 to 2 and VDDQ-TD*) is as follows.

Note: * ~~If VDDQ-TD is connected to VDDQ.~~ In case that VDDQ-TD is connected to GND(0V), there is no restriction for the power supply sequence of VDDQ-TD. But if it is connected to the power, please set the power supply of it within $VDDQ+0.3[V]$.

- Turning On Power Supply
There is no restriction for the order of the power supply between each power supply series (VDD10, VDD18, VDD33). Within 300 ms after turning on one power supply series, turn on all the other power supply series.
- Turning Off Power Supply
There is no restriction for the order of the power supply between each power supply series. (VDD10, VDD18, VDD33). Within 300 ms after turning off the one power supply series, turn off all the other power supply series.



VDD10: VDD, VDD-PLL1 to 2, VDDA-PLL1
VDD18: VDD-DDR (except DDR2-SDRAM backup to turning on)
VDD33: VDDQ, VDDQ-PLL1 to 2, VDDQ-TD*

Note: * ~~If VDDQ-TD is connected to VDDQ.~~ In case that VDDQ-TD is connected to GND(0V), there is no restriction for the power supply sequence of VDDQ-TD. But if it is connected to the power, please set the power supply of it within $VDDQ+0.3[V]$.

V**:
VDD10, VDD18 (transition from DDR power supply backup except DDR2-SDRAM power supply backup mode), VDD33

V**:
VDD10, VDD18 (transition from DDR power supply backup except DDR2-SDRAM power supply backup mode), VDD33

Figure D.1 Sequence of Turning On and Off Each Power Supply

D.2 Power-On and Power –Off Sequences for Power Supplies with Different Potentials in DDR2-SDRAM Power Supply Backup Mode

The power-on and power-off sequences for the 1.0 V power supply (VDD10 using pins VDD, VDD-PLL1, VDDA-PLL1, and VDD-PLL2), 1.8 V power supply (VDD18 using pin VDD-DDR), and 3.3 V power supply (VDD33 using pins VDDQ, VDDQ-PLL1, VDDQ-PLL2, and VDDQ-TD*) in DDR2-SDRAM power supply backup mode are as follows.

Note: * If VDDQ-TD is connected to VDDQ. In case that VDDQ-TD is connected to GND(0V), there is no restriction for the power supply sequence of VDDQ-TD. But if it is connected to the power, please set the power supply of it within VDDQ+0.3[V].

- Power-On Sequence
There is no restriction on the sequence in which the above power supplies are powered on. Ensure that all the power supplies start within 300 ms of the start of a power supply other than VDD-DDR.
- Power-Off Sequence
There is no restriction on the sequence in which the above power supplies are powered off. Ensure that all the power supplies stop within 300 ms of the stop of a power supply other than VDD-DDR.




Figure D.2 Power-On and Power-Off Sequences for Power Supplies with Different Potentials in DDR2-SDRAM Power Supply Backup Mode

D.3 Turning On and Off Between the Same Power Supply Series

The order of the power supply in the VDD10 series, the VDD18 series and the VDD33 series power supply is as follows.

Figure D.3 is an explanation chart of VDD10. The regulation of the potential difference is the same VDD10 as the other(VDD10,VDD33). The order of the power supply in the VDD10 series and the VDD18 series power supply has no restriction.

- Turning On Power Supply
There is no restriction for the order of the power supply between each same power supply series except that the potential difference of the one power supply series is less than 0.3V VDD33. In case that VDDQ-TD is connected to GND(0V), there is no restriction for the power supply sequence of VDDQ-TD. But if it is connected to the power, please set the power supply of it within VDDQ+0.3[V]. **And please set the power supply of VDDQ-PLL1 and VDDQ-PLL2 within VDDQ+0.3[V].**
- Turning Off Power Supply
There is no restriction for the order of the power supply between each same power supply series except that the potential difference of the one power supply series is less than 0.3V VDD33. In case that VDDQ-TD is connected to GND(0V), there is no restriction for the power supply sequence of VDDQ-TD. But if it is connected to the power, please set the power supply of it within VDDQ+0.3[V]. **And please set the power supply of VDDQ-PLL1 and VDDQ-PLL2 within VDDQ+0.3[V]**

"Figure D.3 Sequence of Turning On and Off VDD10 Power Supply Series" is removed.