

Keeping Time with the Intersil CDP68HC68T1 Real Time Clock and the "Millennium Bug"

AN9766
Rev 0.00
Nov 1, 1997

Introduction

The Intersil CDP68HC68T1 is a multifunctional CMOS real time clock with 32 bytes of general purpose RAM and various power sense and watchdog control circuitry. The main function of the CDP68HC68T1 (henceforth referred to as the "T1") is to keep accurate time in the form of seconds, minutes, hours, days, months and years. The interface to the T1 is through the SPI interface, available on many Intersil 68HC05 microcontrollers and other popular MCUs.

This application note deals with various techniques for keeping time with the T1, including keeping track of years into the 21st century and beyond.

This application note assumes that the reader has read and has access to the CDP68HC68T1 technical data sheet (Intersil file number 1547.3). A copy of this data sheet may be obtained from your local Intersil Corporation sales representative, downloaded from the Internet at <http://www.intersil.com>.

The "Millennium Bug" or "Y2K" Problem

The "Millennium Bug" (also referred to as the Year 2K and the Y2K problem) is one of the latest problems facing the software development industry. The problem is very simple - a lot of computer programs have been written to accept only two digits to represent the year for any given input. Thus, the program uses the two digits entered and *assumes* that the year is in the 20th century (i.e. the first two numbers are "19"). Thus, entry "74" for the year refers to the year "1974", and so on. Now that the turn of the century is approaching, the last two digits of the year are going to start over at "00". The result? Lots of computers are going to think that it's the year 1900. As you may image, a lot of chaos will ensue if the problem is not fixed. Paychecks will not be issued, air traffic control systems may shut down, your bank account may be frozen, and the list goes on. As this application note is being written, there are companies popping up all over the world for the express purpose of fixing this problem (it is estimated that it will cost over \$600 billion US to fix!). However, keep in mind one important fact -- for the most part, the millennium bug is a SOFTWARE problem. Most hardware devices, the CDP68HC68T1 inclusive, will keep the correct time through the year 2000 if programmed correctly.

Now, you may be thinking that if the millennium bug is a software problem, there is nothing to worry about with using the T1. For the most part, this is true - if programmed correctly, the host MCU interfacing with the T1 will keep the correct time into the 21st century. Unfortunately, with all of the hype about the millennium bug problem in the software world, people have begun to worry about the problem arising in the hardware (i.e. real time clocks like the CDP6818 and the T1). Some companies have even designed devices to be "Year 2000 compliant". As stated before, the T1 and most other real time clock devices will function just fine in the year 2000 provided the application software is written correctly.

This application note will discuss more about the implications of the year 2000 and using the T1 later in the section **Tracking the year and the "Millennium Bug"**. First, we will discuss general time keeping techniques for use with the T1.

Keeping Time with the T1

Keeping time using the T1 is a very simple and easy task. The T1 keeps track of seconds, minutes, hours, days of the week, dates, months and years in BCD (binary coded decimal) format in a series of seven 8 bit internal registers. Once set, the T1 will keep track of all of these values, incrementing them as needed based on a 1Hz clock generated from an external oscillator. Values in the registers will "roll over" when appropriate so as to keep time according to the western Gregorian calendar. The T1 also accounts for leap years (i.e., Feb 28, 1996 will roll over to Feb 29, 1996. Feb 28, 1997 will roll over to Mar 1, 1997).

Timing and the T1

Before we start talking too much about how time is tracked in the T1, first we need to discuss the device's external and internal timing.

To keep track of time, the T1 needs an accurate clock source. There are three types of clocks that the T1 can use - an external square wave input on the XTALIN input pin, a standard crystal oscillator circuit using XTALIN and XTALOUT, or 50/60 Hz AC line voltage on the LINE input pin (standard 120V AC line current is regulated very accurately to 60Hz in North America and can act as a good clock source).

For the square wave and crystal oscillator setups, there are four frequencies that should be used with the T1. These are 32.768kHz, 1.048576MHz, 2.097152kHz and 4.194304MHz. Using frequencies other than these will directly affect the accuracy of the T1.

NOTE: Although the PC board layout of a crystal oscillator circuit is an important consideration in all designs, it is even more so when using a 32.768kHz crystal with a device like the T1. The reason is that these slow oscillating crystals (with respect to 2MHz and 4MHz crystals) have slower rise and fall times and as a result spent a lot more time around the midpoint of the CMOS inverter being used to oscillate the crystal. This makes the oscillator circuitry especially sensitive to external noise. When using a 32.768kHz crystal, be careful to place the crystal as close to the device as possible. The PC board traces for the oscillator circuit should never be more than an inch long and should not run parallel to each other. Also, it is a good idea to shield the oscillator traces by running a ground trace or ground plane around the circuitry. This will help to insure that no unnecessary clocks are generated internally to the T1 due to noise. Finally, as with most CMOS integrated circuits, it is a good idea to place a 0.1μF capacitor across the V_{DD} and V_{SS} supplies of the device to decouple and filter out any unwanted noise.

Address Space and Register Addressing

Internally, the T1 can be viewed as a 64 byte address space, as shown in Figure 1. In this space are contained 13 timer control and status registers, 32 bytes of general purpose RAM and 19 unused bytes. The host MCU controls which byte is being written to or read from by sending an address byte at the beginning of every SPI data transfer. Since the highest addressable location in the T1 is location \$32, only 6 address bits are needed to access the entire T1 address space. Thus, the address byte consists of the write/read bit, one unused bit, and six address bits. After the address byte is sent, the MCU either sends the data to be written or starts a transmission to read from the T1. For example, to write a \$24 to the seconds register (location \$20), the MCU would send \$A0, \$24. The \$A0 byte is the address (\$20) with the MSB set, indicating a write operation. To read the seconds register, the MCU would send \$20, \$xx, where \$xx is a "don't care byte" sent by the MCU to start the SPI transmission. The data sent to the T1 during a read operation is ignored. The data being read from the T1 is shifted out to the MCU through the MISO pins.

When writing to and reading multiple data bytes from the T1, it is advantageous to use the auto-increment feature of the address pointer. Each time a byte is written to or read from the

T1, the internal address pointer increments to the next available address. By starting a subsequent transmission to the T1 without lowering the CE pin of the T1, the MCU can write or read multiple data bytes in one session. For example, the seconds, minutes and hours registers in the T1 are at locations \$20, \$21, and \$22, respectively. To read all three in one transmission, the MCU would send the address byte \$20 (note that the MSB of the address byte is low signifying a read operation), \$xx, \$xx, and \$xx. After the address byte is sent, the MCU sends a dummy byte to start a SPI transmission to read the contents of the seconds register (\$20). Once the T1 sends the seconds, its internal address pointer increments to \$21. When the next transfer is started, the contents of this location are sent, and so on. The example code in Appendix A shows how this technique is used to set and read the complete date and time in one SPI transfer.

Note that the auto-increment feature confines the address pointer to either the RAM locations or the timer register locations, exclusively. When addressing locations in RAM space (\$00-\$1F), the address pointer will wrap to \$00 after location \$1F. Similarly, when accessing the timer registers, the address pointer will wrap from location \$3F to \$20. Thus, you cannot read RAM data and timer data in the same SPI transfer.




FIGURE 1. MEMORY MAP OF THE CDP68HC68T1

Data Format

One of the most important things to remember about the way the T1 keeps time is that the values in the clock registers are in a binary coded decimal (BCD) format. Each byte wide register is divided into two four bit nibbles; each nibble can represent decimal numbers 0 through 9 with the binary numbers %0000 through %1001. Thus, to represent 54 minutes the T1 would contain the number %01010100 (\$54) in the minutes register. As a result, hexadecimal numbers \$A-\$F are not valid (except in the case of the hours register -- see explanation below). This is important to remember for those of you who are used to keeping track of numbers in hexadecimal format -- e.g., to represent December in the months register, you need to write a BCD "12" (\$12) into the register, not \$0C, the hexadecimal equivalent to a decimal 12.

If you do write a value that is out of range for a particular register (say, for example, you want to set the T1 day of the month register to the 15th, so you write a \$0F instead of a \$15), the T1 will not generate an error or let you know in any way that there is invalid data in the register. Instead, it will continue to increment the data as necessary (for our example, once every 24 hours) and will roll the data over when the last appropriate value is reached. In the day register, the T1 will increment from a \$19 to a \$20 (not a \$1A) and from a \$30 to a \$31 (if in a 31 day month) or to a \$01 (if in a 30 day month).

While keeping the values in the time registers in BCD format can be a burden when it comes to doing binary arithmetic, having information in BCD format facilitates displaying the time and date on an ASCII display device. In the example in Appendix A, the time read from the T1 is written to a standard Optrex interface LCD. Converting the minutes value to ASCII, for example, is trivial since all that is required is to simply add \$30 to the BCD values read from the T1. The example code also shows how to easily display text for the day or the week (Sun, Mon, etc.) and the month using the values read from the T1. A table of the timer registers, their valid BCD ranges and examples is shown in Table 1.

Once a time and a date has been written into the T1, all of the values in the timer register will increment appropriately from the 1Hz clock divided down from the external oscillator. Thus, the minutes register will increment every time the seconds rolls from \$59 to \$00, the hours register will increment every time the minutes roll from \$59 to \$00, and so on. The T1 is designed to know that 1 day is 24 hours (rolling over at 11:59 p.m., or 23:59), there are 7 days in a week, there are 30 days in April, June, September, and November, there are 31 days in January, March, May, July, August, October and December, and there are 28 days in February except during leap years. It also knows to increment the year on December 31 at 11:59 p.m.

TABLE 1. CLOCK/CALENDAR AND ALARM DATA MODES

ADDRESS LOCATION (H)	FUNCTION	DECIMAL RANGE	BCD DATA RANGE	(NOTE 1) BCD DATE EXAMPLE
20	Seconds	0-59	00-59	18
21	Minutes	0-59	00-59	49
22	Hours 12 Hour Mode (Note 2)	1-12	81-92 (AM) A1-B2 (PM)	A3
	Hours 24 Hour Mode	0-23	00-23	15
23	Day of the Week (Sunday = 1)	1-7	01-07	03
24	Day of the Month (Date)	1-31	01-31	29
25	Month Jan = 1, Dec = 12	1-12	01-12	10
26	Years	0-99	00-99	85
28	Alarm Seconds	0-59	00-59	18
29	Alarm Minutes	0-59	00-59	49
2A	Alarm Hours (Note 3) 12 Hour Mode	1-12	01-12 (AM) 21-32 (PM)	23
	Alarm Hours 24 Hour Mode	0-23	00-23	15

NOTES:

1. Example: 3:49:18, Tuesday, Oct. 29, 1985.
2. Most significant Bit, D7, is "0" for 24 hours, and "1" for 12 hour mode. Data Bit D5 is "1" for P.M. and "0" for A.M. in 12 hour mode.
3. Alarm hours. Data Bit D5 is "1" for P.M. and "0" for A.M. in 12 hour mode. Data Bits D7 and D6 are DON'T CARE.

The T1 also has the capability to track hours in a 12 hour or 24 hour format. A flag bit in hours register (bit 7) controls this option. If set, the T1 counts hours from 1 to 12. If B7 is clear, the T1 will count hours from 0 to 23. Note that in 12 hour mode, bit 5 of the hours register becomes a flag bit to indicate a.m. or p.m. The example code in Appendix A displays the hours in 12 hour format and uses this flag bit to display a.m. or p.m.

Tracking the Year and the “Millennium Bug”

Keeping track of all aspects of the current time with the exception of the year is very straight forward with the T1. For Example, to set the current time to 5:33:34 p.m., Wednesday, August 20, write the following to the T1:

- \$34 to the seconds register (\$20)
- \$33 to the minutes register (\$21)
- \$A5 (bits 7 and 5 are set to indicate 12 hour mode and p.m.) to the hours register (\$22)
- \$04 (Wednesday is the 4th day of the week) to the day of the week register (\$23)
- \$20 to the day of the month register (\$24)
- \$08 (August is the 8th month of the year) to the month register (\$25)

The year register, however, only has room for a two digit BCD number. So how do we represent a four digit year? Does \$97 in the year register mean 1997 or 2097? One might think that because there is no century counter in the T1 that this part will obviously not work in the 21st century. The only solution is to get a more expensive real time clock with a four digit year counter. This is, however, not the case. The solution is very simple but is one that must be known to the application designer -- the year must be kept track of in software.

Unlike complex PC and mainframe based applications that must be able to trace dates in the past (birth dates into the 1800's) and well as into the future (driver's license expiration dates into the 21st century), the T1, like most real time clocks, is only concerned with the time and date right now. With that in mind it is quite easy to track the year in software.

For example, let's say we are designing a VCR and we are using the T1 as the clock. Our microcontroller must be able to read the T1 and know the exact time and date. This information will be displayed in the on-screen display and used to start or stop the VCR depending on how the user has programmed it. The time and date for the VCR is set in the T1 by inputs from the user and it can be assumed that the T1 will always be tracking the current time. Since it would be useless for most customers to set the VCR clock to a day in the past (8:37 p.m. on May 6, 1974 for example), the MCU program does not need to be concerned with dates in the past. With that in mind, we can pick a year, 1997 perhaps, that to VCR clock cannot be set before. By doing this the software can be written such that any year read from the T1 that is before \$97 must refer to a date from 2000 to 2096. Otherwise, it must be a date from 1997 to 1999. This gives our VCR a 100 year usable date range from January 1, 1997 to December 31, 2096. This is acceptable since the odds that the VCR will still be around in 2095 are pretty slim.

The code example in Appendix A demonstrates this technique. When the year is read from the T1, it is compared to the number \$97. If the current year is lower (\$00 - \$96), the MCU adds the century on as “20”. Otherwise the century “19” is added. For example, if the MCU reads the year as \$05, it will display the year as 2005. If the year is read as \$98, the MCU will display 1998. Thus, 11:59:59 p.m. on December 31, 1999 will be followed immediately by 12:00:00 on January 1, 2000 (this is, incidentally, not the beginning of the new millennium -- January 1, 2001 is). None of the values in the T1 timer registers need to be altered in this transition.

An alternative approach to the “century assumption” method detailed above is to have the host MCU keep track of the century in a RAM byte. In this situation, the MCU would simply increment this century counter in RAM every time it detects a transition from December 31 to January 1. The simplest way of handling this would be to store the month in a RAM byte every time the MCU reads the date from the T1. On the next date read, the MCU would check the current month (read from the T1 month register at location \$25) against the month value read last time the T1 was accessed (stored in RAM). If the current month is less than the old month, MCU would increment the century counter. Keep in mind, this method assumes the T1 is accessed by the MCU at least once every 11 months. Ideally, the century byte and old month value could be stored in the RAM of the T1 itself, thus allowing the MCU to power down without losing track of the year. Utilizing this method allows the T1 to keep track of the correct time indefinitely.

Now, since it is easy to use the T1 right through the year 2000, there should be no other concerns, right? Well, not exactly. There is one more thing to be considered when dealing with the turn of the century. This concern is the fact that the year 2000 is a leap year and there will be a February 29, 2000.

Big deal, right? There is a leap year every four years, right? Well, not exactly. One of the features of the Gregorian calendar used by most of western civilization is that there is an extra day (February 29) in every year evenly divisible by 4, except for century years (1700, 1800, 1900, etc.) NOT divisible by 400. This was done to compensate for the fact that the earth revolves around the sun in 365.244 days, not 365.25. Thus, the year 1800, 1900, 2100 and 2200 are NOT leap years, even though they are evenly divisible by four.

So what does this mean in terms of the T1? Well, the T1 keeps track of leap year by incrementing the date to February 29 at midnight on February 28 when the value in the year counter is evenly divisible by 4. If the application software uses the year counter as described previously (where \$00 in the year counter represents the year 2000), there is no problem. Since the year 2000 is a leap year, the T1 will keep perfect time and there will be no trace of the millennium bug.

If you use the year \$00 to represent 1900, 2100, or any year not divisible by 400, the T1 will increment to February 29, erroneously considering the year to be a leap year. Since it is not likely that any applications using the T1 will need to track the year 1900 or 2100 (unless you are building a time machine), this is not a problem. Thus, there is no “Millennium Bug” in the T1. If an application using the T1 needs the value \$00 in the year register to represent the year 1900, for example, it is simple enough to have the soft-

ware check the date and, if it is equal to Feb 29, 00, increment the date to March 1.

Example Program

On the following pages is an example program written to demonstrate some of the time keeping techniques discussed in this application note. This program is written in 68HC05 assembly language and targets an 8-bit Intersil CDP68HC05C8B microcontroller. This code has been written so that even those with little to no experience with 68HC05 assembly language can hopefully follow along. For more information on CDP68HC05 microcontrollers, visit the Intersil 68HC05 web site on the Internet at <http://www.intersil.com/68hc05>.

The function of the example program is quite simple. The 68HC05 MCU reads the time data from the seven clock registers in the T1 (locations \$20 to \$26) and uses this data to display the current date and time on an Optrex LCD module. The display format for the data is:

Day HH:MM:SS a.m./p.m.
Month Date, 4 digit year

Thus, the current date and time as this application note is being written would be displayed as:

Thu 10:14:34 p.m.
Aug 21, 1997

NOTE: The LCD interface subroutines used by the 68HC05 in this program have not been listed in the listing file for brevity. For a listing and explanation of these subroutines, please refer to the Intersil application note AN9702, “Keypad scan and LCD interface for the CDP68HC05”.

When reading data from the T1, the 68HC05 does a “burst” read of all seven clock registers. As described before, this can be done because the T1 automatically increments its internal address pointer every time a register is read from or written to. In the example program, the 68HC05 sends the command to read from address \$20 (the seconds register and the lowest addressed clock register). The 68HC05 then starts another SPI transmission to read the data from the seconds register. Once the data transfer is complete, the T1 increments its address pointer and is now pointing at location \$21. When the 68HC05 starts the next SPI transmission (without lowering the CS pin of the T1), the T1 will shift out the contents of the minutes register (\$21). The 68HC05 keeps initiating SPI transfers in this way until all seven T1 clock registers are read.

Now, the MCU could have lowered the CS of the T1 after it received the first byte of data. If the 68HC05 then wanted to read the minutes register, it would then raise the CS line, send the command to read from address \$21, and then start another SPI transmission to read the data. Any of the registers in the T1 may be read in this fashion. However, since the clock registers are arranged sequentially in the T1 memory space, it is convenient and much faster to read them in the burst mode described above.

Once all of the data is read from the T1 and stored into the internal RAM of the 68HC05, the MCU uses this data to display the current time and date on the LCD. Since all of the data read from the T1 is in BCD format, displaying numerical data (seconds, min-

utes, day of the month, etc.) is as simple as taking each nibble of the BCD byte, adding \$30 (ASCII '0') to convert it to ASCII, and sending it to the LCD. Displaying the day, month, and year are a little different but still very simple.

For the day and the month, we would like to display their abbreviation, not just their number. To do this, we set up a table of “pointers” to the ASCII text messages set up in the 68HC05 memory. Using the day or month number, the 68HC05 can pick an address out of the pointer table that corresponds to the address of the text message. For example, let’s say the 68HC05 reads the day as “\$05” from the T1. This represents Thursday, or “Thu”. The 68HC05 then loads this value into the index register and loads the accumulator with the value at dayTable, x. What this does is form an address by adding the contents of the index register (\$05) and the address of dayTable (\$27F). The accumulator is loaded with a byte from the resultant address (\$284). This byte (decimal 24, hex \$18) is the value of the lower byte of the address of the “Thu” message in memory (located at \$318). The “xlcd1” subroutine, used to send text messages to the LCD, knows that the high byte of the address is \$03. This is similar to loading a value from a C pointer array called dayTable by saying &message = dayTable[day]. In this way both the month and the day are displayed.

The full four digit year is displayed as apart of this program using the method talked about in the **Tracking the year and the “Millennium Bug”** section. The two digit year is read from the T1 and stored in the RAM of the 68HC05. When it comes to displaying the full date, this program has been written such that years “00” through “96” will have a “20” added as the century counter. Years “97” to “99” will have a “19” added as the century. Thus, this clock will roll over from 11:59:59 p.m, December 31, 1999 to 12:00:00 a.m., January 1, 2000.

Setting the time in this program is done by issuing a software interrupt (SWI). When this is done, the SWI interrupt service routine (ISR), located at address \$262, will take the values in the 68HC05 RAM locations \$50 to \$56 and write them to the T1 clock register locations \$20 to \$26, respectively. This program was tested on a Intersil 68HC051CEC1-EV in-circuit emulator system so that all that was necessary to change the time was to alter the 68HC05 RAM locations and reset the program. In a real application, the user program could possibly receive input from a keypad as a part of an IRQ interrupt, write this data into the proper RAM locations, call the SWI to set the time and date, and then return. Upon returning from the interrupt routine the new date and time would be set and the clock would continue on from the new time.

Conclusion

The CDP68HC68T1 is a powerful and low cost method to keep track of real time in any MCU system. Despite the fact that the T1 does not have a four digit century counter, with the proper programming it can be impervious to the “Millennium Bug” and all of its consequences. Any MCU system will be able to keep time perfectly into the next century with the T1 if a few simple software precautions are taken.

Appendix A - CDP68HC05 to CDP68HC68T1 Interface Example Code Listing

INTERSIL Corporation (c)1990 - 1997

68HC05 Assembler Version 3.0.2

Filename: T1YEAR2K.LST

Source Created:08/21/97, 10:30 am

Assembled: 08/21/97, 10:30 am

```

00001      ;*****
00002      ;      aaaaaaaaaaaaaa
00003      ;      aH""""HHHH""""Ha
00004      ;      aHH  HHHH  HHa      COPYRIGHT 1995,1996,1997
00005      ;      ;- ;- ;-      INTERSIL CORPORATION
00006      ;      _/ |/_ |/_ |_
00007      ;      HHH  HHHH  HHH
00008      ;      HH  HHHH  HH
00009      ;      "HHHHHHHHHHHHH"
00010      ;
00011      ;      File: t1year2k.s
00012      ;
00013      ;      Version: 1.0
00014      ;
00015      ;      Description:
00016      ;      This is a simple program to demonstrate using the Intersil
00017      ;      CDP68HC68T1 RTC in a simple time/date display circuit.
00018      ;      This program interfaces a Intersil CDP68HC05C8B microcontroller
00019      ;      to both the T1 and an Optrex LCD module. The clock data
00020      ;      read from the T1 is displayed in the proper format on the LCD
00021      ;      display.
00022      ;
00023      ;      Note: The LCD interface subroutines have not been included
00024      ;      in this listing file to conserve space. A full listing and
00025      ;      explanation of these routines can be found in the Intersil
00026      ;      application note AN9702, "Keypad scan and LCD interface for
00027      ;      the CDP68HC05".
00028      ;
00029      ;*****
00030
00031      ;*****
00032      ;      -- Constant definitions --
00033      ;*****
00034      ;
00035      #include <c8b.s>
----- START OF INCLUDE F:\6805\C8B.S -----
00001      #nolist
00123      #list
----- END OF INCLUDE F:\6805\C8B.S -----
00036
00037 $0002 = 2      lcd      equ      portc
00038 $0001 = 1      lcdctl   equ      portb
00039 $0006 = 6      rs       equ      6
00040 $0005 = 5      rw       equ      5
00041 $0004 = 4      e        equ      4
00042 $0001 = 1      t1csp    equ      portb
00043 $0007 = 7      t1cs     equ      7
00044
00045      ;*****
00046      ;      -- Variable definitions --
00047      ;*****
00048
00049      0050          section ramVars, $50
00050
00051      0050          seconds    ds      1
00052      0051          minutes    ds      1
00053      0052          hours      ds      1
00054      0053          day        ds      1
00055      0054          date       ds      1
00056      0055          month     ds      1

```

```

00057 0056      year      ds      1
00058 0057      lcdTemp1  ds      1
00059 0058      lcdTemp2  ds      1
00060 0059      lcdTemp3  ds      1
00061 005A      lcdTemp4  ds      1
00062 005B      lcdTemp5  ds      1
00063 005C      lcdTemp6  ds      1
00064 005D      mytemp    ds      1
00065
00066          ;
00067          ; -- Macro definitions --
00068          ;
00069
00070      #macro sendspi
00071          sta    spdr
00072          brclr  spif,spsr,*
00073          lda    spdr
00074      #endmacro
00075
00076          ;
00077          ; -- Program code --
00078          ;
00079
00080      0100      section code, $100
00081
00082 [2] 0100 9C      rsp              ;reset stack pointer
00083 [2] 0101 9B      sei              ;mask interrupts
00084 [6] 0102 CD0241  jsr    lcdIni      ;initialize LCD
00085 [5] 0105 1E05      bset  t1cs,t1csp+4      ;make t1 CS output
00086 [5] 0107 1F01      bclr  t1cs,t1csp      ;disable T1
00087 [2] 0109 A654      lda    #(2!spe+2!mstr+2!cpha) ;SPI on, master, phase=pol=0, 1MHz
00088 [4] 010B B70A      sta    spcr
00089
00090          ;
00091          ; -- Configure the CDP68HC68T1 --
00092          ;
00093          ; The T1 is set up with the control register ($31) = $81. This
00094          ; sets the START bit to enable the counter, sets the T1 up to use
00095          ; a 4.194304MHz oscillator, and to generate a 2MHz output on the
00096          ; clock out pin. All interrupts for the T1 are disabled by writing
00097          ; a $00 to the interrupt control register ($32).
00098          ;
00099
00100 [2] 010D A681      lda    #$81          ;Write an $81 to the control
00101 [2] 010F AE31      ldx    #$31          ;register in the T1 at $31
00102* [6] 0111 AD7D      jsr    writet1
00103
00104 [2] 0113 A600      lda    #$00          ;Write a $00 to the interrupt
00105 [2] 0115 AE32      ldx    #$32          ;register in the T1 at $32
00106* [6] 0117 AD77      jsr    writet1
00107
00108          ;
00109          ; -- Set the time --
00110          ;
00111          ; In this code, the time is read from the T1 from the clock registers
00112          ; at $20 to $26 and placed in 6805 ram locations $50 to $56. From the
00113          ; data in these RAM locations the time display on the LCD is created.
00114          ; If an SWI is issued, the values in these RAM locations will be written
00115          ; to the T1 such as to set the current time.
00116          ;
00117
00118 [10] 0119 83      swi              ;this causes the data in RAM to be
00119          ;be written to the T1
00120
00121          ;
00122          ; -- Displaying the Time --
00123          ;

```

```

00124      ; In this program, all the 6805 MCU does is read the time and date
00125      ; values from the T1 and display them on a standard Optrex LCD. To do
00126      ; this, the 6805 does a burst read of the T1 clock locations $20 to $26
00127      ; and stores them in RAM at locations $50 to $56. The display section of
00128      ; this loop then takes this data, converts it to the appropriate display
00129      ; data and writes it to the LCD.
00130      ;*****
00131
00132      displayLoop
00133
00134 [5] 011A 1E01      bset   t1cs,t1csp      ;enable t1
00135 [2] 011C A620      lda    #$20            ;read all clock registers
00136 [M] 011E          sendspi                ;starting at address $20
00137 [2] 0125 AE50      ldx    #seconds        ;point X at 6805 RAM locations
00138
00139      getLoop
00140 [M] 0127          sendspi                ;get all 7 clock registers in
00141 [4] 012E F7        sta    x                ;burst xfer mode
00142 [3] 012F 5C        incx                    ;and store them to 6805 RAM
00143 [2] 0130 A356      cpx    #$56
00144 [3] 0132 26F3      bne    getLoop
00145 [5] 0134 1F01      bclr   t1cs,t1csp      ;when done, disable T1 CS
00146
00147      ;*****
00148      ; -- Display Time and Date --
00149      ;
00150      ; This section of code takes the data read from the T1 and stored in
00151      ; the RAM of the 6805 and displays it as the time and date in the
00152      ; following format:
00153      ;           Day HH:MM:SS a.m.
00154      ;           Month Day, Year
00155      ; Thus, the current time as this code is being written is:
00156      ;           Thu 10:42:03 a.m.
00157      ;           Aug 21, 1997
00158      ;*****
00159
00160      display
00161 [3] 0136 BE53      ldx    day                ;display day
00162 [5] 0138 DE027F    ldx    dayTable,x        ;use pointer table to send address
00163 [6] 013B CD01D7    jsr    txlcd1            ;of day message to txlcd1 routine
00164 [3] 013E B652      lda    hours            ;display hours (set up as am/pm)
00165 [2] 0140 A41F      and    #$1F            ;mask upper 3 bits (am/pm and mode)
00166 [6] 0142 CD01C4    jsr    txbcd            ;send to LCD
00167 [2] 0145 A63A      lda    #'.'            ;send colon
00168 [6] 0147 CD01EF    jsr    wdlcd
00169 [3] 014A B651      lda    minutes          ;send the minutes to the LCD
00170* [6] 014C AD76    jsr    txbcd
00171 [2] 014E A63A      lda    #'.'            ;and then another colon
00172 [6] 0150 CD01EF    jsr    wdlcd
00173 [3] 0153 B650      lda    seconds          ;and then the seconds
00174* [6] 0155 AD6D    jsr    txbcd
00175 [2] 0157 A620      lda    #$20            ;and then a space
00176 [6] 0159 CD01EF    jsr    wdlcd
00177 [2] 015C A670      lda    #'p'            ;test B5 of the hours data. If set,
00178 [5] 015E 0A5202    brset  5,hours,pm        ;send "p.m." to the LCD. If clear,
00179 [2] 0161 A661      lda    #'a'            ;send "a.m."
00180      pm
00181 [6] 0163 CD01EF    jsr    wdlcd
00182 [2] 0166 A66D      lda    #'m'
00183 [6] 0168 CD01EF    jsr    wdlcd
00184 [3] 016B BE55      ldx    month            ;use month data as pointer into
00185 [5] 016D DE0287    ldx    monthTable,x        ;string table. Send address of
00186* [6] 0170 AD65    jsr    txlcd1            ;month text to txlcd1 routine
00187 [3] 0172 B654      lda    date            ;send the day of the month
00188* [6] 0174 AD4E    jsr    txbcd
00189 [2] 0176 A62C      lda    #$2c            ;send a comma
00190* [6] 0178 AD75    jsr    wdlcd

```



```

00191 [2] 017A A620      lda    #$20          ;send a space
00192* [6] 017C AD71      jsr    wdlcd
00193 [2] 017E A619      lda    #$19          ;send the 1st two digits of the year
00194 [3] 0180 BE56      ldx    year          ;if the year data is >$96, send
00195 [2] 0182 A396      cpx    #$96          ;a $19. If less, send $20. This will
00196 [3] 0184 2202      bhi    20th          ;give this program a date range from
00197 [2] 0186 A620      lda    #$20          ;1-1-1997 to 12-31-2096
00198      20th
00199* [6] 0188 AD3A      jsr    txbcd          ;send upper digits of the year
00200 [3] 018A B656      lda    year          ;then the lower digits
00201* [6] 018C AD36      jsr    txbcd
00202
00203* [3] 018E 208A      jmp    displayLoop      ;and loop
00204
00205      ;*****
00206      ; -- Subroutines --
00207      ;*****
00208
00209      ;*****
00210      ; -- writet1 --
00211      ;
00212      ; This subroutine writes a byte of data, contained in A, to the
00213      ; address contained in X.
00214      ;*****
00215
00216      writet1
00217 [5] 0190 1E01      bset    t1cs,t1csp      ;enable T1
00218 [4] 0192 B757      sta    lcdtemp1      ;preserve A in temp location
00219 [3] 0194 B60B      lda    spsr          ;read SPSR and SPDR to clear
00220 [3] 0196 B60C      lda    spdr          ;the SPIF flag
00221 [2] 0198 9F        txa          ;X contains the T1 reg. address
00222 [2] 0199 AA80      ora    #$80          ;Set write bit (B7)
00223 [4] 019B B70C      sta    spdr          ;and send to T1
00224 [5] 019D 0F0BFD   brclr  spif,spsr,*      ;wait for tx
00225 [3] 01A0 B657      lda    lcdtemp1      ;get data byte to send
00226 [4] 01A2 B70C      sta    spdr          ;and send it
00227 [5] 01A4 0F0BFD   brclr  spif,spsr,*      ;wait for tx
00228 [3] 01A7 B60C      lda    spdr          ;read SPDR to clear SPIF
00229 [5] 01A9 1F01      bclr   t1cs,t1csp      ;disable T1
00230 [6] 01AB 81        rts          ;and return
00231
00232      ;*****
00233      ; -- readt1 --
00234      ;
00235      ; This subroutine reads a byte of data, from the address contained
00236      ; in X and returns it in A.
00237      ;*****
00238
00239      readt1
00240 [5] 01AC 1E01      bset    t1cs,t1csp      ;enable T1
00241 [3] 01AE B60B      lda    spsr          ;clear the SPIF flag
00242 [3] 01B0 B60C      lda    spdr
00243 [2] 01B2 9F        txa          ;move the address to A
00244 [2] 01B3 A47F      and    #$7F          ;clear W/R bit (B7)
00245 [4] 01B5 B70C      sta    spdr          ;and send
00246 [5] 01B7 0F0BFD   brclr  spif,spsr,*      ;wait for tx
00247 [4] 01BA B70C      sta    spdr          ;write anything to SPDR to start tx
00248 [5] 01BC 0F0BFD   brclr  spif,spsr,*      ;wait for tx
00249 [3] 01BF B60C      lda    spdr          ;get received data
00250 [5] 01C1 1F01      bclr   t1cs,t1csp      ;disable T1
00251 [6] 01C3 81        rts          ;and return
00252
00253      ;*****
00254      ; -- txbcd --
00255      ;
00256      ; This subroutine takes a two BCD digits, contained in A, and writes
00257      ; them to the LCD. The data in A MUST BE BCD DIGITS!

```

```

00258      ;*****
00259
00260      txbcd
00261 [4] 01C4 B75D      sta    mytemp      ;preserve A
00262 [3] 01C6 44      lsr     ;shift high nibble to low nibble
00263 [3] 01C7 44      lsr     ;to send the upper BCD digit to
00264 [3] 01C8 44      lsr     ;the LCD
00265 [3] 01C9 44      lsr
00266 [2] 01CA AB30      add    #$30      ;add $30 to convert to ASCII
00267* [6] 01CC AD21      jsr    wldcd    ;and write the data to the LCD
00268 [3] 01CE B65D      lda     mytemp    ;get the original value
00269 [2] 01D0 A40F      and     #$0F      ;and mask to the lower nibble
00270 [2] 01D2 AB30      add    #$30      ;add $30 to convert to ASCII
00271* [6] 01D4 AD19      jsr    wldcd    ;and send to the LCD
00272 [6] 01D6 81      rts
00460
00461      ;*****
00462      ; -- SWI Interrupt Routine --
00463      ;
00464      ; When called, this ISR will take the values in the 6805 RAM locations
00465      ; $50 to $56 and write them into the T1 clock data registers so as
00466      ; to set the time.
00467      ;*****
00468      swiVec
00469 [5] 0262 1E01      bset    t1cs,t1csp    ;enable t1
00470 [2] 0264 A6A0      lda     #$A0      ;write to all clock registers
00471 [M] 0266      sendspi    ;starting at address $20
00472 [2] 026D AE50      ldx     #seconds    ;point X at 6805 RAM locations
00474      setLoop
00475 [3] 026F F6      lda     x      ;get data to send
00476 [M] 0270      sendspi    ;and write to all 7 clock registers
00477 [3] 0277 5C      incx     ;($20-$26) in the T1
00478 [2] 0278 A356      cpx     #$56
00479 [3] 027A 26F3      bne     setLoop
00480 [5] 027C 1F01      bclr    t1cs,t1csp    ;when done, disable T1 CS
00481 [9] 027E 80      rti
00482
00483      ;*****
00484      ; -- Pointer Tables --
00485      ;
00486      ; These two tables are used by to get the address of the weekday and
00487      ; month display strings. This address is used by txlcd1 to display
00488      ; the text on the LCD.
00489      ;*****
00490
00491      dayTable
00492      027F 0000060C      db     0,0,6,12,18,24,30,36
00493      0283 12181E24
00494      monthTable
00495      0287 2A2A3036      db     42,42,48,54,60,66,72,78,84,90,42,42,42,42,42,96,102,108
00496      028B 3C42484E
00497      028F 545A2A2A
00498      0293 2A2A2A2A
00499      0297 60666C
00497      ;*****
00498      ; -- Display Text --
00499      ;
00500      ; This text is used to show the weekday and the month on the LCD.
00501      ; The BCD data from the T1 is used as a pointer into the dayTable and
00502      ; monthTable tables (above). The data loaded from the table is the
00503      ; offset of the text message from mesPage label. This offset is used
00504      ; by txlcd1 to find and display the text. Note that the first byte of
00505      ; each message is an LCD control character used to position the display
00506      ;*****
00507
00508      0300      section mesPage,(*&$FF00+$100) ;start at even page boundary
00509

```

00510	0300 8053756E	db	\$80,"Sun ",\$00
	0304 2000		
00511	0306 804D6F6E	db	\$80,"Mon ",\$00
	030A 2000		
00512	030C 80547565	db	\$80,"Tue ",\$00
	0310 2000		
00513	0312 80576564	db	\$80,"Wed ",\$00
	0316 2000		
00514	0318 80546875	db	\$80,"Thu ",\$00
	031C 2000		
00515	031E 80467269	db	\$80,"Fri ",\$00
	0322 2000		
00516	0324 80536174	db	\$80,"Sat ",\$00
	0328 2000		
00518	032A C04A616E	db	\$C0,"Jan ",\$00
	032E 2000		
00519	0330 C0466562	db	\$C0,"Feb ",\$00
	0334 2000		
00520	0336 C04D6172	db	\$C0,"Mar ",\$00
	033A 2000		
00521	033C C0417072	db	\$C0,"Apr ",\$00
	0340 2000		
00522	0342 C04D6179	db	\$C0,"May ",\$00
	0346 2000		
00523	0348 C04A756E	db	\$C0,"Jun ",\$00
	034C 2000		
00524	034E C04A756C	db	\$C0,"Jul ",\$00
	0352 2000		
00525	0354 C0417567	db	\$C0,"Aug ",\$00
	0358 2000		
00526	035A C0536570	db	\$C0,"Sep ",\$00
	035E 2000		
00527	0360 C04F6374	db	\$C0,"Oct ",\$00
	0364 2000		
00528	0366 C04E6F76	db	\$C0,"Nov ",\$00
	036A 2000		
00529	036C C0446563	db	\$C0,"Dec ",\$00
	0370 2000		
00531	1FF4	section vectors, \$1ff4	
00532	1FF4 0100	dw	code
00533	1FF6 0100	dw	code
00534	1FF8 0100	dw	code
00535	1FFA 0100	dw	code
00536	1FFC 0262	dw	swiVec
00537	1FFE 0100	dw	code

Notice

1. Descriptions of circuits, software and other related information in this document are provided only to illustrate the operation of semiconductor products and application examples. You are fully responsible for the incorporation or any other use of the circuits, software, and information in the design of your product or system. Renesas Electronics disclaims any and all liability for any losses and damages incurred by you or third parties arising from the use of these circuits, software, or information.
 2. Renesas Electronics hereby expressly disclaims any warranties against and liability for infringement or any other claims involving patents, copyrights, or other intellectual property rights of third parties, by or arising from the use of Renesas Electronics products or technical information described in this document, including but not limited to, the product data, drawings, charts, programs, algorithms, and application examples.
 3. No license, express, implied or otherwise, is granted hereby under any patents, copyrights or other intellectual property rights of Renesas Electronics or others.
 4. You shall not alter, modify, copy, or reverse engineer any Renesas Electronics product, whether in whole or in part. Renesas Electronics disclaims any and all liability for any losses or damages incurred by you or third parties arising from such alteration, modification, copying or reverse engineering.
 5. Renesas Electronics products are classified according to the following two quality grades: "Standard" and "High Quality". The intended applications for each Renesas Electronics product depends on the product's quality grade, as indicated below.

"Standard": Computers; office equipment; communications equipment; test and measurement equipment; audio and visual equipment; home electronic appliances; machine tools; personal electronic equipment; industrial robots; etc.

"High Quality": Transportation equipment (automobiles, trains, ships, etc.); traffic control (traffic lights); large-scale communication equipment; key financial terminal systems; safety control equipment; etc.

Unless expressly designated as a high reliability product or a product for harsh environments in a Renesas Electronics data sheet or other Renesas Electronics document, Renesas Electronics products are not intended or authorized for use in products or systems that may pose a direct threat to human life or bodily injury (artificial life support devices or systems; surgical implantations; etc.), or may cause serious property damage (space system; undersea repeaters; nuclear power control systems; aircraft control systems; key plant systems; military equipment; etc.). Renesas Electronics disclaims any and all liability for any damages or losses incurred by you or any third parties arising from the use of any Renesas Electronics product that is inconsistent with any Renesas Electronics data sheet, user's manual or other Renesas Electronics document.
 6. When using Renesas Electronics products, refer to the latest product information (data sheets, user's manuals, application notes, "General Notes for Handling and Using Semiconductor Devices" in the reliability handbook, etc.), and ensure that usage conditions are within the ranges specified by Renesas Electronics with respect to maximum ratings, operating power supply voltage range, heat dissipation characteristics, installation, etc. Renesas Electronics disclaims any and all liability for any malfunctions, failure or accident arising out of the use of Renesas Electronics products outside of such specified ranges.
 7. Although Renesas Electronics endeavors to improve the quality and reliability of Renesas Electronics products, semiconductor products have specific characteristics, such as the occurrence of failure at a certain rate and malfunctions under certain use conditions. Unless designated as a high reliability product or a product for harsh environments in a Renesas Electronics data sheet or other Renesas Electronics document, Renesas Electronics products are not subject to radiation resistance design. You are responsible for implementing safety measures to guard against the possibility of bodily injury, injury or damage caused by fire, and/or danger to the public in the event of a failure or malfunction of Renesas Electronics products, such as safety design for hardware and software, including but not limited to redundancy, fire control and malfunction prevention, appropriate treatment for aging degradation or any other appropriate measures. Because the evaluation of microcomputer software alone is very difficult and impractical, you are responsible for evaluating the safety of the final products or systems manufactured by you.
 8. Please contact a Renesas Electronics sales office for details as to environmental matters such as the environmental compatibility of each Renesas Electronics product. You are responsible for carefully and sufficiently investigating applicable laws and regulations that regulate the inclusion or use of controlled substances, including without limitation, the EU RoHS Directive, and using Renesas Electronics products in compliance with all these applicable laws and regulations. Renesas Electronics disclaims any and all liability for damages or losses occurring as a result of your noncompliance with applicable laws and regulations.
 9. Renesas Electronics products and technologies shall not be used for or incorporated into any products or systems whose manufacture, use, or sale is prohibited under any applicable domestic or foreign laws or regulations. You shall comply with any applicable export control laws and regulations promulgated and administered by the governments of any countries asserting jurisdiction over the parties or transactions.
 10. It is the responsibility of the buyer or distributor of Renesas Electronics products, or any other party who distributes, disposes of, or otherwise sells or transfers the product to a third party, to notify such third party in advance of the contents and conditions set forth in this document.
 11. This document shall not be reprinted, reproduced or duplicated in any form, in whole or in part, without prior written consent of Renesas Electronics.
 12. Please contact a Renesas Electronics sales office if you have any questions regarding the information contained in this document or Renesas Electronics products.
- (Note 1) "Renesas Electronics" as used in this document means Renesas Electronics Corporation and also includes its directly or indirectly controlled subsidiaries.
- (Note 2) "Renesas Electronics product(s)" means any product developed or manufactured by or for Renesas Electronics.

(Rev.4.0-1 November 2017)



SALES OFFICES

Renesas Electronics Corporation

<http://www.renesas.com>

Refer to "<http://www.renesas.com/>" for the latest and detailed information.

Renesas Electronics America Inc.
1001 Murphy Ranch Road, Milpitas, CA 95035, U.S.A.
Tel: +1-408-432-8888, Fax: +1-408-434-5351

Renesas Electronics Canada Limited
9251 Yonge Street, Suite 8309 Richmond Hill, Ontario Canada L4C 9T3
Tel: +1-905-237-2004

Renesas Electronics Europe Limited
Dukes Meadow, Millboard Road, Bourne End, Buckinghamshire, SL8 5FH, U.K
Tel: +44-1628-651-700, Fax: +44-1628-651-804

Renesas Electronics Europe GmbH
Arcadiastrasse 10, 40472 Düsseldorf, Germany
Tel: +49-211-6503-0, Fax: +49-211-6503-1327

Renesas Electronics (China) Co., Ltd.
Room 1709 Quantum Plaza, No.27 ZhichunLu, Haidian District, Beijing, 100191 P. R. China
Tel: +86-10-8235-1155, Fax: +86-10-8235-7679

Renesas Electronics (Shanghai) Co., Ltd.
Unit 301, Tower A, Central Towers, 555 Langao Road, Putuo District, Shanghai, 200333 P. R. China
Tel: +86-21-2226-0888, Fax: +86-21-2226-0999

Renesas Electronics Hong Kong Limited
Unit 1601-1611, 16/F., Tower 2, Grand Century Place, 193 Prince Edward Road West, Mongkok, Kowloon, Hong Kong
Tel: +852-2265-6688, Fax: +852-2886-9022

Renesas Electronics Taiwan Co., Ltd.
13F, No. 363, Fu Shing North Road, Taipei 10543, Taiwan
Tel: +886-2-8175-9600, Fax: +886-2-8175-9670

Renesas Electronics Singapore Pte. Ltd.
80 Bendemeer Road, Unit #06-02 Hyflux Innovation Centre, Singapore 339949
Tel: +65-6213-0200, Fax: +65-6213-0300

Renesas Electronics Malaysia Sdn.Bhd.
Unit 1207, Block B, Menara Amcorp, Amcorp Trade Centre, No. 18, Jln Persiaran Barat, 46050 Petaling Jaya, Selangor Darul Ehsan, Malaysia
Tel: +60-3-7955-9390, Fax: +60-3-7955-9510

Renesas Electronics India Pvt. Ltd.
No.777C, 100 Feet Road, HAL 2nd Stage, Indiranagar, Bangalore 560 038, India
Tel: +91-80-67208700, Fax: +91-80-67208777

Renesas Electronics Korea Co., Ltd.
17F, KAMCO Yangjae Tower, 262, Gangnam-daero, Gangnam-gu, Seoul, 06265 Korea
Tel: +82-2-558-3737, Fax: +82-2-558-5338