

General Description

Renesas SLG7NT41204 is a low power and small form device. The SoC is housed in a 2mm x 3mm STQFN package which is optimal for using with small devices.


Features

- Low Power Consumption
- Pb-Free / RoHS Compliant
- Halogen-Free
- STQFN-20 Package

Output Summary

- 7 Outputs — Open Drain NMOS 1X

Pin Configuration



Pin Configuration

Pin #	Pin Name	Type	Pin Description
1	VDD	PWR	Supply Voltage
2	PSEUDO_G3	Digital Input	Digital Input without Schmitt trigger
3	PWRBTN_SW	Digital Input	Digital Input with Schmitt trigger
4	ADPTR_PRESENT_EC	Digital Output	Open Drain NMOS 1X
5	ADPTR_PRESENT	Digital Input	Digital Input without Schmitt trigger
6	BXT_GLK_PD	Analog Input/Output	Analog Input/Output
7	SLP_S0ix_N	Digital Input	Digital Input without Schmitt trigger
8	PCH_PWROK	Digital Output	Open Drain NMOS 1X
9	IMVP_VR_ON	Digital Output	Open Drain NMOS 1X
10	VNN_COMP	Analog Input/Output	Analog Input/Output
11	GND	GND	Ground
12	DDR_VR_PGD	Digital Input	Digital Input without Schmitt trigger
13	RSMRST_PWRGD	Digital Input	Digital Input without Schmitt trigger
14	SLP_S3_N	Digital Input	Digital Input without Schmitt trigger
15	THERMTRIP_N	Analog Input/Output	Analog Input/Output
16	NC	--	Keep Floating or Connect to GND
17	VNN_PGD	Digital Output	Open Drain NMOS 1X
18	VTT_CTRL	Digital Output	Open Drain NMOS 1X
19	PWRBTN_EC	Digital Output	Open Drain NMOS 1X
20	5VR_PGD	Digital Output	Open Drain NMOS 1X

Ordering Information

Part Number	Package Type
SLG7NT41204V	V=STQFN-20
SLG7NT41204VTR	VTR=STQFN-20 – Tape and Reel (3k units)

Absolute Maximum Conditions

Parameter	Min.	Max.	Unit
V _{HIGH} to GND	-0.3	7	V
Voltage at input pins	-0.3	7	V
Current at input pin	-1.0	1.0	mA
Storage temperature range	-65	125	°C
Junction temperature	--	150	°C
ESD Protection (Human Body Model)	2000	--	V
ESD Protection (Charged Device Model)	1300	--	V
Moisture Sensitivity Level	1		

Electrical Characteristics


(@ 25°C, unless otherwise stated)

Symbol	Parameter	Condition/Note	Min.	Typ.	Max.	Unit
V _{DD}	Supply Voltage		4.5	5	5.5	V
T _A	Operating Temperature		-40	25	85	°C
I _Q	Quiescent Current	Static inputs and outputs	--	95	--	μA
V _O	Maximal Voltage Applied to any PIN in High-Impedance State		--	--	VDD	V
I _O	Maximal Average or DC Current (note 1)	Per Each Chip Side (PIN2-PIN10, PIN12-PIN20)	--	--	90	mA
V _{IH}	HIGH-Level Input Voltage	Logic Input, at VDD=5.0V	2.64	--	VDD	V
		Logic Input with Schmitt Trigger, at VDD=5.0V	3.16	--	VDD	
V _{IL}	LOW-Level Input Voltage	Logic Input, at VDD=5.0V	--	--	1.84	V
		Logic Input with Schmitt Trigger, at VDD=5.0V	--	--	1.51	
I _{IH}	HIGH-Level Input Current	Logic Input PINs; V _{IN} = VDD	-1.0	--	1.0	μA
I _{IL}	LOW-Level Input Current	Logic Input PINs; V _{IN} = 0V	-1.0	--	1.0	μA
V _{OL}	LOW-Level Output Voltage	Open Drain, I _{OL} = 5mA, 1X Driver, at VDD=5.0 V	--	0.102	0.180	V
I _{OL}	LOW-Level Output Current	Open Drain, V _{OL} = 0.4V, 1X Driver, at VDD=5.0 V	10.82	17.38	--	mA
V _{ACMP0}	Analog Comparator Threshold Voltage	ACMP0 threshold including input offset, reference voltage variation and hysteresis, at temperature 25°C.	1184	--	1219	mV
		ACMP0 threshold including input offset, reference voltage variation and hysteresis, at temperature -40°C +85°C (note 1)	1133	--	1245	
V _{ACMP1}	Analog Comparator Threshold Voltage	ACMP1 threshold including input offset, reference voltage variation and hysteresis, at temperature 25°C.	568	--	633	mV


		ACMP1 threshold including input offset, reference voltage variation and hysteresis, at temperature -40°C +85°C (note 1)	548	--	645	
V _{ACMP3}	Analog Comparator Threshold Voltage	ACMP3 threshold including input offset, reference voltage variation and hysteresis, at temperature 25°C.	777	--	823	mV
		ACMP3 threshold including input offset, reference voltage variation and hysteresis, at temperature -40°C +85°C (note 1)	746	--	838	
V _{HYST}	Analog Comparator Hysteresis Voltage (note 1)	ACMP 3	--	25	--	mV
		ACMP 1	--	50	--	
T _{DLY0}	Delay0 Time	At temperature 25°C	777.14	800.08	823.64	ms
		At temperature -40°C +85°C (note 1)	699.06	800.08	972.55	
T _{DLY1}	Delay1 Time	At temperature 25°C	680	700.08	720.71	ms
		At temperature -40°C +85°C (note 1)	611.68	700.08	851.01	
T _{DLY2}	Delay2 Time	At temperature 25°C	484.93	500.48	516.49	ms
		At temperature -40°C +85°C (note 1)	436.21	500.48	609.87	
T _{DLY3}	Delay3 Time	At temperature 25°C	116.56	140	164.7	μs
		At temperature -40°C +85°C (note 1)	104.85	140	194.48	
T _{DLY4}	Delay4 Time	At temperature 25°C	534.67	551.68	569.19	ms
		At temperature -40°C +85°C (note 1)	480.95	551.68	672.1	
T _{DLY5}	Delay5 Time	At temperature 25°C	271.99	300	329.4	μs
		At temperature -40°C +85°C (note 1)	244.67	300	388.95	
T _{DLY6}	Delay6 Time	At temperature 25°C	241.22	249.6	258.25	ms
		At temperature -40°C +85°C (note 1)	216.98	249.6	304.94	
T _{SU}	Start up Time	From VDD rising past 1.6V	--	0.3	--	ms

1. Guaranteed by Design.

Timing Diagram



Package Top Marking




XXXXX – Part ID Field: identifies the specific device configuration
 DD – Date Code Field: Coded date of manufacture
 LLL – Lot Code: Designates Lot #
 C – Assembly Site/COO: Specifies Assembly Site/Country of Origin
 RR – Revision Code: Device Revision

Datasheet Revision	Programming Code Number	Locked Status	Part Code	Revision	Date
1.04	002	L	41204	AB	02/25/2022

The IC security bit is locked/set for code security for production unless otherwise specified. Revision number is not changed for bit locking.

Package Drawing and Dimensions

20 Lead STQFN Package
JEDEC MO-220, Variation WECE
IC Net Weight: 0.0090 g



Unit: mm

Symbol	Min	Nom.	Max	Symbol	Min	Nom.	Max
A	0.50	0.55	0.60	D	2.95	3.00	3.05
A1	0.005	-	0.050	E	1.95	2.00	2.05
A2	0.10	0.15	0.20	L1	0.75	0.80	0.85
b	0.13	0.18	0.23	L2	0.55	0.60	0.65
e	0.40 BSC			L3	0.275	0.325	0.375


Tape and Reel Specification

Package Type	# of Pins	Nominal Package Size (mm)	Max Units		Reel & Hub Size (mm)	Trailer A		Leader B		Pocket (mm)	
			per reel	per box		Pockets	Length (mm)	Pockets	Length (mm)	Width	Pitch
STQFN 20L 2x3mm 0.4P Green	20	2x3x0.55	3000	3000	178/60	100	400	100	400	8	4

Carrier Tape Drawing and Dimensions

Package Type	Pocket BTM Length (mm)	Pocket BTM Width (mm)	Pocket Depth (mm)	Index Hole Pitch (mm)	Pocket Pitch (mm)	Index Hole Diameter (mm)	Index Hole to Tape Edge (mm)	Index Hole to Pocket Center (mm)	Tape Width (mm)
	A0	B0	K0	P0	P1	D0	E	F	W
STQFN 20L 2x3mm 0.4P Green	2.2	3.15	0.76	4	4	1.5	1.75	3.5	8

Refer to EIA-481 Specifications



Recommended Reflow Soldering Profile

Please see IPC/JEDEC J-STD-020: latest revision for reflow profile based on package volume of 3.3 mm³ (nominal). More information can be found at www.jedec.org.

IMPORTANT NOTICE AND DISCLAIMER

RENESAS ELECTRONICS CORPORATION AND ITS SUBSIDIARIES ("RENESAS") PROVIDES TECHNICAL SPECIFICATIONS AND RELIABILITY DATA (INCLUDING DATASHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, WITHOUT LIMITATION, ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR NON-INFRINGEMENT OF THIRD-PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for developers who are designing with Renesas products. You are solely responsible for (1) selecting the appropriate products for your application, (2) designing, validating, and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, or other requirements. These resources are subject to change without notice. Renesas grants you permission to use these resources only to develop an application that uses Renesas products. Other reproduction or use of these resources is strictly prohibited. No license is granted to any other Renesas intellectual property or to any third-party intellectual property. Renesas disclaims responsibility for, and you will fully indemnify Renesas and its representatives against, any claims, damages, costs, losses, or liabilities arising from your use of these resources. Renesas' products are provided only subject to Renesas' Terms and Conditions of Sale or other applicable terms agreed to in writing. No use of any Renesas resources expands or otherwise alters any applicable warranties or warranty disclaimers for these products.

(Disclaimer Rev.1.01)

Corporate Headquarters

TOYOSU FORESIA, 3-2-24 Toyosu,
Koto-ku, Tokyo 135-0061, Japan
www.renesas.com

Contact Information

For further information on a product, technology, the most up-to-date version of a document, or your nearest sales office, please visit www.renesas.com/contact-us/.

Trademarks

Renesas and the Renesas logo are trademarks of Renesas Electronics Corporation. All trademarks and registered trademarks are the property of their respective owners.