


RX PART NUMBER GUIDE

2026/10/22 REV. 15.4

RENESAS ELECTRONICS CORPORATION

RX PART NUMBER RULE

RX family common info



*1: This information is different every RX group.

RX110 Group



R5 F 5 110 5 A D FM #3 0

Renesas MCU
ROM Type F: Flash
RX100 Series

Product Group

110	RX110
-----	-------

ROM/RAM Size

5	128KB	16KB
4	96KB	16KB
3	64KB	10KB
1	32KB	10KB
J	16KB	8KB
H	8KB	8KB

Production Identification code

Carrier type

U,2,3	Tray (Bulk)
0,1	Tray (Full carton)

Package, pin count and pin pitch

FM	LFQFP	64	0.50 mm
FL	LFQFP	48	0.50 mm
FK	LQFP	64	0.80 mm
LF	WFLGA	64	0.50 mm
LM	WFLGA	36	0.50 mm
NE	HWQFN	48	0.50 mm
NF	HWQFN	40	0.50 mm

Temperature

D	Ta = -40°C to 85°C
G	Ta = -40°C to 105°C

Example shown here:
RX110 (64-pin), Part number R5F51105ADFM#30

This guide shows the meanings of each figure of Product Part Number.
Please refer User's Manual for the actual lineup.

RX111 Group



R5 F 5 111 5 A D FM #3 0

Renesas MCU
ROM Type F: Flash
RX100 Series

Product Group

111	RX111
-----	-------

ROM/RAM/Data flash Size

8	512KB	64KB	8KB
7	384KB	64KB	8KB
6	256KB	32KB	8KB
5	128KB	16KB	8KB
4	96KB	16KB	8KB
3	64KB	10KB	8KB
1	32KB	10KB	8KB
J	16KB	8KB	8KB

Production Identification code

Carrier type

U,2,3	Tray (Bulk)
0,1	Tray (Full carton)
4,5,W	Tape and reel

Package, pin count and pin pitch

FM	LFQFP	64	0.50 mm
FL	LFQFP	48	0.50 mm
FK	LQFP	64	0.80 mm
LF	WFLGA	64	0.50 mm
LM	WFLGA	36	0.50 mm
NE	HWQFN	48	0.50 mm
NF	HWQFN	40	0.50 mm

Temperature

D	Ta = -40°C to 85°C
G	Ta = -40°C to 105°C

Example shown here:

RX111 (64-pin), Part number R5F51115ADFM#30

This guide shows the meanings of each figure of Product Part Number.
Please refer User's Manual for the actual lineup.

RX113 Group



R5 F 5 113 8 A D FM #3 A

Renesas MCU
ROM Type F: Flash
RX100 Series

Product Group

113	RX113
-----	-------

ROM/RAM/Data flash Size

8	512KB	64KB	8KB
7	384KB	64KB	8KB
6	256KB	32KB	8KB
5	128KB	32KB	8KB

Production Identification code

Terminal specification

2,3	Tray (Bulk)
1	Tray (Full carton)
5	Tape and reel

Package, pin count and pin pitch

FP	LFQFP	100	0.50 mm
FM	LFQFP	64	0.50 mm
LJ	TFLGA	100	0.65 mm

Temperature

D	Ta = -40°C to 85°C
G	Ta = -40°C to 105°C

Example shown here:
RX113 (64-pin), Part number R5F51138ADFM#3A

This guide shows the meanings of each figure of Product Part Number.
Please refer User's Manual for the actual lineup.

RX130 Group



R5 F 5 130 5 A D FM #3 0

Renesas MCU
ROM Type F: Flash
RX100 Series

Product Group

130	RX130
-----	-------

ROM/RAM/Data flash Size

8	512KB	48KB	8KB
7	384KB	48KB	8KB
6	256KB	32KB	8KB
5	128KB	16KB	8KB
3	64KB	10KB	8KB

Chip version

A	Chip version A
B	Chip version B

Production Identification code

Terminal specification

U,2,3	Tray (Bulk)
0,1	Tray (Full carton)
5	Tape and reel

Package, pin count and pin pitch

FP	LFQFP	100	0.50 mm
FN	LFQFP	80	0.50 mm
FM	LFQFP	64	0.50 mm
FL	LFQFP	48	0.50 mm
FK	LQFP	64	0.80 mm
NE	HWQFN	48	0.50 mm

Temperature

D	Ta = -40°C to 85°C
G	Ta = -40°C to 105°C

Example shown here:

RX130 (64-pin), Part number R5F51305ADFM#30

This guide shows the meanings of each figure of Product Part Number.
Please refer User's Manual for the actual lineup.

RX13T Group



R5 F 5 13T 5 A D FL #3 0

Renesas MCU ROM Type F: Flash RX100 Series

Product Group

13T	RX13T
-----	-------

ROM/RAM/ Data flash Size

5	128KB	12KB	4KB
3	64KB	12KB	4KB

Production Identification code

Terminal specification

2,3	Tray (Bulk)
1	Tray (Full carton)

Package, pin count and pin pitch

FJ	LQFP	32	0.80 mm
FL	LFBGA	48	0.50 mm
NE	QFN	48	0.50 mm
NH	QFN	32	0.50 mm

Temperature

D	Ta = -40°C to 85°C
G	Ta = -40°C to 105°C

Example shown here:
RX13T (48-pin), Part number R5F513T5ADFL#30

This guide shows the meanings of each figure of Product Part Number.
Please refer User's Manual for the actual lineup.

RX14T Group



R5 F 5 14T 5 A G FM #3 0

Renesas MCU
ROM Type F: Flash
RX100 Series

Product Group

14T	RX14T
-----	-------

ROM/RAM/ Data flash Size

5	128KB	12KB	4KB
---	-------	------	-----

Production Identification code

Terminal specification

1	Tray (Full carton)
7	Tray (Full Tray)
5	Tape and reel

Package, pin count and pin pitch

FM	LFQFP	64	0.50 mm
FK	LQFP	64	0.80 mm
FD	LQFP	52	0.65 mm
FL	LFQFP	48	0.50 mm

FV	LQFP	44	0.80 mm
NH	LQFP	32	0.80 mm
NE	HWQFN	48	0.50 mm
NH	HWQFN	32	0.50 mm
NK	HWQFN	24	0.50 mm

Temperature

G	Ta = -40°C to 105°C
M	Ta = -40°C to 125°C

Example shown here:

RX14T (64-pin), Part number R5F514T5AGFM#30

This guide shows the meanings of each figure of Product Part Number.
Please refer User's Manual for the actual lineup.

RX140 Group



R5 F 5 140 6 A D FM #3 0

Renesas MCU
ROM Type F: Flash
RX100 Series

Product Group

140	RX140
-----	-------

ROM/RAM/Data flash Size

6	256KB	64KB	8KB
5	128KB	32KB	8KB
3	64KB	16KB	4KB

Encryption Support

A	No
B	Yes

Production Identification code

Terminal specification

3	Tray (Bulk)
1	Tray (Full carton)
5	Tape and reel

Package, pin count and pin pitch

FN	LFQFP	80	0.50 mm
FM	LFQFP	64	0.50 mm
FK	LQFP	64	0.80 mm
FL	LFQFP	48	0.50 mm
NE	HWQFN	48	0.50 mm
FJ	LFQFP	32	0.80 mm
NH	HWQFN	32	0.50 mm

Temperature

D	Ta = -40°C to 85°C
G	Ta = -40°C to 105°C

Example shown here:

RX140 (64-pin), Part number R5F51406ADFM#30

This guide shows the meanings of each figure of Product Part Number.
Please refer User's Manual for the actual lineup.

RX210 Group



R5 F 5 210 8 A D F P # V 0

Renesas MCU
ROM Type F: Flash
RX200 Series

Product Group

210	RX210
-----	-------

ROM/RAM/Data flash Size

B	1MB	96KB	8KB	6	256KB	32KB	8KB
A	768KB	96KB	8KB	5	128KB	20KB	8KB
8	512KB	64KB	8KB	4	96KB	16KB	8KB
7	384KB	64KB	8KB	3	64KB	12KB	8KB

Chip version

A	Chip version A
B	Chip version B
C	Chip version C

Production Identification code

Terminal specification

U,V,3	Tray (Bulk)
1	Tray (Full carton)
5	Tape and reel

Package, pin count and pin pitch

FB	LFQFP	144	0.50 mm	FK	LQFP	64	0.80 mm
FP	LFQFP	100	0.50 mm	LK	TFLGA	145	0.50 mm
FN	LFQFP	80	0.50 mm	LA	TFLGA	100	0.50 mm
FM	LFQFP	64	0.50 mm	LJ	TFLGA	100	0.65 mm
FL	LFQFP	48	0.50 mm	LH	TFLGA	64	0.65 mm
FF	LQFP	80	0.65 mm				

Temperature

D	Ta = -40°C to 85°C
G	Ta = -40°C to 105°C

Example shown here:

RX210 (100-pin), Part number R5F52108ADFP#V0

This guide shows the meanings of each figure of Product Part Number.
Please refer User's Manual for the actual lineup.

RX21A Group



R5 F 5 21A 8 B D FM #3 0

Renesas MCU
ROM Type F: Flash
RX200 Series

Product Group

21A	RX21A
-----	-------

ROM/RAM/Data flash Size

8	512KB	64KB	8KB
7	384KB	64KB	8KB
6	256KB	32KB	8KB

Production Identification code

Terminal specification

U,V,3	Tray (Bulk)
1	Tray (Full carton)

Package, pin count and pin pitch

FP	LFQFP	100	0.50 mm
FN	LFQFP	80	0.50 mm
FM	LFQFP	64	0.50 mm
LJ	TFLGA	100	0.65 mm

Temperature

D	Ta = -40°C to 85°C
G	Ta = -40°C to 105°C

Example shown here:

RX21A (64-pin), Part number R5F521A8BDFM#30

This guide shows the meanings of each figure of Product Part Number.
Please refer User's Manual for the actual lineup.

RX220 Group



R5 F 5 220 6 B D FP #3 0

Renesas MCU
ROM Type F: Flash
RX200 Series

Product Group

220	RX220
-----	-------

ROM/RAM/Data flash Size

6	256KB	16KB	8KB
5	128KB	8KB	8KB
3	64KB	8KB	8KB
1	32KB	4KB	8KB

Production Identification code

Terminal specification

V,3	Tray (Bulk)
1	Tray (Full carton)
5	Tape and reel

Package, pin count and pin pitch

FP	LFQFP	100	0.50 mm
FM	LFQFP	64	0.50 mm
FL	LFQFP	48	0.50 mm
FK	LQFP	64	0.80 mm

Temperature

D	Ta = -40°C to 85°C
G	Ta = -40°C to 105°C

Example shown here:

RX220 (100-pin), Part number R5F52206BDFP#30

This guide shows the meanings of each figure of Product Part Number.
Please refer User's Manual for the actual lineup.

RX230 Group



R5 F 5 230 6 A D FM #3 0

Renesas MCU
ROM Type F: Flash
RX200 Series

Product Group

230	RX230
-----	-------

ROM/RAM/Data flash Size

6	256KB	32KB	8KB
5	128KB	32KB	8KB

Production Identification code

Terminal specification

U,2,3	Tray (Bulk)
0,1	Tray (Full carton)
5	Tape and reel

Package, pin count and pin pitch

FP	LFQFP	100	0.50 mm
FM	LFQFP	64	0.50 mm
FL	LFQFP	48	0.50 mm
LA	TFLGA	100	0.50 mm
LF	WFLGA	64	0.50 mm
ND	HWQFN	64	0.50 mm
NE	HWQFN	48	0.50 mm

Temperature

D	Ta = -40°C to 85°C
G	Ta = -40°C to 105°C

Example shown here:
RX230 (64-pin), Part number R5F52306ADFM#30

This guide shows the meanings of each figure of Product Part Number.
Please refer User's Manual for the actual lineup.

RX231 Group



R5 F 5 231 8 A D FM #3 0

Renesas MCU
ROM Type F: Flash
RX200 Series

Product Group

231	RX231
-----	-------

ROM/RAM/Data flash Size

8	512KB	64KB	8KB
7	384KB	64KB	8KB
6	256KB	32KB	8KB
5	128KB	32KB	8KB

Encryption / SDHI / CAN Support

A	No	No	Yes
B	Yes	Yes	Yes
C	No	No	No

Production Identification code

Terminal specification

U,2,3	Tray (Bulk)
0,1	Tray (Full carton)
5	Tape and reel

Package, pin count and pin pitch

FP	LFQFP	100	0.50 mm
FM	LFQFP	64	0.50 mm
FL	LFQFP	48	0.50 mm
LA	TFLGA	100	0.50 mm
LF	WFLGA	64	0.50 mm
ND	HWQFN	64	0.50 mm
NE	HWQFN	48	0.50 mm

Temperature

D	Ta = -40°C to 85°C
G	Ta = -40°C to 105°C

Example shown here:

RX231 (64-pin), Part number R5F52318ADFM#30

This guide shows the meanings of each figure of Product Part Number.
Please refer User's Manual for the actual lineup.

RX23E-A Group



R5 F 5 23E 6 A D FL #3 0

Renesas MCU ROM Type F: Flash RX200 Series

Product Group

23E	RX23E
-----	-------

ROM/RAM/Data flash Size

6	256KB	32KB	8KB
5	128KB	16KB	8KB

Sensor(DSAD)

A	2 unit
S	1 unit

Production Identification code

Terminal specification

2,3	Tray (Bulk)
1	Tray (Full carton)
4,5	Tape and reel

Package, pin count and pin pitch

FL	LFQFP	48	0.50 mm
NF	HWQFN	40	0.50 mm

Temperature

D	Ta = -40°C to 85°C
G	Ta = -40°C to 105°C

Example shown here:

RX23E-A (48-pin), Part number R5F523E6ADFL#30

This guide shows the meanings of each figure of Product Part Number.
Please refer User's Manual for the actual lineup.

RX23E-B Group



R5 F 5 23E 6 A D FL #3 0

Renesas MCU ROM Type F: Flash RX200 Series

Product Group

23E	RX23E
-----	-------

ROM/RAM/Data flash Size

6	256KB	32KB	8KB
5	128KB	16KB	8KB

24bit $\Delta\Sigma$ AD sampling rate / Analog input range / LCD support

B	125Ksps	5V	No
J	125Ksps	5V	Yes
K	125Ksps	10V	No
L	125Ksps	10V	Yes
M	31.25Ksps	5V	No
N	31.25Ksps	5V	Yes

Example shown here:

RX23E-B (40-pin), Part number R5F523E6BDNF#30

Production Identification code

Terminal specification

2,3	Tray (Bulk)
0,1	Tray (Full carton)
4,5	Tape and reel

Package, pin count and pin pitch

BS	TFBGA	100	0.50 mm
FP	LFQFP	100	0.50 mm
FN	LFQFP	80	0.50 mm
FM	LFQFP	64	0.50 mm
FL	LFQFP	48	0.50 mm
NF	HWQFN	40	0.50 mm

Temperature

D	Ta = -40°C to 85°C
G	Ta = -40°C to 105°C

This guide shows the meanings of each figure of Product Part Number.
Please refer User's Manual for the actual lineup.

RX23T Group



R5 F 5 23T 5 A D FM #3 0

Renesas
MCU

ROM Type
F: Flash

RX200
Series

Product Group

23T

RX23T

ROM/RAM Size

5	128KB	12KB
3	64KB	12KB

Operation voltage

A

5V

Production Identification code

Terminal specification

3

Tray (Bulk)

1

Tray (Full carton)

Package, pin count and pin pitch

FM	LFQFP	64	0.50 mm
FL	LFQFP	48	0.50 mm
FD	LQFP	52	0.65 mm

Temperature

D

Ta = -40°C to 85°C

G

Ta = -40°C to 105°C

Example shown here:

RX23T (64-pin), Part number R5F523T5ADFM#30

This guide shows the meanings of each figure of Product Part Number.
Please refer User's Manual for the actual lineup.

RX23W Group



R5 F 5 23W 8 A D BL #3 0

Renesas MCU ROM Type F: Flash RX200 Series

Product Group

23W	RX23W
-----	-------

ROM/RAM/Data flash Size

8	512KB	64KB	8KB
7	384KB	64KB	8KB

Encryption Support / antenna support

A	No	No
B	Yes	No
C	No	Yes
D	Yes	Yes

Production Identification code

Terminal specification

U,2,3	Tray (Bulk)
-------	-------------

Package, pin count and pin pitch

BL	TFBGA	85	0.50 mm
LN	TFLGA	83	0.50 mm
NG	HVQFN	56	0.40 mm

Temperature

D	Ta = -40°C to 85°C
---	--------------------

Example shown here:

RX23W (85-pin), Part number R5F523W8ADBL#30

This guide shows the meanings of each figure of Product Part Number.
Please refer User's Manual for the actual lineup.

RX24T Group



R5 F 5 24T A A D FP #3 0

Renesas MCU
ROM Type F: Flash
RX200 Series

Product Group

24T	RX24T
-----	-------

ROM/RAM/Data flash Size

E	512KB	32KB	8KB
C	384KB	32KB	8KB
B	256KB	32KB	8KB
A	256KB	16KB	8KB
8	128KB	16KB	8KB

Operation voltage

A	5V
---	----

Production Identification code

Terminal specification

3	Tray (Bulk)
1	Tray (Full carton)
5	Tape and reel

Package, pin count and pin pitch

FP	LFQFP	100	0.50 mm
FF	LQFP	80	0.65 mm
FN	LFQFP	80	0.50 mm
FM	LFQFP	64	0.50 mm
FK	LQFP	64	0.8 mm

Temperature

D	Ta = -40°C to 85°C
---	--------------------

Example shown here:

RX24T (100-pin), Part number R5F524TAADFP#30

This guide shows the meanings of each figure of Product Part Number.
Please refer User's Manual for the actual lineup.

RX24U Group



R5 F 5 24U E A D FB #3 0

Renesas MCU
ROM Type F: Flash
RX200 Series

Product Group

24U	RX24U
-----	-------

ROM/RAM/Data flash Size

E	512KB	32KB	8KB
C	384KB	32KB	8KB
B	256KB	32KB	8KB

Operation voltage

A	5V
---	----

Production Identification code

Terminal specification

3	Tray (Bulk)
1	Tray (Full carton)

Package, pin count and pin pitch

FB	LFQFP	144	0.50 mm
FP	LFQFP	100	0.50 mm

Temperature

D	Ta = -40°C to 85°C
---	--------------------

Example shown here:

RX24U (144-pin), Part number R5F524UEADFB#30

This guide shows the meanings of each figure of Product Part Number.
Please refer User's Manual for the actual lineup.

RX260 Group



R5 F 5 260 8 A D FP #3 0

Renesas MCU
ROM Type F: Flash
RX200 Series

Product Group

260	RX260
-----	-------

ROM/RAM/Data flash Size

8	512KB	128KB	8KB
7	384KB	128KB	8KB
6	256KB	128KB	8KB

Encryption / USB / CAN FD Support

A	No	No	No
---	----	----	----

Production Identification code

Terminal specification

1	Tray (Full carton)
5	Tape and reel

Package, pin count and pin pitch

FP	LFQFP	100	0.50 mm
FN	LFQFP	80	0.50 mm
FM	LFQFP	64	0.50 mm
FL	LFQFP	48	0.50 mm
NE	HWQFN	48	0.50 mm

Temperature

D	Ta = -40°C to 85°C
G	Ta = -40°C to 105°C

Example shown here:

RX260 (100-pin), Part number R5F52608ADFP#30

This guide shows the meanings of each figure of Product Part Number.
Please refer User's Manual for the actual lineup.

RX261 Group



R5 F 5 261 8 A D FP #3 0

Renesas MCU
ROM Type F: Flash
RX200 Series

Product Group

261	RX261
-----	-------

ROM/RAM/Data flash Size

8	512KB	128KB	8KB
7	384KB	128KB	8KB
6	256KB	128KB	8KB

Encryption / USB / CAN FD Support

A	No	Yes	Yes
B	Yes	Yes	Yes

Production Identification code

Terminal specification

1	Tray (Full carton)
7	Tray (Full Tray)
5	Tape and reel

Package, pin count and pin pitch

FP	LFQFP	100	0.50 mm
FN	LFQFP	80	0.50 mm
FM	LFQFP	64	0.50 mm
FL	LFQFP	48	0.50 mm
NE	HWQFN	48	0.50 mm

Temperature

D	Ta = -40°C to 85°C
G	Ta = -40°C to 105°C

Example shown here:

RX261 (100-pin), Part number R5F52618ADFP#30

This guide shows the meanings of each figure of Product Part Number.
Please refer User's Manual for the actual lineup.

RX26T Group



R5 F 5 26T E A D F P #3 0

Renesas MCU
ROM Type F: Flash
RX200 Series

Product Group

26T	RX26T
-----	-------

ROM/RAM/Data flash Size

F	512KB	64KB	16KB
B	256KB	64KB	16KB
A	256KB	48KB	16KB
9	128KB	64KB	16KB
8	128KB	48KB	16KB

CAN FD, TSIP-Lite

A	No	No
B	No	Yes
C	Yes	No
E	Yes	Yes

Production Identification code

Terminal specification

3	Tray (Bulk)
1	Tray (Full carton)
5	Tape and reel

Package, pin count and pin pitch

FP	LFQFP	100	0.50 mm
FN	LFQFP	80	0.50 mm
FM	LFQFP	64	0.50 mm
FL	LFQFP	48	0.50 mm
ND	HWQFN	64	0.50 mm
NE	HWQFN	48	0.50 mm
NH	HWQFN	32	0.50 mm

Temperature

D	Ta = -40°C to 85°C
G	Ta = -40°C to 105°C

Example shown here:

RX26T (100-pin), Part number R5F526TEADFP#30

This guide shows the meanings of each figure of Product Part Number.
Please refer User's Manual for the actual lineup.

RX621 Group



R5 F 5 621 7 B D B G #U 0

Renesas MCU
ROM Type F: Flash
RX600 Series

Product Group

621	RX621
-----	-------

ROM/RAM/Data flash Size

8	512KB	96KB	32KB
7	384KB	64KB	32KB
6	256KB	64KB	32KB

CAN Support

A	No
B	Yes

Production Identification code

Terminal specification

U,V	Tray (Bulk)
0,1	Tray (Full carton)

Package, pin count and pin pitch

FB	LFQFP	144	0.50 mm
FP	LFQFP	100	0.50 mm
LE	TFLGA	145	0.65 mm
LD	TFLGA	85	0.65 mm
BG	LFBGA	176	0.80 mm

Temperature

D	Ta = -40°C to 85°C
---	--------------------

Example shown here:

RX621 (176-pin), Part number R5F56217BDBG#U0

This guide shows the meanings of each figure of Product Part Number.
Please refer User's Manual for the actual lineup.

RX62G Group



R5 F 5 62G A B D FH #V 3

Renesas MCU ROM Type F: Flash RX600 Series

Product Group

62G	RX62G
-----	-------

ROM/RAM/Data flash Size

A	256KB	16KB	32KB
7	128KB	8KB	8KB

Operation voltage, CAN Support

A	5V	Yes
D	5V	No

Production Identification code

Terminal specification

V	Tray (Bulk)
1	Tray (Full carton)

Package, pin count and pin pitch

FP	LFQFP	100	0.50 mm
FH	LQFP	112	0.65 mm

Temperature

D	Ta = -40°C to 85°C
G	Ta = -40°C to 105°C

Example shown here:

RX62G (112-pin), Part number R5F562GABDFH#V3

This guide shows the meanings of each figure of Product Part Number.
Please refer User's Manual for the actual lineup.

RX62N Group



R5 F 5 62N 7 B D B G #U 0

Renesas MCU
ROM Type F: Flash
RX600 Series

Product Group

62N	RX62N
-----	-------

ROM/RAM/Data flash Size

8	512KB	96KB	32KB
7	384KB	64KB	32KB

CAN Support

A	No
B	Yes

Production Identification code

Terminal specification

U,V	Tray (Bulk)
0,1	Tray (Full carton)

Package, pin count and pin pitch

FB	LFQFP	144	0.50 mm
FP	LFQFP	100	0.50 mm
LE	TFLGA	145	0.65 mm
BG	LFBGA	176	0.80 mm

Temperature

D	Ta = -40°C to 85°C
---	--------------------

Example shown here:

RX62N (176-pin), Part number R5F562N7BDBG#U0

This guide shows the meanings of each figure of Product Part Number.
Please refer User's Manual for the actual lineup.

RX62T Group



R5 F 5 62T A B D FH #V 3

Renesas MCU
ROM Type F: Flash
RX600 Series

Product Group

62T	RX62T
-----	-------

ROM/RAM/Data flash Size

A	256KB	16KB	32KB
7	128KB	8KB	8KB
6	64KB	8KB	8KB

Operation voltage, CAN Support

A	5V	Yes
B	3V	Yes
D	5V	No
E	3V	No

Production Identification code

Terminal specification

V	Tray (Bulk)
H,1	Tray (Full carton)

Package, pin count and pin pitch

FP	LFQFP	100	0.50 mm
FM	LFQFP	64	0.50 mm
FH	LQFP	112	0.65 mm
FF	LQFP	80	0.65 mm
FK	LQFP	64	0.80 mm

Temperature

D	Ta = -40°C to 85°C
G	Ta = -40°C to 105°C

Example shown here:

RX62T (112-pin), Part number R5F562TABDFH#V3

This guide shows the meanings of each figure of Product Part Number.
Please refer User's Manual for the actual lineup.

RX630 Group



R5 F 5 630 7 C D FN #V 0

Renesas MCU
ROM Type F: Flash
RX600 Series

Product Group

630	RX630
-----	-------

ROM/RAM/Data flash Size

E	2MB	128KB	32KB	A	786KB	96KB	32KB
D	1.5MB	128KB	32KB	8	512KB	64KB	32KB
B	1MB	96KB	32KB	7	384KB	64KB	32KB

CAN Support

C	No
D	Yes

Production Identification code

Terminal specification

U,V	Tray (Bulk)
1	Tray (Full carton)

Package, pin count and pin pitch

FC	LFQFP	176	0.50 mm	LC	TFLGA	177	0.50 mm
FB	LFQFP	144	0.50 mm	LK	TFLGA	145	0.50 mm
FP	LFQFP	100	0.50 mm	LA	TFLGA	100	0.50 mm
FN	LFQFP	80	0.50 mm	BG	LFBGA	176	0.80 mm

Temperature

D	Ta = -40°C to 85°C
G	Ta = -40°C to 105°C

Example shown here:

RX630 (80-pin), Part number R5F56307CDFN#V0

This guide shows the meanings of each figure of Product Part Number.
Please refer User's Manual for the actual lineup.

RX631 Group



R5 F 5 631 A C D F P #V 0

Renesas MCU
ROM Type
 F: Flash
 S: Rom Less

RX600 Series

Product Group

631	RX631
-----	-------

ROM/RAM/Data flash Size

F	2MB	256KB	32KB	6	256KB	128KB	32KB
K	2MB	192KB	32KB	P	512KB	64KB	32KB
E	2MB	128KB	32KB	N	384KB	64KB	32KB
J	1.5MB	256KB	32KB	M	256KB	64KB	32KB
G	1.5MB	192KB	32KB	0	0KB	128KB	0KB
D	1.5MB	128KB	32KB				
Y	1MB	256KB	32KB				
W	1MB	192KB	32KB				
B	1MB	128KB	32KB				
A	786KB	128KB	32KB				
8	512KB	128KB	32KB				
7	384KB	128KB	32KB				

CAN, DEU, PDC Support

H	Yes	Yes	No
D	Yes	No	No
C	No	No	No
S	Yes	No	Yes
F*	Yes	No	No

*64pin TFLGA only

Production Identification code

Terminal specification

U,V	Tray (Bulk)
1	Tray (Full carton)

Package, pin count and pin pitch

FC	LFQFP	176	0.50 mm	BG	LFBGA	176	0.80 mm
FB	LFQFP	144	0.50 mm	LC	TFLGA	177	0.50 mm
FP	LFQFP	100	0.50 mm	LK	TFLGA	145	0.50 mm
FM	LFQFP	64	0.50 mm	LJ	TFLGA	100	0.65 mm
FL	LFQFP	48	0.50 mm	LH	TFLGA	64	0.65 mm

Temperature

D	Ta = -40°C to 85°C
G	Ta = -40°C to 105°C

Example shown here:

RX631 (100-pin), Part number R5F5631ACDFP#V0

This guide shows the meanings of each figure of Product Part Number.
 Please refer User's Manual for the actual lineup.

RX634 Group



R5 F 5 634 E Y D FB #3 0

Renesas MCU
ROM Type F: Flash
RX600 Series

Product Group

634	RX634
-----	-------

ROM/RAM/Data flash Size

E	2MB	128KB	32KB
D	1.5MB	128KB	32KB
B	1MB	128KB	32KB

Operation voltage

Y	5V
C	3V

Production Identification code

Terminal specification

3	Tray (Bulk)
1	Tray (Full carton)

Package, pin count and pin pitch

FB	LFQFP	144	0.50 mm
----	-------	-----	---------

Temperature

D	Ta = -40°C to 85°C
---	--------------------

Example shown here:

RX634 (144-pin), Part number R5F5634EYDFB#30

This guide shows the meanings of each figure of Product Part Number.
Please refer User's Manual for the actual lineup.

RX63N Group



R5 F 5 63N A C D FP #V 0

Renesas MCU
ROM Type F: Flash
RX600 Series

Product Group

63N	RX63N
-----	-------

ROM/RAM/Data flash Size

F	2MB	256KB	32KB	Y	1MB	256KB	32KB
K	2MB	192KB	32KB	W	1MB	192KB	32KB
E	2MB	128KB	32KB	B	1MB	128KB	32KB
D	1.5MB	128KB	32KB	A	786KB	128KB	32KB

CAN, DEU Support

H	Yes	Yes
D	Yes	No
C	No	No

Production Identification code

Terminal specification

U,V	Tray (Bulk)
1	Tray (Full carton)

Package, pin count and pin pitch

FC	LFQFP	176	0.50 mm	BG	LFBGA	176	0.80 mm
FB	LFQFP	144	0.50 mm	LC	TFLGA	177	0.50 mm
FP	LFQFP	100	0.50 mm	LK	TFLGA	145	0.50 mm
				LJ	TFLGA	100	0.65 mm

Temperature

D	Ta = -40°C to 85°C
G	Ta = -40°C to 105°C

Example shown here:

RX63N (100-pin), Part number R5F563NACDFP#V0

This guide shows the meanings of each figure of Product Part Number.
Please refer User's Manual for the actual lineup.

RX63T Group



R5 F 5 63T E A D FB #V 1

Renesas MCU ROM Type F: Flash RX600 Series

Product Group

63T	RX63T
-----	-------

ROM/RAM/Data flash Size

E	512KB	48KB	32KB	6	64KB	8KB	8KB
C	384KB	32KB	32KB	5	48KB	8KB	8KB
B	256KB	24KB	32KB	4	32KB	8KB	8KB

Operation voltage, CAN Support

A	5V	Yes
B	3V	Yes
D	5V	No
E	3V	No

Production Identification code

Terminal specification

V	Tray (Bulk)
H,1	Tray (Full carton)

Package, pin count and pin pitch

FB	LFQFP	144	0.50 mm
FA	LFQFP	120	0.50 mm
FP	LFQFP	100	0.50 mm
FM	LFQFP	64	0.50 mm
FL	LFQFP	48	0.50 mm
FH	LQFP	112	0.65 mm

Temperature

D	Ta = -40°C to 85°C
G	Ta = -40°C to 105°C

Example shown here:

RX63T (144-pin), Part number R5F563TEADFB#V1

This guide shows the meanings of each figure of Product Part Number.
Please refer User's Manual for the actual lineup.

RX64M Group



R5 F 5 64M L C D FC #3 1

Renesas MCU
ROM Type F: Flash
RX600 Series

Product Group

64M	RX64M
-----	-------

ROM/RAM/Data flash Size

L	4MB	512KB	64KB
J	3MB	512KB	64KB
G	2.5MB	512KB	64KB
F	2KB	512KB	64KB

Encryption, SDHI Support

D	No	Yes
H	Yes	Yes
C	No	No
G	Yes	No

Production Identification code

Terminal specification

V,2,3	Tray (Bulk)
1	Tray (Full carton)

Package, pin count and pin pitch

FC	LFQFP	176	0.50 mm
FB	LFQFP	144	0.50 mm
FP	LFQFP	100	0.50 mm
LC	TFLGA	177	0.50 mm
LK	TFLGA	145	0.50 mm
LJ	TFLGA	100	0.65 mm
BG	LFBGA	176	0.80 mm

Temperature

D	Ta = -40°C to 85°C
G	Ta = -40°C to 105°C

Example shown here:

RX64M (176-pin), Part number R5F564MLCDFC#31

This guide shows the meanings of each figure of Product Part Number.
Please refer User's Manual for the actual lineup.

RX651 Group



R5 F 5 651 9 A D FB #3 1

Renesas MCU
ROM Type F: Flash
RX600 Series

Product Group

64M	RX651
-----	-------

ROM/RAM/Data flash Size

E	2MB	640KB	32KB
C	1.5MB	640KB	32KB
9	1MB	256KB	-
7	768KB	256KB	-
4	512KB	256KB	-

Encryption, SDHI/SDSI, Dual Bank Support

A	No	No	No
B	No	Yes	No
D	No	Yes	Yes
E	Yes	No	No
F	Yes	Yes	No
H	Yes	Yes	Yes

Example shown here:

RX651 (144-pin), Part number R5F56519ADFB#31

Production Identification code

Terminal specification

V,2,3	Tray (Bulk)
1	Tray (Full carton)

Package, pin count and pin pitch

FC	LFQFP	176	0.50 mm	FM	LFQFP	64	0.50 mm
BG	LFBGA	176	0.80 mm	BP	TFBGA	64	0.50 mm
LC	TFLGA	177	0.50 mm				
FB	LFQFP	144	0.50 mm				
LK	TFLGA	145	0.50 mm				
FP	LFQFP	100	0.50 mm				
LJ	TFLGA	100	0.65 mm				

Temperature

D	Ta = -40°C to 85°C
G	Ta = -40°C to 105°C

This guide shows the meanings of each figure of Product Part Number.
Please refer User's Manual for the actual lineup.

RX65N Group



R5 F 5 65N 9 A D FB #3 1

Renesas MCU ROM Type F: Flash RX600 Series

Product Group

64M	RX65N
-----	-------

ROM/RAM/Data flash Size

E	2MB	640KB	32KB
C	1.5MB	640KB	32KB
9	1MB	256KB	-
7	768KB	256KB	-
4	512KB	256KB	-

Encryption, SDHI/SDSI, Dual Bank Support

A	No	No	No
B	No	Yes	No
D	No	Yes	Yes
E	Yes	No	No
F	Yes	Yes	No
H	Yes	Yes	Yes

Example shown here:

RX65N (144-pin), Part number R5F565N9ADFB#31

Production Identification code

Terminal specification

V,2,3	Tray (Bulk)
1	Tray (Full carton)

Package, pin count and pin pitch

FC	LFQFP	176	0.50 mm
BG	LFBGA	176	0.80 mm
LC	TFLGA	177	0.50 mm
FB	LFQFP	144	0.50 mm
LK	TFLGA	145	0.50 mm
FP	LFQFP	100	0.50 mm
LJ	TFLGA	100	0.65 mm

Temperature

D	Ta = -40°C to 85°C
G	Ta = -40°C to 105°C

This guide shows the meanings of each figure of Product Part Number.
Please refer User's Manual for the actual lineup.

RX65W-A Group



R5 F 5 65W E A D B F #2 0

Renesas MCU ROM Type F: Flash RX600 Series

Product Group

65W RX65W-A

ROM/RAM/Data flash Size

E	2MB	640KB	32KB
---	-----	-------	------

Encryption, EtherC, SDHI/SDSI Support

A	Yes	Yes	Yes
M	No	No	No

Production Identification code

Terminal specification

2 Tray (Bulk)

Package, pin count and pin pitch

BF	TGBGA	145	0.50 mm
----	-------	-----	---------

Temperature

D Ta = -40°C to 85°C

Example shown here:

RX65W (145-pin), Part number R5F565WEADB F#20

This guide shows the meanings of each figure of Product Part Number.
Please refer User's Manual for the actual lineup.

RX660 Group



R5 F 5 660 9 A D FB #3 0

Renesas MCU
ROM Type F: Flash
RX600 Series

Product Group

66N	RX660
-----	-------

ROM/RAM/Data flash Size

9	1MB	128KB	32KB
4	512KB	128KB	32KB

JTAG, Sub-Clock, CAN-FD

A	No	No	No*	F	Yes	No	Yes
B	No	No	Yes	G	Yes	Yes	No*
C	No	Yes	No*	H	Yes	Yes	Yes
D	No	Yes	Yes				
E	Yes	No	No*				

*CAN2.0 is support

Production Identification code

Terminal specification

3	Tray (Bulk)
1	Tray (Full carton)

Package, pin count and pin pitch

FB	LFQFP	144	0.50 mm
FP	LFQFP	100	0.50 mm
FN	LFQFP	80	0.50 mm
FM	LFQFP	64	0.50 mm
FL	LFQFP	48	0.50 mm

Temperature

D	Ta = -40°C to 85°C
G	Ta = -40°C to 105°C

Example shown here:

RX660 (144-pin), Part number R5F56609ADFB#30

This guide shows the meanings of each figure of Product Part Number.
Please refer User's Manual for the actual lineup.

RX66N Group



R5 F 5 66N N D D BD #V 0

Renesas MCU
ROM Type F: Flash
RX600 Series

Product Group

66N	RX66N
-----	-------

ROM/RAM/Data flash Size

N	4MB	1MB	32KB
D	2MB	1MB	32KB

Encryption

D	No
H	Yes

Production Identification code

Terminal specification

V,2,3	Tray (Bulk)
1	Tray (Full carton)

Package, pin count and pin pitch

BD	LFBGA	224	0.80 mm
BG	LFBGA	176	0.80 mm
FB	LFQFP	144	0.50 mm
FC	LFQFP	176	0.50 mm
FP	LFQFP	100	0.50 mm
LK	TFLGA	145	0.50 mm

Temperature

D	Ta = -40°C to 85°C
G	Ta = -40°C to 105°C

Example shown here:

RX66N (224-pin), Part number R5F566NNDDBD#V0

This guide shows the meanings of each figure of Product Part Number.
Please refer User's Manual for the actual lineup.

RX66T Group



R5 F 5 66T E A D FB #3 1

Renesas MCU ROM Type F: Flash RX600 Series

Product Group

66T	RX66T
-----	-------

ROM/RAM/Data flash Size

K	1MB	128KB	32KB
F	512KB	128KB	32KB
E	512KB	64KB	32KB
A	256KB	64KB	32KB

PGA, Encryption, USB

A	Yes	No	No
B	No	No	No
C	Yes	No	Yes
E	Yes	Yes	No
F	No	Yes	No
G	Yes	Yes	Yes

Example shown here:

RX66T (144-pin), Part number R5F566TEADFB#31

Production Identification code

Terminal specification

3	Tray (Bulk)
1	Tray (Full carton)

Package, pin count and pin pitch

FB	LFQFP	144	0.50 mm
FH	LQFP	112	0.65 mm
FP	LFQFP	100	0.50 mm
FF	LQFP	80	0.65 mm
FN	LFQFP	80	0.50 mm
FM	LFQFP	64	0.50 mm
FL	LFQFP	48	0.50 mm

Temperature

D	Ta = -40°C to 85°C
G	Ta = -40°C to 105°C

This guide shows the meanings of each figure of Product Part Number.
Please refer User's Manual for the actual lineup.

RX671 Group



R5 F 5 671 E D D FB #1 0

Renesas MCU
ROM Type F: Flash
RX600 Series

Product Group

671	RX671
-----	-------

ROM/RAM/Data flash Size

E	2MB	384KB	8KB
C	1.5MB	384KB	8KB
9	1MB	384KB	8KB

Encryption

D	No
H	Yes

Production Identification code

Terminal specification

2,3	Tray (Bulk)
1	Tray (Full carton)

Package, pin count and pin pitch

LE	TFLGA	145	0.65 mm	NE	HWQFN	48	0.50 mm
LK	TFLGA	145	0.50 mm				
FB	LFQFP	144	0.50 mm				
FP	LFQFP	100	0.50 mm				
LJ	TFLGA	100	0.65 mm				
FM	LFQFP	64	0.50 mm				
BP	TFBGA	64	0.50 mm				

Temperature

D	Ta = -40°C to 85°C
G	Ta = -40°C to 105°C

Example shown here:

RX671 (144-pin), Part number R5F5671EDDFB#10

This guide shows the meanings of each figure of Product Part Number.
Please refer User's Manual for the actual lineup.

RX71M Group



R5 F 5 71M L C D FC #V 0

Renesas MCU
ROM Type F: Flash
RX700 Series

Product Group

71M	RX71M
-----	-------

ROM/RAM/Data flash Size

L	4MB	512KB	64KB
J	3MB	512KB	64KB
G	2.5MB	512KB	64KB
F	2KB	512KB	64KB

Encryption, SDHI Support

D	No	Yes
H	Yes	Yes
C	No	No
G	Yes	No

Production Identification code

Terminal specification

V,2,3	Tray (Bulk)
1	Tray (Full carton)

Package, pin count and pin pitch

FC	LFQFP	176	0.50 mm
FB	LFQFP	144	0.50 mm
FP	LFQFP	100	0.50 mm
LC	TFLGA	177	0.50 mm
LK	TFLGA	145	0.50 mm
LJ	TFLGA	100	0.65 mm
BG	LFBGA	176	0.80 mm

Temperature

D	Ta = -40°C to 85°C
G	Ta = -40°C to 105°C

Example shown here:

RX71M (176-pin), Part number R5F571MLCDFC#V0

This guide shows the meanings of each figure of Product Part Number.
Please refer User's Manual for the actual lineup.

RX72M Group



R5 F 5 72M N D D FC #3 1

Renesas MCU
ROM Type F: Flash
RX700 Series

Product Group

72M	RX72M
-----	-------

ROM/RAM/Data flash Size

N	4MB	1MB	32KB
D	2MB	1MB	32KB

Encryption

D	No
H	Yes

Production Identification code

Terminal specification

V,2,3	Tray (Bulk)
1	Tray (Full carton)

Package, pin count and pin pitch

BD	LFBGA	224	0.85 mm
BG	LFBGA	176	0.80 mm
FC	LFQFP	176	0.50 mm
FB	LFQFP	144	0.50 mm
FP	LFQFP	100	0.50 mm

Temperature

D	Ta = -40°C to 85°C
G	Ta = -40°C to 105°C

Example shown here:

RX72M (176-pin), Part number R5F572MNDDFC#31

This guide shows the meanings of each figure of Product Part Number.
Please refer User's Manual for the actual lineup.

RX72N Group



R5 F 5 72N N D D BD #V 0

Renesas MCU ROM Type F: Flash RX700 Series

Product Group

72N	RX72N
-----	-------

ROM/RAM/Data flash Size

N	4MB	1MB	32KB
D	2MB	1MB	32KB

Encryption

D	No
H	Yes

Production Identification code

Terminal specification

V,2,3	Tray (Bulk)
1	Tray (Full carton)

Package, pin count and pin pitch

BD	LFBGA	224	0.80 mm
BG	LFBGA	176	0.80 mm
FB	LFQFP	144	0.50 mm
FC	LFQFP	176	0.50 mm
FP	LFQFP	100	0.50 mm
LK	TFLGA	145	0.50 mm

Temperature

D	Ta = -40°C to 85°C
G	Ta = -40°C to 105°C

Example shown here:

RX72N (224-pin), Part number R5F572NNDDBD#V0

This guide shows the meanings of each figure of Product Part Number.
Please refer User's Manual for the actual lineup.

RX72T Group



R5 F 5 72T E A D FB #3 1

Renesas MCU ROM Type F: Flash RX700 Series

Product Group

72T	RX72T
-----	-------

ROM/RAM/Data flash Size

K	1MB	128KB	32KB
F	512KB	128KB	32KB

PGA, Encryption, USB

A	Yes	No	No
B	No	No	No
C	Yes	No	Yes
E	Yes	Yes	No
F	No	Yes	No
G	Yes	Yes	Yes

Production Identification code

Terminal specification

3	Tray (Bulk)
1	Tray (Full carton)

Package, pin count and pin pitch

FB	LFQFP	144	0.50 mm
FP	LFQFP	100	0.50 mm

Temperature

D	Ta = -40°C to 85°C
G	Ta = -40°C to 105°C

Example shown here:

RX72T (144-pin), Part number R5F572TEADFB#31

This guide shows the meanings of each figure of Product Part Number.
Please refer User's Manual for the actual lineup.

RX74M Group



R5 K 5 74M C A 4 FC #60

Renesas MCU ROM Type K: MRAM RX700 Series

Product Group

74M	RX74M
-----	-------

Code MRAM/RAM/Data MRAM

C	1MB	1.5MB	48KB
6	512KB	1.5MB	48KB

ICLK(MHz),CAN FD, ESC

A	600	No*	Yes	F	300	Yes	Yes
B	600	Yes	Yes	T	600	No*	No
C	480	No*	Yes	U	600	Yes	No
D	480	Yes	Yes	V	480	No*	No
E	300	No*	Yes	W	480	Yes	No

*CAN 2.0 support only

Production Identification code

Terminal specification

6,7	Tray (Full tray)
0,1	Tray (Full carton)

Package, pin count and pin pitch

AE	LFBGA	320	0.80 mm
BD	LFBGA	224	0.80 mm
BG	LFBGA	176	0.80 mm
FC	LFQFP	176	0.50 mm
FB	LFQFP	144	0.50 mm
FP	LFQFP	100	0.50 mm

Temperature

4	Tj = -40°C to 125°C
---	---------------------

Example shown here:

RX74M (320-pin), Part number R5K574MCA4FC#60

This guide shows the meanings of each figure of Product Part Number.
Please refer User's Manual for the actual lineup.

RX74N Group



R5 K 5 74N C A 4 FC #60

Renesas MCU ROM Type K: MRAM RX700 Series

Product Group

74N	RX74N
-----	-------

Code MRAM/RAM/Data MRAM

C	1MB	1.5MB	48KB
6	512KB	1.5MB	48KB

ICLK(MHz),CAN FD

A	600	No*	F	300	Yes
B	600	Yes			
C	480	No*			
D	480	Yes			
E	300	No*			

*CAN 2.0 support only

Production Identification code

Terminal specification

6,7	Tray (Full tray)
0,1	Tray (Full carton)

Package, pin count and pin pitch

AE	LFBGA	320	0.80 mm
BD	LFBGA	224	0.80 mm
BG	LFBGA	176	0.80 mm
FC	LFQFP	176	0.50 mm
FB	LFQFP	144	0.50 mm
FP	LFQFP	100	0.50 mm

Temperature

4	Tj = -40°C to 125°C
---	---------------------

Example shown here:

RX74N (320-pin), Part number R5K574NCA4FC#60

This guide shows the meanings of each figure of Product Part Number.
Please refer User's Manual for the actual lineup.

RX610 Group



R5 F 5 610 8 V N FP #V 0

Renesas MCU
ROM Type F: Flash
RX600 Series

Product Group

610	RX610
-----	-------

ROM/RAM/Data flash Size

8	2MB	128KB	32KB
7	1.5MB	128KB	32KB
6	1MB	128KB	32KB
4	768KB	128KB	32KB

Pin Count

V	144
W	176

Production Identification code

Terminal specification

U,V Tray (Bulk)

Package, pin count and pin pitch

FP	LFQFP	144	0.50 mm
BG	LFBGA	176	0.80 mm

Temperature

N	Ta = -20°C to 85°C
D	Ta = -40°C to 85°C

Red letters: RX610 is different from RX common rules.

Example shown here:

RX610 (144-pin), Part number R5F56108VNFP#V0

This guide shows the meanings of each figure of Product Part Number.
Please refer User's Manual for the actual lineup.