



Integrated Device Technology, Inc.
2975 Stender Way, Santa Clara, CA - 95054

PRODUCT/PROCESS CHANGE NOTICE (PCN)

ATTACHMENT - PCN #: F-0403-08

Product Details

IDT Part Number

IDT7207L15D
IDT7207L15J
IDT7207L15J8
IDT7207L15P
IDT7207L20D
IDT7207L20DB
IDT7207L20J
IDT7207L20J8
IDT7207L20LB
IDT7207L20LB8
IDT7207L20P
IDT7207L25D
IDT7207L25J
IDT7207L25J8
IDT7207L25JI
IDT7207L25JI8
IDT7207L25P

IDT Part Number

IDT7207L25PI
IDT7207L30DB
IDT7207L30LB
IDT7207L30LB8
IDT7207L35D
IDT7207L35J
IDT7207L35J8
IDT7207L35P
IDT7207L50D
IDT7207L50DB
IDT7207L50J
IDT7207L50J8
IDT7207L50LB
IDT7207L50LB8
IDT7207L50P
IDT7207L25LB
IDT7207L20DB/6351

IDT Part Number

IDT7208L20J
IDT7208L20J8
IDT7208L20P
IDT7208L25J
IDT7208L25J8
IDT7208L25JI
IDT7208L25JI8
IDT7208L25P
IDT7208L25PI
IDT7208L35J
IDT7208L35J8
IDT7208L35P

Qualification Plans: QFI-03-15, QFI-03-16

Test Vehicle: IDT7207Y, IDT7208Y

Test Description/Condition	Test Methods	IDT7207Y		IDT7208Y	
		Required SS / # Fails	Required SS / # Fails	Required SS / # Fails	Expected Completion
Temperature Cycling (-65°C to +150°C, 500 cyc)	MIL-STD-883, Method 1010	45 / 0	45 / 0	45 / 0	5/1/04
Life Test (+125°C, 1000 hrs)	MIL-STD-883, Method 1005	116 / 0	116 / 0	116 / 0	5/1/04
Latch-Up Immunity (+ - I and V stress, + - 100mA Trigger)	EIA/JESD 78	10 / 0	10 / 0	10 / 0	5/1/04
ESD Human Body Model	MIL-STD-883, Method 3015	3 / 0	3 / 0	3 / 0	5/1/04
ESD Charge Device Model	JESD22-C101	3 / 0	3 / 0	3 / 0	5/1/04