



Integrated Device Technology, Inc.
2975 Stender Way, Santa Clara, CA - 95054

PRODUCT/PROCESS CHANGE NOTICE (PCN)

PCN #: **L0404-02**

DATE: 5/24/2004

Product Affected: IDT 5V2305

Date Effective: 8/24/2004

MEANS OF DISTINGUISHING CHANGED DEVICES:

☐ Product Mark

☐ Back Mark

☒ Date Code

Date Code of 0435 or later

☐ Other

Contact: Bimla Paul

Title: Product Assurance Manager

Phone #: 408-654-6419

Fax #: 408-492-8362

E-mail: bimla.paul@idt.com

Attachment: ☒ Yes

☐ No

Samples:

DESCRIPTION AND PURPOSE OF CHANGE:

☐ Die Technology

☐ Wafer Fabrication Process

☐ Assembly Process

☐ Equipment

☐ Material

☐ Testing

☐ Manufacturing Site

☒ Data Sheet

☐ Other

To revise selected timing parameters to reflect device characterization. This is a data sheet change only and does not reflect any process or product changes.

RELIABILITY/QUALIFICATION SUMMARY:

N/A

CUSTOMER ACKNOWLEDGMENT OF RECEIPT:

IDT records indicate that you require written notification of this change. Please use the acknowledgement below or E-Mail to grant approval or request additional information. If IDT does not receive acknowledgement within 30 days of this notice it will be assumed that this change is acceptable.

IDT reserves the right to ship either version manufactured after the process change effective date until the inventory on the earlier version has been depleted.

Customer: _____



Approval for shipments prior to effective date.

Name/Date: _____

E-Mail Address: _____

Title: _____

Phone# /Fax# : _____

CUSTOMER COMMENTS: _____

IDT ACKNOWLEDGMENT OF RECEIPT:

RECD. BY: _____

DATE: _____



Integrated Device Technology, Inc.
2975 Stender Way, Santa Clara, CA - 95054

PRODUCT/PROCESS CHANGE NOTICE (PCN)

ATTACHMENT - PCN #: L0404-02

PCN Type: Data Sheet

Data Sheet Change: Yes

Detail of Change:

OPERATION	DATA SHEET PARAMETER	OLD VALUE	NEW VALUE
3.3 V	pg 5 Tsk(o) - Output Skew, Yx to Yx	50ps	75ps
	pg 5 Tsk(p) - Pulse Skew	300ps	200ps
	pg 5 Tr - Rise Time	0.7 - 2. V/ns	0.7 - 2.3 V/ns
	pg 5 Tf - Fall Time	0.7 - 2. V/ns	0.7 - 2.3 V/ns
2.5V	pg 5 Tplh and Tphl - CLK to Yx	1.5 - 3.5 ns	1.5 - 3.0 ns
	pg 5 Tsk(o) - Output Skew, Yx to Yx	75ps	100ps
	pg 5 Tsk(p) - Pulse Skew	700ps	350ps
	pg 5 Tr - Rise Time	0.4 - 1.4 V/ns	0.4 - 1.625 V/ns
	pg 5 Tf - Fall Time	0.4 - 1.4 V/ns	0.4 - 1.625 V/ns