PRODUCT CHANGE NOTICE

Product Improvement – Material Change for the Listed Intersil QFN Packaged Products

Refer to: PCN14057

Date: November 26, 2014



November 26, 2014

To: Our Valued Intersil Customer

Subject: Product Improvement – Material Change for the Listed Intersil QFN Packaged Products

This notice is to inform you that Intersil has qualified a change that standardizes materials and the assembly process for the listed QFN (Quad Flat No-Lead) packaged products. The change implements the use of a higher quality mold compound (old: EG-100LA; new: G770HJ), which eliminates the need for under fill in the product. The change is necessary to maintain product manufacturability in support of customer delivery requirements.

Products affected:

ISL8200AMIRZ	ISL8200MIRZ-T	ISL8204MIRZ	ZL9117MAIRZ-T
ISL8200AMIRZ-T	ISL8200MIRZ-TR5545	ISL8204MIRZ-T	ZL9117MIRZ
ISL8200AMMREP	ISL8200MIRZ-TS2751	ISL8206MIRZ	ZL9117MIRZR5494
ISL8200AMMREP	ISL8200MIRZ-132751	ISL8206MIRZ-T	ZL9117MIRZ-T
ISL8200MIRYR5450	ISL8200MMREP-T	ZL9101MAIRZ	ZL9117MIRZ-TR5494
ISL8200MIRY-TR5450	ISL8201MIRYR5450	ZL9101MAIRZ-T	7L9122MAIRZ
ISL8200MIRT-TR5450	ISL8201MIRTR5450	ZL9101MARZ-1	ZL9122MAIRZ-T
ISL8200MIRZR5545	ISL8201MIRZ	ZL9101MIRZ-T	ZL9122MIRZ
ISL8200MIRZS2751	ISL8201MIRZ-T	ZL9117MAIRZ	ZL9122MIRZ-T

The qualification plan is designed using JEDEC and other applicable industry standards to confirm form, fit, function, and interchangeability of product. A summary of the qualification results are included for reference. The remainder of the manufacturing operations (wafer fabrication, package level electrical testing, etc.) will continue to be processed to previously established conditions and systems.

There will be no change in the external marking of the packaged parts or to the product data sheet electrical specification. Product affected by this change is identifiable via Intersil's internal traceability system.

Intersil will take all necessary actions to conform to agreed upon customer requirements and to ensure the continued high quality and reliability of Intersil products being supplied. Customers may expect to receive product manufactured with the changed materials beginning *ninety* days from the date of this notification or earlier with approval.

If you have concerns with this change notice, Intersil must hear from you promptly. Please contact the nearest Intersil Sales Office or call the Intersil Corporate line at 1-888-468-3774, in the United States, or 1-321-724-7143 outside of the United States.

Regards,

rey R. Touvell

Jeffrey R. Touvell Intersil Corporation

PCN14057

cc: M. Kwoka W. Rowe T. Linder G. Parker Y.W. Cheong C. Dunlap



PCN14057 – Reliability Qualification Results

Stress / Conditions	Duration	ZL9117MIRZ 21 Lead 15x15 QFN	ISL8200MIRZ 23 Lead 15x15 QFN
Moisture Sensitivity Classification		N = 66 Acc = 0	N = 66 Acc = 0
		L3 PBFREE	L3 PBFREE
High Temperature Operating Life	1000 Hrs	N = 80	N = 84
+125C	1000 HIS	Acc = 0	Acc = 0
Temperature Humidity Bias	1000 Hrs	N/A	N = 84
+85C / 85% RH	1000 HIS		Acc = 0
Unbiased HAST	96 Hrs	N = 80 Acc = 0	N/A
+130C / 85% RH	90 115		
Pressure Cooker Test	oker Test 96 Hrs		N = 168
+121C / 100% RH	90 115	N/A	Acc = 0
Temp Cycle	1000 Cy	N = 246	$N = 252^{1}$
+125C / -40C	1000 Cy	Acc = 0	Acc = 0
High Temperature Storage		N = 80	$N = 84^2$
T _A = +150C	1000 Hrs	Acc = 0	Acc = 0

Note 1: TC performed at T_A = +125C / -55C, 1000 cycles

Note 2: HTS performed at T_A = 125C, 1000 hrs

Qualification Complete - Passed

