

DCN	REV	DESCRIPTION	DATE	APPROVAL
22316	00	ORIGINAL ISSUE	4/6/92	<i>J. Guichant</i>

TOP VIEW

NOTES:

- ALL DIMENSIONS ARE IN MILLIMETERS, UNLESS OTHERWISE SPECIFIED.
- BSC – BASIC LEAD SPACING BETWEEN CENTERS.
- D1 & E1 SHOULD BE MEASURED FORM THE BOTTOM OF THE PACKAGE.
- ND & NE REPRESENT NUMBER OF LEADS IN D & E DIRECTIONS RESPECTIVELY.

SYMBOLS	MIN	MAX
A	3.50	3.86
A1	.25	.51
A2	3.17	3.43
b	.22	.35
C	.13	.20
D/E	31.70	32.10
D1/E1	27.56	27.72
D3/E3	25.35 BSC	
e	.65 BSC	
h	.89 REF	
J	.20 REF	
L	.67	.93
ND/NE	40	

TOLERANCES UNLESS OTHERWISE SPECIFIED	
FRAC	DEC ANGLES
± -	± - ± -

Integrated Device Technology, Inc.

2972 Stender WY, Santa Clara, CA 95054

(408) 727-6116 FAX (408) 492 8512

APPROVALS	DATE
DRAWN <i>AA</i>	04/92
CHECKED <i>JH</i>	4/92

160 LD MQUAD® MKT DWG
(.65 LD PITCH, GULLWING)

SCALE	SIZE	DRAWING NO.	REV
N/A	A	PSC-4038	00

DO NOT SCALE DRAWING

SHEET 2 OF 2