

ISL70219ASEH

Neutron Testing of the ISL70219SEH Dual, Low-Power Precision Amplifier

Introduction

This report summarizes results of 1MeV equivalent neutron testing of the ISL70219ASEH dual operational amplifier. The test was conducted to determine the sensitivity of the part to Displacement Damage (DD) caused by neutron or proton environments. Planned neutron fluences ranged from $5 \times 10^{11} \text{ n/cm}^2$ to $1 \times 10^{14} \text{ n/cm}^2$ with actual fluences coming within $\pm 15\%$ of that. This project was carried out in collaboration with Honeywell Aerospace Corporation in Clearwater, FL and their support is gratefully acknowledged.

Product Description

The ISL70219ASEH is a precision dual operational amplifier featuring competitive low noise vs. power consumption characteristics, low offset voltage, low input bias current and low temperature drift, making this device an excellent choice for hardened applications requiring high DC accuracy and moderate AC performance. Specifications for Rad Hard QML devices are controlled by the Defense Logistics Agency (DLA) in Columbus, OH. The SMD is the controlling document and must be cited when ordering.

Related Literature

For a full list of related documents, visit our website:

- [ISL70219ASEH](#) device page
- MIL-STD-883 test method 1017

Contents

1. Test Description	2
1.1 Irradiation Facility	2
1.2 Test Fixturing	2
1.3 Radiation Dosimetry	2
1.4 Characterization Equipment and Procedures	2
1.5 Experimental Matrix	2
2. Results	3
2.1 Attributes Data	3
2.2 Variables Data	3
3. Discussion and Conclusion	13
4. Revision History	13
5. Appendices	14
5.1 Reported Parameters	14

1. Test Description

1.1 Irradiation Facility

Neutron fluence irradiations were performed on the test samples on June 25, 2018, at the WSMR Fast Burst Reactor (FBR) per Mil-STD-883G, Method 1017.2, with each part unpowered during irradiation and all leads shorted. The target irradiation levels were $5 \times 10^{11} \text{ n/cm}^2$, $1 \times 10^{12} \text{ n/cm}^2$, $1 \times 10^{13} \text{ n/cm}^2$, and $1 \times 10^{14} \text{ n/cm}^2$. As neutron irradiation activates many of the heavier elements found in a packaged integrated circuit, the parts exposed at the higher neutron levels required (as expected) some cooldown time before being shipped back to Renesas (Palm Bay, FL) for electrical testing.

1.2 Test Fixturing

No formal irradiation test fixturing is involved, as these DD tests are bag tests in the sense that the parts are irradiated with all leads shorted together.

1.3 Radiation Dosimetry

Table 1 shows the TLD and Sulfur pellet dosimetry from WSMR indicating the total accumulated gamma dose and actual neutron fluence exposure levels for each sets of samples. This dosimetry process is traceable to NIST (IAW ASTM E722).

Table 1. ISL70219ASEH Neutron Fluence Dosimetry Data

TLD		Sulfur Pellet						
TLD #	cGy(Si) ^[1]	Pellet #	Distance (inches)	Exposure ID	Flu >3MeV (n/cm ²)	% Unc ^[2]	Total Fluence (n/cm ²)	1Mev Si (n/cm ²)
288	1.170E+02	6474	26.6	Free Field	7.302E+10	7.1%	5.904E+11	5.079E+11
284	3.903E+02	6420	13.45	Free Field	3.180E+11	7.1%	2.509E+12	2.225E+12
267	2.267E+03	6492	24	Free Field	1.456E+13	7.1%	1.168E+14	1.011E+13
252	1.909E+04	6467	8	Free Field	1.213E+13	7.1%	9.525E+14	8.509E+13

1. 1cGy(Si) = 1rad(Si)

2. The Uncertainty (% Unc) column is applicable only to the Fluence > 3MeV,

1.4 Characterization Equipment and Procedures

Electrical testing was performed before and after irradiation using the production Automated Test Equipment (ATE). All electrical testing was performed at room temperature.

1.5 Experimental Matrix

Testing proceeded in general accordance with the guidelines of MIL-STD-883 TM 1017. The experimental matrix consisted of five samples to be irradiated at $5 \times 10^{11} \text{ n/cm}^2$, five to be irradiated at $1 \times 10^{12} \text{ n/cm}^2$, five to be irradiated at $1 \times 10^{13} \text{ n/cm}^2$, and five to be irradiated at $1 \times 10^{14} \text{ n/cm}^2$. The actual levels achieved (shown in Table 2) were $5.1 \times 10^{11} \text{ n/cm}^2$, $2.2 \times 10^{12} \text{ n/cm}^2$, $1.0 \times 10^{13} \text{ n/cm}^2$, and $8.5 \times 10^{13} \text{ n/cm}^2$. Two control units were used.

ISL70219ASEH samples were drawn from lots X0M0JCDA and X0M0JCADA. Samples were packaged in the standard hermetic 10 Ld ceramic flatpack (CFP) production package. Samples were processed through burn-in before irradiation and were screened to the SMD limits at room, low, and high temperatures before the start of neutron testing.

2. Results

Neutron testing of the ISL70219ASEH is complete and the results are reported in the balance of this report. It should be understood when interpreting the data that each neutron irradiation was performed on a different set of samples; this is not total dose testing, where the damage is cumulative.

2.1 Attributes Data

Table 2. Attributes Data

1MeV Fluence, (n/cm ²)		Sample Size	Pass ^[1]	Fail	Notes
Planned	Actual				
5x10 ¹¹	5.079x10 ¹¹	5	5	0	All passed
2x10 ¹²	2.225x10 ¹²	5	5	0	All passed
1x10 ¹³	1.011x10 ¹³	5	5	0	All passed
1x10 ¹⁴	8.509x10 ¹³	5	0	5	Failed AVOL; PSRR

1. A pass indicates a sample that passes all SMD limits.

2.2 Variables Data

The plots in [Figure 1](#) through [Figure 19](#) show data plots for key parameters before and after irradiation to each level. The plots show the mean of each parameter as a function of neutron irradiation. The plots also include error bars at each downpoint, representing the minimum and maximum measured values of the samples, although in some plots the error bars might not be visible due to their values compared to the scale of the graph. The applicable electrical limits taken from the SMD are also shown.

All samples passed the post-irradiation SMD limits after all exposures up to and including 1x10¹³n/cm², but after 8.5x10¹³n/cm² all five units failed at least one of the Open-Loop Gain (A_{VOL}) measurements at $V_S = \pm 5V$ ([Figure 12](#)), with a worst-case value of 1794V/mV to a 3000V/mV minimum limit. Also, the B output on two units failed the post-irradiation limits for Power Supply Rejection Ratio (PSRR) at $V_S = \pm 18V$ ([Figure 13](#)) after 8.5x10¹³n/cm² and the B output on four units failed at $V_S = \pm 5V$ ([Figure 14](#)). The minimum measurement was 112dB as compared to a 120dB minimum limit. All units remained fully functional.




Figure 1. ISL70219ASEH Output Voltage High (V_{OH}), Channels A and B, with $V_S = \pm 18V$, $\pm 5V$, and $\pm 2.25V$, $R_L = 10k\Omega$, following irradiation to each level. The error bars (if visible) represent the minimum and maximum measured values. The SMD limits are 16.2V minimum for $V_S = \pm 18V$, 3.2V minimum for $V_S = \pm 5V$, and 0.5V minimum for $V_S = \pm 2.25V$.




Figure 2. ISL70219ASEH Output Voltage High (V_{OH}), Channels A and B, with $V_S = \pm 18V$, $\pm 5V$, and $\pm 2.25V$, $R_L = 2k\Omega$, following irradiation to each level. The error bars (if visible) represent the minimum and maximum measured values. The SMD limits are 16V minimum for $V_S = \pm 18V$, 3V minimum for $V_S = \pm 5V$, and 0.45V minimum for $V_S = \pm 2.25V$.




Figure 3. ISL70219ASEH Output Voltage Low (V_{OL}), Channels A and B, with $V_S = \pm 18V$, $\pm 5V$, and $\pm 2.25V$, $R_L = 10k\Omega$, following irradiation to each level. The error bars (if visible) represent the minimum and maximum measured values. The SMD limits are -16.2V maximum for $V_S = \pm 18V$, -3.2V maximum for $V_S = \pm 5V$, and -0.5V maximum for $V_S = \pm 2.25V$.




Figure 4. ISL70219ASEH Output Voltage Low (V_{OL}), Channels A and B, with $V_S = \pm 18V$, $\pm 5V$, and $\pm 2.25V$, $R_L = 2k\Omega$, following irradiation to each level. The error bars (if visible) represent the minimum and maximum measured values. The SMD limits are -16V maximum for $V_S = \pm 18V$, -3V maximum for $V_S = \pm 5V$, and -0.45V maximum for $V_S = \pm 2.25V$.




Figure 5. ISL70219ASEH Positive and Negative Supply Current (I_{SVP} and I_{SVN}), for Channels A + B, with $V_S = \pm 18V$, $\pm 5V$, and $\pm 2.25V$, following irradiation to each level. The error bars (if visible) represent the minimum and maximum measured values. The SMD limits are $-1.35mA$ minimum and $1.35mA$ maximum.




Figure 6. ISL70219ASEH Input Offset Voltage (V_{OS}), Channels A and B, with $V_S = \pm 18V$ and $\pm 2.25V$, following irradiation to each level. The error bars (if visible) represent the minimum and maximum measured values. The SMD limits $-110\mu V$ minimum and $110\mu V$ maximum.




Figure 7. ISL70219ASEH Input Bias Current (I_B), Channels A and B, with $V_S = \pm 18V$, following irradiation to each level. The error bars (if visible) represent the minimum and maximum measured values. The SMD limits are -15nA minimum and 15nA maximum.




Figure 8. ISL70219ASEH Input Bias Current (I_B), Channels A and B, with $V_S = \pm 5V$, following irradiation to each level. The error bars (if visible) represent the minimum and maximum measured values. The SMD limits are -15nA minimum and 15nA maximum.




Figure 9. ISL70219ASEH Input Bias Current (I_B), Channels A and B, with $V_S = \pm 2.25V$, following irradiation to each level. The error bars (if visible) represent the minimum and maximum measured values. The SMD limits are -15nA minimum and 15nA maximum.




Figure 10. ISL70219ASEH Input Offset Current (I_{OS}), Channels A and B, with $V_S = \pm 18V$, $\pm 5V$, and $\pm 2.25V$, following irradiation to each level. The error bars (if visible) represent the minimum and maximum measured values. The SMD limits are -10nA minimum and 10nA maximum.




Figure 11. ISL70219ASEH Open-Loop Gain (A_{VOL}), Channels A and B, with $V_S = \pm 18V$, following irradiation to each level. The error bars (if visible) represent the minimum and maximum measured values. The SMD limit is 3000V/mV minimum.




Figure 12. ISL70219ASEH Open-Loop Gain (A_{VOL}), Channels A and B, with $V_S = \pm 5V$, following irradiation to each level. The error bars (if visible) represent the minimum and maximum measured values. The SMD limit is 3000V/mV minimum.




Figure 13. ISL70219ASEH Power Supply Rejection Ratio (PSRR), Channels A and B, with $V_S = \pm 18V$, following irradiation to each level. The error bars (if visible) represent the minimum and maximum measured values. The SMD limit is 120dB minimum.




Figure 14. ISL70219ASEH Power Supply Rejection Ratio (PSRR), Channels A and B, with $V_S = \pm 5V$, following irradiation to each level. The error bars (if visible) represent the minimum and maximum measured values. The SMD limit is 120dB minimum.




Figure 15. ISL70219ASEH Common-Mode Rejection Ratio (CMRR), Channels A and B, with $V_S = \pm 18\text{V}$, following irradiation to each level. The error bars (if visible) represent the minimum and maximum measured values. The SMD limit is 120dB minimum.




Figure 16. ISL70219ASEH Common-Mode Rejection Ratio (CMRR), Channels A and B, with $V_S = \pm 5\text{V}$, following irradiation to each level. The error bars (if visible) represent the minimum and maximum measured values. The SMD limit is 120dB minimum.




Figure 17. ISL70219ASEH Common-Mode Rejection Ratio (CMRR), Channels A and B, with $V_S = \pm 2.25V$, following irradiation to each level. The error bars (if visible) represent the minimum and maximum measured values. The SMD limit is 95dB minimum.




Figure 18. ISL70219ASEH Slew Rate (SR), Channels A and B, with $V_S = \pm 18V$, $A_V = 1$, $R_L = 2k\Omega$, following irradiation to each level. The error bars (if visible) represent the minimum and maximum measured values. The SMD limit is 0.2V/μs minimum.




Figure 19. ISL70219ASEH Rise Time (t_r) and Fall Time (t_f), Channels A and B, with $V_S = \pm 18V$, following irradiation to each level. The error bars (if visible) represent the minimum and maximum measured values. The SMD limit is 625ns maximum.

3. Discussion and Conclusion

This document reports the results of 1MeV equivalent neutron testing of the ISL70219ASEH dual, low-power precision amplifier. Parts were tested at $5.1 \times 10^{11} \text{ n/cm}^2$, $2.2 \times 10^{12} \text{ n/cm}^2$, $1.0 \times 10^{13} \text{ n/cm}^2$, and $8.5 \times 10^{13} \text{ n/cm}^2$. The results of key parameters before and after irradiation to each level are plotted in Figure 1 through Figure 19. The plots show the mean of each parameter as a function of neutron irradiation, with error bars that represent the minimum and maximum measured values. The figures also show the applicable electrical limits taken from the SMD. All samples passed the post-irradiation SMD limits after all exposures up to and including $1 \times 10^{13} \text{ n/cm}^2$, but after $8.5 \times 10^{13} \text{ n/cm}^2$ all five units failed at least one of the Open-Loop Gain (A_{VOL}) measurements at $V_S = \pm 5V$ (see Figure 12) and some units failed Power Supply Rejection Ratio (PSRR), as can be seen in Figure 13 and Figure 14, even though they all remained fully functional.

4. Revision History

Rev.	Date	Description
1.01	Jun 5, 2025	Applied the latest template. Minor update to the Variables Data and Discussion and Conclusion sections.
1.00	Apr 6, 2020	Initial release

5. Appendices

5.1 Reported Parameters

Figure	Parameter	Symbol	Low Limit	High Limit	Units	Notes
1	Output Voltage High ($R_L = 10k\Omega$)	V_{OH}	16.2	-	V	$V_S = \pm 18V$
			3.2	-		$V_S = \pm 5V$
			0.5	-		$V_S = \pm 2.25V$
2	Output Voltage High ($R_L = 2k\Omega$)	V_{OH}	16	-	V	$V_S = \pm 18V$
			3	-		$V_S = \pm 5V$
			0.45	-		$V_S = \pm 2.25V$
3	Output Voltage Low ($R_L = 10k\Omega$)	V_{OL}	-	-16.2	V	$V_S = \pm 18V$
			-	-3.2		$V_S = \pm 5V$
			-	-0.5		$V_S = \pm 2.25V$
4	Output Voltage Low ($R_L = 2k\Omega$)	V_{OL}	-	-16	V	$V_S = \pm 18V$
			-	-3		$V_S = \pm 5V$
			-	-0.45		$V_S = \pm 2.25V$
5	Supply Current	I_{SVN}	-1.35	-	mA	Sum of both Ch
		I_{SVP}		1.35		
6	Input Offset Voltage ($V_S = \pm 2.25V$; 18V)	V_{OS}	-110	110	μV	Ch A and B
7	Input Bias Current	I_B	-15	15	nA	$V_S = \pm 18V$
8						$V_S = \pm 5V$
9						$V_S = \pm 2.25V$
10	Input Offset Current	I_{OS}	-10	10	nA	Ch A and B
11	Open-Loop Gain ($V_O = -3V$ to $+3V$, $R_L = 10k\Omega$ to ground)	A_{VOL}	3000	-	V/mV	$V_S = \pm 18V$
12						$V_S = \pm 5V$
13	Power Supply Rejection Ratio	PSRR	120	-	dB	$V_S = \pm 18V$
14						$V_S = \pm 5V$
15	Common-Mode Rejection Ratio	CMRR	120	-	dB	$V_S = \pm 18V$
16			120	-		$V_S = \pm 5V$
17			95	-		$V_S = \pm 2.25V$
18	Slew Rate (V_{OUT} 20% to 80%, $A_V = 1$, $R_L = 2k\Omega$, $V = 4V_{PP}$)	SR	0.2	-	V/ μs	$V_S = \pm 18V$
19	Rise Time (10% to 90% of V_{OUT})	t_r	625	-	ns	Ch A and B
	Fall Time (90% to 10% of V_{OUT})	t_f	625	-	ns	Ch A and B

IMPORTANT NOTICE AND DISCLAIMER

RENESAS ELECTRONICS CORPORATION AND ITS SUBSIDIARIES ("RENESAS") PROVIDES TECHNICAL SPECIFICATIONS AND RELIABILITY DATA (INCLUDING DATASHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, WITHOUT LIMITATION, ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR NON-INFRINGEMENT OF THIRD-PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for developers who are designing with Renesas products. You are solely responsible for (1) selecting the appropriate products for your application, (2) designing, validating, and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, or other requirements. These resources are subject to change without notice. Renesas grants you permission to use these resources only to develop an application that uses Renesas products. Other reproduction or use of these resources is strictly prohibited. No license is granted to any other Renesas intellectual property or to any third-party intellectual property. Renesas disclaims responsibility for, and you will fully indemnify Renesas and its representatives against, any claims, damages, costs, losses, or liabilities arising from your use of these resources. Renesas' products are provided only subject to Renesas' Terms and Conditions of Sale or other applicable terms agreed to in writing. No use of any Renesas resources expands or otherwise alters any applicable warranties or warranty disclaimers for these products.

(Disclaimer Rev.1.01)

Corporate Headquarters

TOYOSU FORESIA, 3-2-24 Toyosu,
Koto-ku, Tokyo 135-0061, Japan
www.renesas.com

Contact Information

For further information on a product, technology, the most up-to-date version of a document, or your nearest sales office, please visit www.renesas.com/contact-us/.

Trademarks

Renesas and the Renesas logo are trademarks of Renesas Electronics Corporation. All trademarks and registered trademarks are the property of their respective owners.