# RENESAS

#### To request the full datasheet, please visit www.intersil.com/products/isl24813

### ISL24813

Programmable 18-Channel x 2 Bank, 10-Bit TFT-LCD  $V_{REF}$  Generator with Buffered  $V_{COM}$  Calibrator

FN6615 Rev 2.00 October 30, 2014

DATA SHORT

The ISL24813 is an I<sup>2</sup>C programmable 18-channel, 10-bit reference voltage generator with a digitally controlled V<sub>COM</sub> calibrator and op amp. Two selectable banks of 18 channels allow fast hardware or software switching between two different gamma curves. The ISL24813 is configured and controlled via a standard I<sup>2</sup>C interface.

ISL24813 is available in a 32 Ld TQFN package and is specified for operation across the -40°C to +85°C temperature range.

### **Features**

- 18 I<sup>2</sup>C programmable 10-bit DACs
- Integrated programmable V<sub>COM</sub> calibrator
- One V<sub>COM</sub> op amp
- Two banks of volatile memory for DACs
- 5V to 18V analog supply range
- 2.5V to 3.3V digital supply range
- 20mA analog supply current (unloaded)
- 700µA digital supply current
- I<sup>2</sup>C serial interface
- Pb-free (RoHS compliant)

## **Applications**

- TFT-LCD column driver reference generator
- General-purpose reference voltage generators



FIGURE 1. TYPICAL APPLICATION CIRCUIT



© Copyright Intersil Americas LLC 2010-2014. All Rights Reserved. All trademarks and registered trademarks are the property of their respective owners.

For additional products, see www.intersil.com/en/products.html

Intersil products are manufactured, assembled and tested utilizing ISO9001 quality systems as noted in the quality certifications found at <a href="http://www.intersil.com/en/support/qualandreliability.html">www.intersil.com/en/support/qualandreliability.html</a>

Intersil products are sold by description only. Intersil may modify the circuit design and/or specifications of products at any time without notice, provided that such modification does not, in Intersil's sole judgment, affect the form, fit or function of the product. Accordingly, the reader is cautioned to verify that datasheets are current before placing orders. Information furnished by Intersil is believed to be accurate and reliable. However, no responsibility is assumed by Intersil or its subsidiaries for its use; nor for any infringements of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Intersil or its subsidiaries.

For information regarding Intersil Corporation and its products, see www.intersil.com

FN6615 Rev 2.00 October 30, 2014

