

CUSTOMER NOTIFICATION

SUD-TT-0014-2-E
April 8, 2002
Koji Nishibayashi, Project Manager Microcomputer Group 2 System LSI Solution Engineering Div. NEC Electron Devices NEC Corporation

CP (K), O

IE-703079-MC-EM1
(Control Code: A, B, C, D, E, F, G)

Operating Precautions

Be sure to read this document before using the product.

1. Product Version 1
2. Product History 1
3. Details of Bugs and Added Specifications 2
4. Other Cautions 5

Notes on Using IE-703079-MC-EM1

1. Product Version

Control code	Board version	Peripheral EVA chip	ROM (IC1)	ROM (IC20)
A	V1.00	UPD70F3079Y DS1.0	HN27C101AG-12 V1.0	CY7C263-20JC V1.0
B	V1.01	UPD70F3079Y DS1.1	HN27C101AG-12 V1.1	CY7C263-20JC V1.0
C	V1.02	UPD70F3079Y ES1.1	HN27C101AG-12 V1.2	CY7C263-20JC V1.0
D	V1.03	UPD70F3079Y ES1.1	HN27C101AG-12 V1.3	CY7C263-20JC V1.0
E	V1.04	UPD70F3079Y DS2.0	HN27C101AG-12 V1.3	CY7C263-20JC V1.0
F	V1.24	UPD70F3079AY DS1.1	HN27C101AG-12 V1.3	CY7C263-20JC V1.0
G	V1.34	UPD70F3079AY DS1.1	HN27C101AG-12 V1.3	CY7C263-20JC V1.0

Employ an IE-703002-MC with a control code of H or later when using this option board.

2. Product History

No.	Bugs and Changes/Additions to Specification	Control Code ^{Note}						
		A	B	C	D	E	F	G
1	P0.0 cannot be used.	×	√	√	√	√	√	√
2	POC function cannot be used.	Permanent restriction						
3	When FCAN memory is accessed, bus cycle is output from the external expansion pin.	Permanent restriction						
4	Restriction on P4, 5, 6, 9, and 11 in input mode	×	√	√	√	√	√	√
5	Restriction when P11 is set as a multiplexed pin	×	×	√	√	√	√	√
6	The high-level signal output from P0.0 is lower than the PortVDD potential by about 1 V.	×	×	×	√	√	√	√
7	The high-level signal output from P0.0 is fixed at 5 V.	Permanent restriction						
8	Restriction on the FCAN function when the WAIT pin is used	×	×	×	√	√	√	√
9	Caution when FCAN memory is accessed	×	×	×	×	√	√	√
10	Restrictions on external clock	Permanent restriction						
11	ROM correction function cannot be emulated	Permanent restriction						
12	Emulation during oscillation stabilization time after RESET release cannot be performed	Permanent restriction						
13	Restriction on interrupts in STOP/IDLE mode	×	×	×	×	×	×	√
14	Modification of emulation target CPU	×	×	×	×	×	√	√
15	Hi-Z output from the CLKOUT pin cannot be emulated	Permanent restriction						

×: Applicable, √: Not applicable or already corrected

Note The “control code” is the second digit from the left in the 10-digit serial number in the warranty supplied with the in-circuit emulator you purchased (if it has not been upgraded). If the in-circuit emulator has been upgraded, a label indicating the new version is attached to the in-circuit emulator and the x in V-UP LEVEL x on this label indicates the control code.

3. Details of Bugs and Added Specifications

No. 1 P0.0 cannot be used

[Description]

P0.0 cannot be used.

[Workaround]

There is no workaround.

This bug has been corrected in the control code B model.

No. 2 POC function cannot be used

[Description]

POC function cannot be used.

[Workaround]

There is no workaround.

This will be designated as a permanent restriction.

No. 3 When FCAN memory is accessed, bus cycle is output from the external expansion pin

[Description]

When FCAN memory is accessed, bus cycle is output from the external expansion pin.

[Workaround]

There is no workaround.

This will be designated as a permanent restriction.

No. 4 Restriction on P4, 5, 6, 9, and 11 in input mode

[Description]

If P4, 5, 6, 9, and 11 are in input mode, the potential of the pins is lowered even if a pull-up resistor is connected on the target system (approx. 2.5 to 4 V).

[Workaround]

There is no workaround.

This bug has been corrected in the control code B model.

No. 5 Restriction when P11 is set as a multiplexed pin

[Description]

If PM11 is set to output mode while P11 is set as a multiplexed pin (CAN control pin), the potential of the low-level output signal is not lowered to less than 2.5 V.

[Workaround]

There is no workaround.

This bug has been corrected in the control code C model.

No. 6 The high-level signal output from P0.0 is lower than the PortV_{DD} potential by about 1 V.

[Description]

The high-level signal output from P0.0 is lower than the PortV_{DD} potential by about 1 V.

[Workaround]

There is no workaround.

This bug has been corrected in the control code D model.

No. 7 The high-level signal output from P0.0 is fixed at 5 V.

[Description]

The high-level output from P0.0 is fixed at 5 V regardless of PortV_{DD}.

[Workaround]

There is no workaround.

This will be designated as a permanent restriction.

No. 8 Restriction on the FCAN function when the WAIT pin is used

[Description]

The FCAN function cannot be used if the WAC flag of the PAC register is set to the WAIT pin.

[Workaround]

There is no workaround.

This bug has been corrected in the control code D model.

No. 9 Caution when FCAN memory is accessed

[Description]

The in-circuit emulator deadlocks if addresses between 0xnffe00 and 0xnffff (n = 3, 7, b) of the FCAN address area are accessed (this area is unusable).

[Workaround]

Do not access addresses between 0xnffe00 and 0xnffff (n = 3, 7, b).

This bug has been corrected in the control code E model.

No. 10 Restrictions on external clock

[Description]

Emulation cannot be performed externally with the main clock or the subclock.

[Workaround]

Use the clock in the emulator.

This will be designated as a permanent restriction.

No. 11 ROM correction function cannot be emulated

[Description]

The ROM correction function cannot be emulated.

[Workaround]

There is no workaround.

This will be designated as a permanent restriction.

No. 12 Emulation during oscillation stabilization time after RESET release cannot be performed

[Description]

Emulation during the oscillation stabilization time after RESET release cannot be performed.

[Workaround]

There is no workaround.



This will be designated as a permanent restriction.

No. 13 Restriction on interrupts in STOP/IDLE mode

[Description]

The emulator is deadlocked if the device is shifted to the STOP/IDLE mode while the interrupt request flag for an interrupt that is not masked is set.

[Workaround 1]

Be sure to clear the non-masked interrupt request flag before shifting to the STOP/IDLE mode. If the device is inadvertently shifted before clearing the flag, execute “Run” → “Stop” or click the  button on the debugger. The program is forcibly terminated. Then, execute “Run” → “CPU Reset” or click the  button.

[Workaround 2]

Do not allow the device to shift to the STOP/IDLE mode while the interrupt request flag for an interrupt that is not masked is set.

This bug has been corrected in the control code G model.

No. 14 Modification of emulation target CPU

[Description]

The emulation target CPUs have been changed from the μ PD70F3079Y, 70307xY (non-A products) to the μ PD70F3079AY, 70307xAY (A products).

* Care must be taken because the initial value of the oscillation stabilization time selection register (OSTS) differs between the μ PD70F3079Y, 70307xY (non-A products) and the μ PD70F3079AY, 70307xAY (A products).

* The Hi-Z output from the CLKOUT pin cannot be emulated.

[Workaround]

There is no workaround.

This change has been implemented in the control code F model.

No. 15 Hi-Z output from the CLKOUT pin cannot be emulated

[Description]

The Hi-Z output from the CLKOUT pin cannot be emulated. Even if the power save control register (PSC) is set to “Hi-Z output (DCLK1 = 0, DCLK0 = 1)” in the emulator, the same operation as “output enable (DCLK1 = 0, DCLK0 = 0)” is performed.

[Workaround]

There is no workaround.

This will be designated as a permanent restriction.

4. Other Cautions

When using the FCAN function, implement the following procedure on startup of the debugger.

- a) Before startup of the debugger, supply power to pin VDD0 (GC package: pin 8, GF package: pin 11) on the target board
- b) Set the memory mapping on the debugger as shown below.
Attribute: Target memory
Mapping address: nFF800H to nFFFFFFH (n = 3, 7, B)
- c) Do not mask WAIT and HLDRQ when accessing the FCAN memory.