

# RENESAS TECHNICAL UPDATE

1753, Shimonumabe, Nakahara-ku, Kawasaki-shi, Kanagawa 211-8668 Japan  
Renesas Electronics Corporation

Product Category	MPU/MCU		Document No.	TN-SH7-A786A/E	Rev.	1.00
Title	Limitation on Use of SH7785 HAC 20-bit TX DMA		Information Category	Technical Notification		
Applicable Product	SH7785 Group	Lot No.	Reference Document	SH7785 Hardware Manual Rev.1.00 Jan.10.2008 (REJ09B0261-0100)		
		All lots				

There is a limitation of the Audio Codec Interface (HAC) of the SH7785.

## [Summary]

When using the HAC with all the following conditions 1) to 3), the PCM playback data may not be transferred correctly, a same data is written to the HACPCML and HACPCMR. As a result, as the shown below figure, the HAC transmits the same PCM data to slot 3 and 4 of the AC97 frame and the data that is not transmitted during slot 3 and 4 are lost.




Figure. 20-Bit PCM Playback Data in TX DMA Enable

## [Condition]

- 1) Slot 3 and 4 PCM playback data stream: 20 bits.
- 2) PCM playback data transfer (PCM data output).
- 3) Using TX DMA transfer for the PCM playback data transfer (TX DMA enable).

## [Workaround]

When using TX DMA transfer of the 20-bit PCM playback data for slot 3 and 4 by, there is no workaround.

Use not the DMA transfer but the PIO transfer for the 20-bit PCM playback data for slot 3 and 4.

Note that, the 16-bit data DMA operation for slot 3 and 4, and the 20-bit PCM record data transfer (RX DMA enable) are no problem.

- End of Text -