

## Interface IP

# SerDes PHY(PCIe2.1, USB3.0 SS) 5Gbps for TSMC 28nm HPC+

### Overview


The Renesas SerDes PHY is useful analog transceiver hard macro for various high speed serial interface PHY layer of TSMC 28nm HPC+ process. This macro is designed for PCI Express 2.1 / USB3.0 SuperSpeed.

### Key Features

- Renesas SerDes PHY can be used for analog transceiver of following interface .
  - PCI Express 2.1 ( compliant with “PCI-Express Base Specification Revision 2.1”) \*1
  - USB3.0 SuperSpeed ( compliant with “Universal Serial Bus 3.0 Specification Revision 1.0 ) \*1
- PCI Express 2.1 and USB3.0 SuperSpeed can be used as Combo macro \*1
- Multi-lane support for PCI Express 2.1 ( 1 / 2 / 4 / 8 lanes available ).
- Technology is TSMC 28nm HPC+ 1p10M .
- Supply voltage can be applied 0.90V for nominal and 1.0V for overdrive of core voltage, 1.8V for IO voltage.
- Selectable 10bit / 20bit for parallel side interface.
- 2Tap FIR filter for Tx equalizer / Tunable peaking amplifier for Rx equalizer.
- Built-in differential input buffer for clean reference clock.

\*1 There are some restrictions for use case of these standards. Please contact and consult to Renesas Electronics for detail information before purchasing product.

### Block Diagram



*\*This IP is contract design IP. Please contact for detail.*

PMO-25-038  
R06PF0094EJ0101