

[Notes]

R20TS0576EC0100

Rev.1.00

Smart Configurator for RH850

May. 16, 2020

Outline

When using Smart Configurator for RH850, note the following point.

1. When using CSI master and CSI slave

1. When Using CSI Master and CSI Slave

1.1 Applicable Products

Smart Configurator for RH850 V1.1.0 or later

1.2 Applicable Devices

RH850 family: RH850/F1KM group

- RH850/F1KM-S1 (48-pin, 64-pin, 80-pin, and 100-pin products)
- RH850/F1KM-S4 (100-pin, 144-pin, 176-pin, and 233-pin products)

1.3 Details

When using CSI master or CSI slave as receive mode or transmit/receive mode on the following peripherals, transmission process does not work from the second time because the variable of receive count initialization is wrong.

- RH850/F1KM-S1: 48-pin, 64-pin products
CSIG0, CSIH0
- RH850/F1KM-S1: 80-pin products
CSIG0, CSIH0, CSIH1, CSIH2
- RH850/F1KM-S1: 100-pin products
CSIG0, CSIH0, CSIH1, CSIH2, CSIH3
- RH850/F1KM-S4: 100-pin products
CSIG0, CSIH0, CSIH1, CSIH2, CSIH3
- RH850/F1KM-S4: 144-pin products
CSIG0, CSIG1, CSIH0, CSIH1, CSIH2, CSIH3
- RH850/F1KM-S4: 176-pin, 233-pin products
CSIG0, CSIG1, CSIG2, CSIG3, CSIH0, CSIH1, CSIH2, CSIH3

- GUI configuration when using CSI master as receive mode on CSIG0

Add new configuration for selected component



CSI Master	
Configuration name:	Config_CSIG0
Operation:	Master receive
Resource:	CSIG0

- GUI configuration when using CSI slave as receive mode on CSIG0

Add new configuration for selected component



CSI Slave	
Configuration name:	Config_CSIG0
Operation:	Slave receive
Resource:	CSIG0

1.4 Workaround

Manually modify the variable name of receive count from "g_<csign>_tx_num" to "g_<csign>_rx_num" in the following source file ^(Note). <csign> varies depending on the selected resource.

- Source file: "<Configuration-name>.c".
- Function: "MD_STATUS R_<Configuration-name>_Receive (uint16_t* rx_buf, uint16_t rx_num)"

Note: If code is generated again, the previous state is restored. Modification is necessary each time you perform code generation.

The following is an example of the required modification when <Configuration-name> is Config_CSIG0 in the RH850/F1KM group. Manually modify the wrong code in red to correct code in blue.

Before modification

```
MD_STATUS R_Config_CSIG0_Receive(uint16_t* rx_buf, uint16_t rx_num)
{
    MD_STATUS status = MD_OK;
    if (rx_num < 1U)
    {
        status = MD_ARGERROR;
    }
    else
    {
        g_csig0_rx_total_num = rx_num;
        gp_csig0_rx_address = rx_buf;
        g_csig0_tx_num = 0U;
    }

    return (status);
}
```

After modification

```
MD_STATUS R_Config_CSIG0_Receive(uint16_t* rx_buf, uint16_t rx_num)
{
    MD_STATUS status = MD_OK;
    if (rx_num < 1U)
    {
        status = MD_ARGERROR;
    }
    else
    {
        g_csig0_rx_total_num = rx_num;
        gp_csig0_rx_address = rx_buf;
        g_csig0_rx_num = 0U;
    }

    return (status);
}
```

1.5 Schedule for Fixing the Problem

This problem will be fixed in a later version.

Revision History

Rev.	Date	Description	
		Page	Summary
1.00	May.16.20	-	First edition issued

Renesas Electronics has used reasonable care in preparing the information included in this document, but Renesas Electronics does not warrant that such information is error free. Renesas Electronics assumes no liability whatsoever for any damages incurred by you resulting from errors in or omissions from the information included herein.

The past news contents have been based on information at the time of publication. Now changed or invalid information may be included.

The URLs in the Tool News also may be subject to change or become invalid without prior notice.

Corporate Headquarters

TOYOSU FORESIA, 3-2-24 Toyosu,
Koto-ku, Tokyo 135-0061, Japan
www.renesas.com

Trademarks

Renesas and the Renesas logo are trademarks of Renesas Electronics Corporation. All trademarks and registered trademarks are the property of their respective owners.

Contact information

For further information on a product, technology, the most up-to-date version of a document, or your nearest sales office, please visit:
www.renesas.com/contact/