

CC-RL

C++14 Technical Preview Version

User's Manual

Applicable Revision
V1.12.00

All information contained in these materials, including products and product specifications, represents information on the product at the time of publication and is subject to change by Renesas Electronics Corp. without notice. Please review the latest information published by Renesas Electronics Corp. through various means, including the Renesas Electronics Corp. website (<http://www.renesas.com>).

Notice

1. Descriptions of circuits, software and other related information in this document are provided only to illustrate the operation of semiconductor products and application examples. You are fully responsible for the incorporation or any other use of the circuits, software, and information in the design of your product or system. Renesas Electronics disclaims any and all liability for any losses and damages incurred by you or third parties arising from the use of these circuits, software, or information.
 2. Renesas Electronics hereby expressly disclaims any warranties against and liability for infringement or any other claims involving patents, copyrights, or other intellectual property rights of third parties, by or arising from the use of Renesas Electronics products or technical information described in this document, including but not limited to, the product data, drawings, charts, programs, algorithms, and application examples.
 3. No license, express, implied or otherwise, is granted hereby under any patents, copyrights or other intellectual property rights of Renesas Electronics or others.
 4. You shall be responsible for determining what licenses are required from any third parties, and obtaining such licenses for the lawful import, export, manufacture, sales, utilization, distribution or other disposal of any products incorporating Renesas Electronics products, if required.
 5. You shall not alter, modify, copy, or reverse engineer any Renesas Electronics product, whether in whole or in part. Renesas Electronics disclaims any and all liability for any losses or damages incurred by you or third parties arising from such alteration, modification, copying or reverse engineering.
 6. Renesas Electronics products are classified according to the following two quality grades: "Standard" and "High Quality". The intended applications for each Renesas Electronics product depends on the product's quality grade, as indicated below.
 - "Standard": Computers; office equipment; communications equipment; test and measurement equipment; audio and visual equipment; home electronic appliances; machine tools; personal electronic equipment; industrial robots; etc.
 - "High Quality": Transportation equipment (automobiles, trains, ships, etc.); traffic control (traffic lights); large-scale communication equipment; key financial terminal systems; safety control equipment; etc.
- Unless expressly designated as a high reliability product or a product for harsh environments in a Renesas Electronics data sheet or other Renesas Electronics document, Renesas Electronics products are not intended or authorized for use in products or systems that may pose a direct threat to human life or bodily injury (artificial life support devices or systems; surgical implantations; etc.), or may cause serious property damage (space system; undersea repeaters; nuclear power control systems; aircraft control systems; key plant systems; military equipment; etc.). Renesas Electronics disclaims any and all liability for any damages or losses incurred by you or any third parties arising from the use of any Renesas Electronics product that is inconsistent with any Renesas Electronics data sheet, user's manual or other Renesas Electronics document.
7. No semiconductor product is absolutely secure. Notwithstanding any security measures or features that may be implemented in Renesas Electronics hardware or software products, Renesas Electronics shall have absolutely no liability arising out of any vulnerability or security breach, including but not limited to any unauthorized access to or use of a Renesas Electronics product or a system that uses a Renesas Electronics product. RENESAS ELECTRONICS DOES NOT WARRANT OR GUARANTEE THAT RENESAS ELECTRONICS PRODUCTS, OR ANY SYSTEMS CREATED USING RENESAS ELECTRONICS PRODUCTS WILL BE INVULNERABLE OR FREE FROM CORRUPTION, ATTACK, VIRUSES, INTERFERENCE, HACKING, DATA LOSS OR THEFT, OR OTHER SECURITY INTRUSION ("Vulnerability Issues"). RENESAS ELECTRONICS DISCLAIMS ANY AND ALL RESPONSIBILITY OR LIABILITY ARISING FROM OR RELATED TO ANY VULNERABILITY ISSUES. FURTHERMORE, TO THE EXTENT PERMITTED BY APPLICABLE LAW, RENESAS ELECTRONICS DISCLAIMS ANY AND ALL WARRANTIES, EXPRESS OR IMPLIED, WITH RESPECT TO THIS DOCUMENT AND ANY RELATED OR ACCOMPANYING SOFTWARE OR HARDWARE, INCLUDING BUT NOT LIMITED TO THE IMPLIED WARRANTIES OF MERCHANTABILITY, OR FITNESS FOR A PARTICULAR PURPOSE.
 8. When using Renesas Electronics products, refer to the latest product information (data sheets, user's manuals, application notes, "General Notes for Handling and Using Semiconductor Devices" in the reliability handbook, etc.), and ensure that usage conditions are within the ranges specified by Renesas Electronics with respect to maximum ratings, operating power supply voltage range, heat dissipation characteristics, installation, etc. Renesas Electronics disclaims any and all liability for any malfunctions, failure or accident arising out of the use of Renesas Electronics products outside of such specified ranges.
 9. Although Renesas Electronics endeavors to improve the quality and reliability of Renesas Electronics products, semiconductor products have specific characteristics, such as the occurrence of failure at a certain rate and malfunctions under certain use conditions. Unless designated as a high reliability product or a product for harsh environments in a Renesas Electronics data sheet or other Renesas Electronics document, Renesas Electronics products are not subject to radiation resistance design. You are responsible for implementing safety measures to guard against the possibility of bodily injury, injury or damage caused by fire, and/or danger to the public in the event of a failure or malfunction of Renesas Electronics products, such as safety design for hardware and software, including but not limited to redundancy, fire control and malfunction prevention, appropriate treatment for aging degradation or any other appropriate measures. Because the evaluation of microcomputer software alone is very difficult and impractical, you are responsible for evaluating the safety of the final products or systems manufactured by you.
 10. Please contact a Renesas Electronics sales office for details as to environmental matters such as the environmental compatibility of each Renesas Electronics product. You are responsible for carefully and sufficiently investigating applicable laws and regulations that regulate the inclusion or use of controlled substances, including without limitation, the EU RoHS Directive, and using Renesas Electronics products in compliance with all these applicable laws and regulations. Renesas Electronics disclaims any and all liability for damages or losses occurring as a result of your noncompliance with applicable laws and regulations.
 11. Renesas Electronics products and technologies shall not be used for or incorporated into any products or systems whose manufacture, use, or sale is prohibited under any applicable domestic or foreign laws or regulations. You shall comply with any applicable export control laws and regulations promulgated and administered by the governments of any countries asserting jurisdiction over the parties or transactions.
 12. It is the responsibility of the buyer or distributor of Renesas Electronics products, or any other party who distributes, disposes of, or otherwise sells or transfers the product to a third party, to notify such third party in advance of the contents and conditions set forth in this document.
 13. This document shall not be reprinted, reproduced or duplicated in any form, in whole or in part, without prior written consent of Renesas Electronics.
 14. Please contact a Renesas Electronics sales office if you have any questions regarding the information contained in this document or Renesas Electronics products.

(Note1) "Renesas Electronics" as used in this document means Renesas Electronics Corporation and also includes its directly or indirectly controlled subsidiaries.

(Note2) "Renesas Electronics product(s)" means any product developed or manufactured by or for Renesas Electronics.

(Rev.5.0-1 October 2020)

Corporate Headquarters

TOYOSU FORESIA, 3-2-24 Toyosu,
Koto-ku, Tokyo 135-0061, Japan

www.renesas.com

Contact information

For further information on a product, technology, the most up-to-date version of a document, or your nearest sales office, please visit:
www.renesas.com/contact/.

Trademarks

Renesas and the Renesas logo are trademarks of Renesas Electronics Corporation. All trademarks and registered trademarks are the property of their respective owners.

Table of Contents

1.	OUTLINE	4
1.1	About the Technical Preview Edition	4
1.2	Copyrights	4
2.	OPTIONS.....	5
2.1	Existing options available under the C++14 specification	5
2.1.1	Compile option	5
2.1.2	Assemble options.....	8
2.1.3	Link options	8
3.	COMPILER LANGUAGE SPECIFICATIONS	9
3.1	Basic language specifications.....	9
3.1.1	Unsupported C++ language specifications	9
3.1.2	Implementation-defined behavior of C++14.....	9
3.1.3	Internal representation and allocation of data.....	11
3.2	Language extension specifications.....	13
3.2.1	Reserved words	13
3.2.2	Macros.....	13
3.2.3	#pragma directives.....	13
3.2.4	Intrinsic functions	13
4.	SECTION SPECIFICATIONS	14
4.1	Section name	14
5.	LIBRARY FUNCTIONAL SPECIFICATIONS.....	15
5.1	Outline.....	15
5.2	Supplied Libraries	15
5.3	Header Files.....	15
6.	STARTUP	19
6.1	Startup Routine	19
6.1.1	Initialization of global objects of class type	19
7.	MESSAGE	20
7.1	Message Formats	20
7.1.1	Format 1	20
7.1.2	Format 2	20
7.2	Message Types.....	20
8.	NOTES	21
8.1	Missing information for source level debugging.....	21

1. OUTLINE

This user's manual describes the specifications and notes when using the option `-lang=cpp14`, which allows the compiler to compile the source program with C++14 standard and is a part of the C compiler package for RL78 family CC-RL V1.12.00.

Please also refer to the CC-RL User's Manual as well.

1.1 About the Technical Preview Edition

The Technical Preview Edition is a feature from future to be improved through the feedback from users. At the time of release of CC-RL V1.12.00, the option `-lang=cpp14` is provided for users as the Technical Preview Edition. Please keep the following notes in mind.

- Do not apply the option `-lang=cpp14` for building the product software. The option is only for evaluation and has no warranty.
- The following message will be output when using the option `-lang=cpp14`:
W0519999: The `-lang=cpp14` option in CC-RL V1.12.00 is a technical preview edition. It cannot be used in product development.
- Please send your feedback on this feature from the URL below:
<https://forms.office.com/r/wSGqp6BKic>

1.2 Copyrights

This software uses the following softwares.

- LLVM and Clang are copyrights of University of Illinois at Urbana-Champaign.
- Protocol Buffers is copyright of Google Inc.

The libraries for C++ use the following softwares. Please refer to the license files included in the compiler package for detail.

- `compiler_rt`
- `libc++`
- `libc++abi`
- `newlib`

Other software components are copyright of Renesas Electronics Corporation.

2. OPTIONS

Specify the following option for compiling a source program with C++14 standard.

```
-lang=cpp14
```

[Detailed description]

This option allows the compiler to compile a source program with C++14 standard (ISO/IEC 14882:2014).

- A compile error will occur when C source files are specified as input with this option. For details of the kind of input/output files, please refer to "2.2 I/O Files" in CC-RL User's Manual.
- Please refer to the following section for the existing options that can be used with this option.

2.1 Existing options available under the C++14 specification

2.1.1 Compile option

This section shows the existing compile options allowed to combine with `-lang=cpp14`. "X" in the "Combinable" column indicates that the option is just ignored, or an error message will be output.

Table 1 Compiler options available under the C++14 standard

Category	Option	Combinable	Note
Version display specification	-V	✓	
Help display specification	-help	✓	
Output file specification	-o	✓	
	-obj_path	✓	
	-asm_path	✓	
	-prep_path	✓	
Source debugging control	-g	✓	Some debug information of C++ standard specifications will be discarded. Please refer to the section "NOTES" below.
	-g_line	✓	
Device specification relation	-cpu	✓	
	-use_mda	✓	
Processing interrupt specification	-P	✓	
	-S	✓	
	-c	✓	

Table 1 Compiler options available under the C++14 standard (2)

Category	Option	Combinable	Note
Preprocessor control	-D	✓	
	-U	✓	
	-I	✓	
	-preinclude	✓	
	-preprocess	X	
Memory model	-memory_model={small medium}	✓	
	-far_rom	✓	Internal error may occur in some programs.
Optimization	-O{ size speed default lite nothing }	✓	
	-goptimize	✓	
Optimization (detailed)	-Oinline_level[= <i>value</i>]	✓	
	-Oinline_size[= <i>value</i>]	✓	
	-Opipeline[={on off}]	✓	
	-Ounroll[= <i>value</i>]	✓	
	-Otail_call[={on off}]	✓	
	-Odelete_static_func[={on off}]	✓	
	-Omerge_files	X	
	-Ointermodule	X	
	-Owhile_program	X	
	-Oalias={ansi noansi}	X	
	-Osame_code={on off}	✓	
Additional information output	-cref	X	
	-pass_source	✓	
Error output control	-no_warning_num	✓	Applicable to the messages ranged for W0510000-W0519999 and W0530000-W0559999 (W0520000-W0529999 are not output when -lang=cpp14 is specified).
	-change_message	✓	Applicable to the messages ranged for W0510000-W0519999 and W0530000-W0549999 (W0520000-W0529999 are not output when -lang=cpp14 is specified)
	-error_file	✓	

Table 1 Compiler options available under the C++14 standard (3)

Category	Option	Combinable	Note
Code generation changing	-dbl_size={4 8}	✓	
	-signed_char	✓	
	-signed_bitfield	X	This option has no effect when -lang=cpp14 is specified: The bitfield type for which neither "signed" nor "unsigned" is specified as "signed". This is different from the interpretation when -lang=c or -lang=c99 is specified: those options handle the bitfield type for which neither "signed" nor "unsigned" is specified as "unsigned".
	-switch	✓	
	-volatile	X	
	-merge_string	X	
	-pack	✓	
	-stuff	X	
	-stack_protector -stack_protector_all	X	
	-insert_nop_with_label -control_flow_integrity	X	
Extensions	-strict_std	X	
	-refs_without_declaration	X	
	-large_variable	X	
	-nest_comment	X	
	-character_set	X	This option has no effect when -lang=cpp14 is specified: The encoding in the source file is always interpreted as UTF-8.
MISRA check	-misra2004	X	
	-misra2012	X	
	-ignore_files_misra	X	
	-check_language_extension	X	
	-misra_intermodule	X	
Subcommand file specification	-subcommand	✓	
Assembler and linker control	-asmopt= <i>arg</i>	✓	
	-lnkopt= <i>arg</i>	✓	
	-asmcmd= <i>filename</i>	✓	
	-lnkcmd= <i>filename</i>	✓	
	-dev= <i>filename</i>	✓	
Compiler transition support	-convert_cc={ca78k0r nc30 iar}	X	
	-unaligned_pointer_for_ca78k0r	X	

2.1.2 Assemble options

All existing assemble options are allowed to combine with `-lang=cpp14`.

2.1.3 Link options

The existing link option below is not allowed to combine with `-lang=cpp14`. The other options are allowed to combine with `-lang=cpp14`.

Table 2 Link options available under the C++14 standard

Category	Option	Combinable	Note
Output control	<code>-VFINFO</code>	X	

3. COMPILER LANGUAGE SPECIFICATIONS

3.1 Basic language specifications

3.1.1 Unsupported C++ language specifications

The following language specifications are not supported by the Technical Preview Edition.

- Exception handling
- Runtime type identification
- Threads
- Atomic operations

3.1.2 Implementation-defined behavior of C++14

This section covers the implementation-defined behavior.

Table 3 Implementation-defined behavior

Section No.	Item	Description
1.3.6	diagnostic message	Refer to "7. Message".
1.4	required libraries for freestanding implementation	Refer to "5. Library Specifications".
1.7	bits in a byte	8 bits.
1.9	interactive device	What constitutes an interactive device is not specified.
1.10	number of threads in a program under a freestanding implementation	Multi-threaded execution is not supported.
2.2	mapping physical source file characters to basic source character set	Map as UTF-8 as-is.
2.2	physical source file characters	UTF-8.
2.2	converting characters from source character set to execution character set	The source character set and the execution character set are the same.
2.2	whether source of translation units must be available to locate template definitions	The source is not required.
2.9	mapping header name to header or external source file	Interpreted as described and mapped to a file name.
2.14.3	value of multicharacter literal	the lower 4 bytes of the execution character set.
2.14.3	value of wide-character literal containing multiple characters	the last character in the execution character set.
2.14.3	value of wide-character literal with single c-char that is not in execution wide-character set	the value of the character.
2.14.3	encoding of universal character name not in execution character set	the value of the character.
2.14.3	semantics of non-standard escape sequences	¥e and ¥E are valid. Both values are 0x1b.
2.14.3	value of character literal outside range of corresponding type	An error occurs.
2.14.5	concatenation of some types of string literals	An error occurs.

Table 3 Implementation-defined behavior

Section No.	Item	Description
3.6.1	defining main in freestanding environment	Not defined.
3.6.1	parameters to main	Not defined.
3.6.1	start-up and termination in freestanding environment	Not defined. Depends on the startup routine.
3.6.1	linkage of main	C linkage.
3.6.2	dynamic initialization of static objects before main	Depends on the startup routine.
3.6.2	dynamic initialization of thread-local objects before entry	Threads are not supported.
3.9.1	extended signed integer types	Extended signed integer types are not supported.
3.9.1	representation of char	1 byte.
3.9.1	signedness of char	Unsigned char type. However, it can be switched to signed char type by <code>-signed_char</code> option.
3.9.1	value representation of floating-point types	Compliant with IEEE754.
3.9.2	value representation of pointer types	Refer to "3.1.3 Internal representation and value area of data".
3.11	alignment	Refer to "3.1.3 Internal representation and value area of data".
4.13	rank of extended signed integer type	Extended signed integer type is not supported.
5.3.3	sizeof applied to fundamental types other than char, signed char, and unsigned char	Refer to "3.1.3 Internal representation and value area of data".
5.3.4	support for over-aligned types	Over-aligned types are not supported.
5.8	result of right shift of negative value	Arithmetic shift is performed.
7.2	underlying type for enumeration	Refer to "3.1.3 Internal representation and value area of data".
7.4	meaning of asm declaration	The asm declaration is not supported.
8.4.1	string resulting from <code>__func__</code>	A function name is returned.
16.2	nesting limit for <code>#include</code> directives	The nesting limit depends on the memory available.
16.6	<code>#pragma</code>	Refer to "Pragma directive".
16.8	text of <code>__DATE__</code> when date of translation is not available	The date is always available.
16.8	text of <code>__TIME__</code> when time of translation is not available	The time is always available.
16.8	definition and meaning of <code>__STDC__</code>	Defined as 1.
16.8	definition and meaning of <code>__STDC_VERSION__</code>	Not defined.
17.6.5.12	exceptions thrown by standard library functions that do not have an exception specification	Exceptions are not supported.
18.2	type of <code>size_t</code>	unsigned int.
18.5	exit status	Not defined.

3.1.3 Internal representation and allocation of data

This section describes the internal representation and value range for each data type in CC-RL.

(1) Basic type

Table 4 Basic types

Data Type	Size (byte)	Alignment (byte)	Signed/Unsigned	Data range Minimum Value	Maximum Value	Note
char	1	1	Unsigned	0	+255	The value range is the same as that of signed char when -signed_char is specified.
signed char	1	1	Signed	-128	+127	
unsigned char	1	1	Unsigned	0	+255	
short	2	2	Signed	-32768	+32767	
signed short	2	2	Signed	-32768	+32767	
unsigned short	2	2	Unsigned	0	+65535	
int	2	2	Signed	-32768	+32767	
signed int	2	2	Signed	-32768	+32767	
unsigned int	2	2	Unsigned	0	+65535	
long	4	2	Signed	-2147483648	+2147483647	
singed long	4	2	Signed	-2147483648	+2147483647	
unsigned long	4	2	Unsigned	0	+4294967295	
long long	8	2	Signed	-9223372036 854775808	+9223372036 854775807	
signed long long	8	2	Signed	-9223372036 854775808	+9223372036 54775807	
unsigned long long	8	2	Unsigned	0	+1844674407 3709551615	

Table 4 Basic types (2)

Data Type	Size (byte)	Alignment (byte)	Signed/ Unsigned	Data range Minimum Value	Maximum Value	Note
wchar_t	2	2	Unsigned	0	+65535	
char16_t	2	2	Unsigned	0	+65535	
char32_t	4	2	Unsigned	0	+4294967295	
bool	1	1	Unsigned	-	-	Only the bit 0 is meaningful. The bits from 1 to 7 are undefined.
float	4	2	Signed	1.17549435E-38F	3.40282347E+38F	
double (-double_size=4)	4	2	Signed	1.17549435E-38F	3.40282347E+38F	
double (-double_size=8)	8	2	Signed	2.2250738585072014E-308	1.7976931348623158E+308	
long double (-double_size=4)	4	2	Signed	1.17549435E-38F	3.40282347E+38F	The size is same as that of double but regarded as a different type.
long double (-double_size=8)	8	2	Signed	2.2250738585072014E-308	1.7976931348623158E+308	The size is same as that of double but regarded as a different type.

(2) Derived types

- Pointer and array types

Table 5 Pointer and array types

Data Type	Size(byte)	Alignment(byte)
Pointer type	near pointer	2
	far pointer	4
Lvalue reference type	near reference	2
Rvalue reference type	far reference	4
Pointer to data member type	2	2
Pointer to member function type	4	2
Array type	The size of the element type * The number of the elements	The alignment of the element type

- Enumeration type

Table 6 Enumeration type

The minimum value for enumerator	The maximum value for enumerator	Underlying type	Note
-128	127	signed char	-
0	255	unsigned char	If all enumerators are in the range 0-127, this representation applies.
-32768	32767	signed short	-
0	65535	unsigned short	If all enumerators are in the range 0-65535, this representation applies.
-2147483647	2147483647	signed long	-
0	4294967295	unsigned long	If all enumerators are in the range 0-4294967295, this representation applies.
-9223372036854775808	9223372036854775807	signed long long	-
Otherwise		signed long long	A warning will be output.

3.2 Language extension specifications

3.2.1 Reserved words

Please refer to “4.2.1 Reserved words” in the CC-RL User's Manual for detail of the keywords reserved by CC-RL.

3.2.2 Macros

The Table 6 shows the macros whose definitions differ along with the parameter given for the option `-lang`. Please also refer to “4.2.2 Macros” in the CC-RL Users' Manual as well for detail of the other macros.

Note that the values in the table are in decimal.

Table 7 Macros

Name	Definition when <code>-lang=cpp14</code> is specified	Definition when <code>-lang=c</code> or <code>-lang=c99</code> is specified
<code>__cplusplus</code>	201402L	Undefined
<code>__clang__</code>	1	Undefined
<code>__STDC_HOSTED__</code>	0	0 (when <code>-lang=c99</code> is specified)
<code>__STDC__</code>	1	1 (when <code>-strict_std</code> is specified)
<code>__STDC_VERSION__</code>	Undefined	199409L (when both <code>-lang=c</code> and <code>-strict_std</code> are specified) 199901L (when <code>-lang=c99</code> is specified)
<code>__STDC_IEC_559__</code>	Undefined	1 (when <code>-lang=c99</code> is specified)

3.2.3 #pragma directives

#pragma directives described in “4.2.4 #pragma directives” in the CC-RL User's Manual are not supported.

3.2.4 Intrinsic functions

Intrinsic functions described in “4.2.7 Intrinsic functions” in the CC-RL User's Manual are supported. Please refer to the CC-RL User's Manual for details.

4. SECTION SPECIFICATIONS

This section describes the names and the relocation attributes of the reserved sections when compiling under C++14 language specifications. Please refer to the CC-RL User's Manual for the other sections.

4.1 Section name

Table 8 Reserved section names

Default Section Name	Relocation Attribute	Description
.init_array	CONSTF	Section for the global constructors
.callt0	CALLT0	Section for the table used when callt functions called
.text	TEXT	Section for code (allocated to the near area)
.textf	TEXTF	Section for code (allocated to the far area)
.textf_unit64kp	TEXTF_UNIT64KP	Section for code (section is allocated so that the start address is an even address and the section does not exceed the (64 Kbytes - 1) boundary)
.const	CONST	ROM data (allocated to the near area) (within the mirror area)
.constf	CONSTF	ROM data (allocated to the far area)
.data	DATA	Section for near initialized data (with initial value)
.dataf	DATAF	Section for far initialized data (with initial value)
.sdata	SDATA	Section for initialized data (with initial value, allocated to saddr)
.bss	BSS	Section for data area (without initial value, allocated to near area)
.bssf	BSSF	Section for data area (without initial value, allocated to far area)
.sbss	SBSS	Section for data area (without initial value, allocated to saddr)
.option_byte	OPT_BYTE	Section specific for user option byte and on-chip debugging specification
.security_id	SECUR_ID	Section specific for security ID specification
.flash_security_id	FLASH_SECUR_ID	Section specific for flash programmer security ID specification
.vect<vector table address>	AT	Interrupt vector table If the -split_vect option is specified, a section is generated based on ".vect<vector table address>". The vector table address is in hexadecimal notation

5. LIBRARY SPECITICATIONS

5.1 Outline

The CC-RL Technical Preview Edition provides the dedicated libraries for compiling C++ source programs based on the software below. Please refer to the source program included in the compiler package for detail.

- compiler_rt
- libc++
- libc++abi
- newlib

5.2 Supplied Libraries

The following 6 libraries are provided for each of the CPU core types S1, S2, and S3 specified by the option `-cpu`. All these libraries are dedicated for uses with `-lang=cpp14` specified, and does not supported uses with `-lang=c` or `-lang=c99`.

Table 9 Supplied libraries

Library Name	Outline
rl78_libc.lib	The standard library (C99)
rl78_libm.lib	The standard math library (C99)
rl78_libgloss.lib	The low-level library
rl78_libcxx.lib	The standard library (C++14)
rl78_libcxxabi.lib	The runtime library for ABI support (C++14)
rl78_compiler-rt.lib	The runtime library for the compiler

* The libraries corresponding for the S2 core are built with multiplier and divider/multiply-accumulator enabled (`-use_mda=mda`).

* All the libraries assume single precision for the "double" and "long double" floating point type (`-dbl_size=4`).

5.3 Header Files

The header files required for using the C++ libraries of the Technical Preview Edition are listed below.

Table 10 Header Files

Category	File Name	Description
The standard library (C99)	<assert.h>	Header file for program diagnostics
	<complex.h>	Header file for complex number
	<ctype.h>	Header file for character conversion and classification
	<errno.h>	Header file for reporting error condition

Table 10 Header Files (2)

Category	File Name	Description
The standard library (C99)	<float.h>	Header file for floating-point representation and operation
	<inttypes.h>	Header file for the maximum-width integer type
	<iso646.h>	Header file for alternative spellings of macro names
	<limits.h>	Header file for quantitative limiting of integers
	<locale.h>	Header file for localization
	<math.h>	Header file for mathematical calculation
	<setjmp.h>	Header file for non-local jump
	<signal.h>	Header file for signal handling
	<stdarg.h>	Header file for supporting functions having variable arguments
	<stdbool.h>	Header file for logical types and values
	<stddef.h>	Header file for common definitions
	<stdint.h>	Header file for integer type of the specified width
	<stdio.h>	Header file for standard I/O
	<stdlib.h>	Header file for general utilities
	<string.h>	Header file for manipulation of sequential memory and character string
	<tgmath.h>	Header file for type generic mathematical calculation
	<time.h>	Header file for date and time
	<wchar.h>	Header file for utilities related to multibyte/wide character
	<wctype.h>	Header file for wide character conversion and classification
	The standard library (C++14)	<algorithm>
<array>		Header file for fixed sized sequential container
<bitset>		Header file for fixed sized sequential bit container
<chrono>		Header file for date and time
<codecvt>		Header file for character code conversion
<complex>		Header file for complex number
<condition_variable>		Header file for synchronization among the threads

Table 10 Header Files (3)

Category	File Name	Description
The standard library (C++14)	<deque>	Header file for double ended queue
	<exception>	Header file for exception handling
	<forward_list>	Header file for singly-linked list
	<fstream>	Header file for file stream
	<functional>	Header file for function object
	<future>	Header file for providing "future" pattern
	<initializer_list>	Header file for initializer list
	<iomanip>	Header file for I/O manipulator and formatting
	<ios>	Header file for base classes of iostream
	<iosfwd>	Header file for forward declaration of iostream
	<iostream>	Header file for standard iostream objects
	<istream>	Header file for input streams
	<iterator>	Header file for iterators
	<limits>	Header file for properties of the implementation's representation of the arithmetic type
	<list>	Header file for doubly-linked list
	<locale>	Header file for the information peculiar to a locale
	<map>	Header file for associative container of unique keys and values
	<memory>	Header file for memory management
	<mutex>	Header file for mechanisms for mutual exclusion
	<new>	Header file for dynamic storage allocation
	<numeric>	Header file for generalized numeric operations
	<ostream>	Header file for output streams
	<queue>	Header file for queue
	<random>	Header file for random number generation
	<ratio>	Header file for compile time rational arithmetic
	<regex>	Header file for regular expression template
	<scoped_allocator>	Header file for scoped allocator
<set>	Header file for associative container of unique keys	

Table 10 Header Files (4)

Category	File Name	Description
The standard library (C++14)	<sstream>	Header file for string stream
	<stack>	Header file for stack
	<stdexcept>	Header file for exception classes
	<streambuf>	Header file for stream buffers
	<string>	Header file for string classes
	<system_error>	Header file for system error support
	<tuple>	Header file for tuples
	<type_traits>	Header file for type traits
	<typeindex>	Header file for type indexes
	<unordered_map>	Header file for unordered associative containers of unique kyes and values
	<unordered_set>	Header file for unordered associative containers of unique keys
	<utility>	Header file for utility components
	<valarray>	Header file for numeric arrays
<vector>	Header file for vector	
The C compatible standard libraries	<cassert>	Header file compatible with assert.h
	<ccomplex>	Header file compatible with complex.h
	<cctype>	Header file compatible with ctype.h
	<cerrno>	Header file compatible with errno.h
	<cfloat>	Header file compatible with float.h
	< cinttypes>	Header file compatible with inttypes.h
	<ciso646>	Header file compatible with iso646.h
	<climits>	Header file compatible with limits.h
	<locale>	Header file compatible with locale.h
	<cmath>	Header file compatible with math.h
	<csetjmp>	Header file compatible with setjmp.h
	<csignal>	Header file compatible with signal.h
	<cstdarg>	Header file compatible with stdarg.h
	<cstdbool>	Header file compatible with stdbool.h
	<cstddef>	Header file compatible with stddef.h
	<cstdint>	Header file compatible with stdint.h
	<cstdio>	Header file compatible with stdio.h
	<cstdlib>	Header file compatible with stdlib.h
	<cstring>	Header file compatible with string.h
	<ctgmath>	Header file compatible with tgmath.h
	<ctime>	Header file compatible with time.h
	<wchar>	Header file compatible with wchar.h
	<wctype>	Header file compatible with wctype.h

6. STARTUP

6.1 Startup Routine

Before entering the main function, execute the following processes in addition to those described in 8.2 Startup Routine in CC-RL User's Manual.

6.1.1 Initialization of global objects of class type

Call the constructor for each object of class type declared with static storage duration.

The addresses of those constructors are stored in the section named `.init_array`. Put the following description in the startup routine for calling all of them.

```
MOVW    BC,#LOWW(SIZEOF(.init_array))
BR      $.L2_INIT
.L1_INIT:
DECW    BC
DECW    BC
MOV     ES,#HIGHW(STARTOF(.init_array))
MOVW    AX,ES:LOWW(STARTOF(.init_array))[BC]
MOV     CS,#0x00
PUSH    BC
CALL    AX
POP     BC
.L2_INIT:
CLRW    AX
CMPW    AX,BC
BNZ    $.L1_INIT
```

7. MESSAGE

7.1 Message Formats

There are two formats of message when `-lang=cpp14` is specified.

7.1.1 Format 1

This kind of format contains a message number as explained in “10 MESSAGE” in CC-RL User's Manual. Please refer to the manual for detail.

Those messages are numbered as:

0510000-0519999, 0530000-0539999, 0540000-0549999, 0550000-0559999, and
0560000-0569999.

(1) When the file name and line number are included

```
file-name (line-number) : message-type 05 message-number : message
```

(2) When the file name and line number aren't included

```
message-type 05 message-number : message
```

7.1.2 Format 2

This kind of format is output as below.

(1) When the file name, line number, and column number are included

```
file-name : line-number : column-number : message-type : message
```

(2) When neither the file name, line number, nor column number are included

```
message-type : message
```

7.2 Message Types

The message types are as follows.

Table 11 Message Types

Message Type		Description
Format 1	Format 2	
C	-	Internal error : Processing is aborted. No object codes are generated.
E	error	Error : Processing is aborted if a set number of errors occur. No object codes are generated.
F	fatal	Fatal error : Processing is aborted. No object codes are generated.
M	remark	Information : Processing continues. Object codes are generated.
W	warning	Warning : Processing continues. Object codes are generated (They might not be what the user intended).
-	note	Additional information for the other types of messages.

8. NOTES

8.1 Missing information for source level debugging

Information for source level debugging for the language specification listed below is not supported.

- Anonymous unions
- Namespaces
- Derived classes
 - Virtual base classes
 - Virtual functions
 - Pure virtual functions
- Templates

Revision History	CC-RL C++14 Technical Preview Version User's Manual
------------------	---

Rev.	Date	Description	
		Page	Summary
1.00	Jan.20.23	—	First Edition issued

CC-RL
C++14 Technical Preview Version User's Manual

Publication Date: Rev.1.00 Jan.20.23

Published by: Renesas Electronics Corporation

CC-RL
C++14 Technical Preview Version
User's Manual

