

Code Generator for RL78

 R20UT4632EJ0102
 Rev.1.02
 Apr.20.20

CS+ Code Generator for RL78 (CS+ for CC/CA,CX) V2.19.00,
 e² studio Code Generator Plug-in V2.15.1 / V2.16.100,
 AP4 for RL78 V1.18.00, Applilet3 for RL78 V1.18.00

Release Note

Introduction

Thank you for using the Code Generator for RL78. This document describes the restrictions and points for caution. Read this document before using the product. You can also check the latest release notes on the RENESAS website.

- [Code Generator for RL78 Release Note](#)

Contents

1.	Introduction.....	3
1.1	Product version.....	3
1.2	Operating environments	4
1.2.1	PC.....	4
1.2.2	Development tools.....	4
2.	Supported devices	5
3.	Changes	10
3.1	List of Changes.....	10
3.2	Details of Changes	10
3.2.1	Supports e ² studio 64-bit version	10
4.	History of Corrections Announced in Renesas Tool New	11
5.	Restrictions.....	16
5.1	List of Restrictions	16
5.2	Details for Restriction	18
5.2.1	Timer array unit input clock sauce.....	18
5.2.2	24-pin device TAU0 channel 1 setting restriction.....	18
5.2.3	Real-time clock API function	18
5.2.4	Unit for 'Gain setting' of $\Delta\Sigma$ A/D CONVERTER.....	18
5.2.5	Restrictions on CSI continuous transfer mode.....	19
5.2.6	Incorrect clock mode selection (SELPLL) of R_CGC_Set_ClockMode() function.....	21
5.2.7	Incorrect function description in data lash library	21
5.2.8	Operation clock when fSUB and fIL are selected in TAU input pulse interval measurement	21
5.2.9	64-bit environment restrictions	22

6. Cautions	23
6.1 List for Cautions.....	23
6.2 Details for Cautions	25
6.2.1 Online Help (Applilet3, AP4).....	25
6.2.2 Coding rule of MISRA-C.....	25
6.2.3 High-speed on-chip oscillator frequency select register	25
6.2.4 Internal low-speed or internal high-speed oscillator trimming.....	25
6.2.5 Serial array unit	25
6.2.6 Flash memory CRC operation function (high-speed CRC).....	25
6.2.7 Port mode select register (PMS)	25
6.2.8 LIN-bus function of UART	25
6.2.9 Extension code, multimaster, wakeup function of serial interface IICA or IIC0	25
6.2.10 CAN controllers	25
6.2.11 Safety Functions.....	25
6.2.12 USB	26
6.2.13 RI78V4 project.....	26
6.2.14 DTC function (CS+ for CA,CX).....	26
6.2.15 High Speed DTC chain transfer	27
6.2.16 Fast Mode Plus setting in IICA slave.....	27
6.2.17 High-speed on-chip oscillator (CS+ for CA,CX)	27
6.2.18 Pin Configurator (CS+ for CA,CX).....	27
6.2.19 Version notation of RL78/G13A generation file.....	27
Revision History	28

1. Introduction

The Code Generator for RL78 is a software tool to generate control programs (device driver programs) for peripheral modules (timers, UART, A/D, etc.). It generates device driver codes using user settings through GUI. Initialize code and API (Application Programming Interface) functions are provided. The following products are provided as code generator for RL78.

- Code Generator Plug-in for RL78 (IDE CS+ for CC, CS+ for CA,CX, e² studio)
- AP4 for RL78
- Applilet3 for RL78

1.1 Product version

- CS+ Code Generator for RL78 (CS+ for CC) 2.19.00
- CS+ Code Generator for RL78 (CS+ for CA,CX) 2.19.00
- e² studio V7.8.0 Code Generator Plug-in 2.15.1
- e² studio 2020-04 (64-bit) Code Generator Plug-in 2.16.100
- AP4 for RL78 1.18.00 (3.08.04.01)

Group	Version	Group	Version
RL78/D1A	V2.04.03.01	RL78/G13, G13A	V2.05.04.02
RL78/F12	V2.04.04.02	RL78/G14	V2.05.04.02
RL78/F13	V2.03.05.02	RL78/G1A	V2.04.02.02
RL78/F14	V2.03.05.02	RL78/I1A	V2.04.03.01
RL78/F15	V1.01.05.02	RL78/L12	V2.04.02.01
RL78/G12	V2.04.04.02		

- Applilet3 for RL78 1.18.00 (1.10.05.01)

Group	Version	Group	Version
RL78/F1E	V1.01.04.02	RL78/H1D	V1.00.00.05
RL78/G10	V1.05.03.02	RL78/I1B	V1.03.02.03
RL78/G11	V1.02.03.02	RL78/I1C	V1.01.04.02
RL78/G1C	V1.03.02.01	RL78/I1D	V1.01.03.02
RL78/G1D	V1.01.02.03	RL78/I1E	V1.03.03.02
RL78/G1E	V1.04.02.04	RL78/L13	V1.04.02.03
RL78/G1F	V1.01.03.02	RL78/I1A	V1.01.03.01
RL78/G1G	V1.01.01.03	RL78/L1C	V1.03.01.04
RL78/G1H	V1.01.03.02		

1.2 Operating environments

1.2.1 PC

- IBM PC/AT compatible (Windows® 10, Windows® 8.1)
- Processor: At least 1 GHz (the product supports hyper-threading and multi-core CPUs)
- Memory capacity: 2 GB or more is recommended. At least 1 GB (or 2 GB for 64-bit versions of Windows®) is required.
- Hard disk capacity: At least 200 MB available
- Display resolution: 1024x768 or higher; at least 65536 colors
- Required elements of the software environment other than the Windows OS: .NET Framework 4.5 plus a language pack

1.2.2 Development tools

1.2.2.1 CS+

- Integrated development environment CS+ from Renesas, V8.03.00 or later
- Renesas electronics Compiler for RL78 [CC-RL] V1.08 or later
- Renesas electronics Compiler for 78K0R [CA78K0R] V1.30 or later

1.2.2.2 e² studio, AP4 for RL78 and Applilet3 for RL78

- Integrated development environment e² studio (64-bit) from Renesas, 2020-04 or later
- Integrated development environment e² studio (32-bit) from Renesas, V7.8.0 or later
- Renesas electronics Compiler for RL78 [CC-RL] V1.08 or later
- Renesas GCC for RL78 V4.9 or later
- IAR Embedded Workbench for Renesas RL78 V2.21 or later

2. Supported devices

The devices supported by the Code Generator for RL78 are listed below.

Table 2-1. Supported devices

○: Support -: Not support

Group (HW Manual number)	PIN	Device name	CS+	e ² studio	AP4	Appliiers3
RL78/F12 Group (R01UH0231EJ0111)	20pin	R5F1096E, R5F1096D, R5F1096C, R5F1096B, R5F1096A, R5F10968	○	○	-	○
	30pin	R5F109AE, R5F109AD, R5F109AC, R5F109AB, R5F109AA	○	○	-	○
	32pin	R5F109BE, R5F109BD, R5F109BC, R5F109BB, R5F109BA	○	○	-	○
	48pin	R5F109GE, R5F109GD, R5F109GC, R5F109GB, R5F109GA	○	○	-	○
	64pin	R5F109LE, R5F109LD, R5F109LC, R5F109LB, R5F109LA	○	○	-	○
RL78/F13 Group (R01UH0368EJ0210)	20pin	R5F10A6A, R5F10A6C, R5F10A6D, R5F10A6E	○	○	-	○
	30pin	R5F10AAA, R5F10AAC, R5F10AAD, R5F10AAE, R5F10BAC, R5F10BAD, R5F10BAE, R5F10BAF, R5F10BAG	○	○	-	○
	32pin	R5F10ABA, R5F10ABC, R5F10ABD, R5F10ABE, R5F10BBC, R5F10BBD, R5F10BBE, R5F10BBF, R5F10BBG	○	○	-	○
	48pin	R5F10AGA, R5F10AGC, R5F10AGD, R5F10AGE, R5F10AGF, R5F10AGG, R5F10BGC, R5F10BGD, R5F10BGE, R5F10BGF, R5F10BGG	○	○	-	○
	64pin	R5F10BLC, R5F10ALD, R5F10ALE, R5F10ALF, R5F10ALG, R5F10BLC, R5F10BLD, R5F10BLE, R5F10BLF, R5F10BLG	○	○	-	○
	80pin	R5F10AME, R5F10AMF, R5F10AMG, R5F10BME, R5F10BMF, R5F10BMG	○	○	-	○
RL78/F14 Group (R01UH0368EJ0210)	30pin	R5F10PAD, R5F10PAE	○	○	-	○
	32pin	R5F10PBD, R5F10PBE	○	○	-	○
	48pin	R5F10PGD, R5F10PGE, R5F10PGF, R5F10PGG, R5F10PGH, R5F10PGJ	○	○	-	○
	64pin	R5F10PLE, R5F10PLF, R5F10PLG, R5F10PLH, R5F10PLJ	○	○	-	○
	80pin	R5F10PME, R5F10PMF, R5F10PMG, R5F10PMH, R5F10PMJ	○	○	-	○
	100pin	R5F10PPE, R5F10PPF, R5F10PPG, R5F10PPH, R5F10PPJ	○	○	-	○
RL78/F15 Group (R01UH0559EJ0100)	48pin	R5F113GL, R5F113GK	○	○	-	○
	64pin	R5F113LL, R5F113LK	○	○	-	○
	80pin	R5F113ML, R5F113MK	○	○	-	○
	100pin	R5F113PL, R5F113PK, R5F113PJ, R5F113PH, R5F113PG	○	○	-	○
	144pin	R5F113TL, R5F113TK, R5F113TJ, R5F113TH, R5F113TG	○	○	-	○
RL78/F1E Group (R01UH0611EJ0052)	64pin	R5F11KLE, R5F11LLE, R5F11KLF, R5F11LLF, R5F11KLG, R5F11LLG	○	○	○	-

Table 2-2. Supported devices

○: Support -: Not support

Group (HW Manual number)	PIN	Device name	CS+	e ² studio	AP4	Applifiers3
RL78/G10 Group (R01UH0384EJ0311)	10pin	R5F10Y14, R5F10Y16, R5F10Y17	○	○	○	-
	16pin	R5F10Y44, R5F10Y46, R5F10Y47	○	○	○	-
RL78/G11 Group (R01UH0637EJ0110)	10pin	R5F1051A	○	○	○	-
	16pin	R5F1054A	○	○	○	-
	20pin	R5F1056A	○	○	○	-
	24pin	R5F1057A	○	○	○	-
	25pin	R5F1058A	○	○	○	-
RL78/G12 Group (R01UH0200EJ0210)	20pin	R5F10266, R5F10267, R5F10268, R5F10269, R5F1026A, R5F10366, R5F10367, R5F10368, R5F10369, R5F1036A	○	○	-	○
	24pin	R5F10277, R5F10278, R5F10279, R5F1027A, R5F10377, R5F10378, R5F10379, R5F1037A	○	○	-	○
	30pin	R5F102A7, R5F102A8, R5F102A9, R5F102AA, R5F103A7, R5F103A8, R5F103A9, R5F103AA	○	○	-	○
RL78/G13 Group (R01UH0146EJ0330)	20pin	R5F1006A, R5F1006C, R5F1006D, R5F1006E, R5F1016A, R5F1016C, R5F1016D, R5F1016E	○	○	-	○
	24pin	R5F1007A, R5F1007C, R5F1007D, R5F1007E, R5F1017A, R5F1017C, R5F1017D, R5F1017E	○	○	-	○
	25pin	R5F1008A, R5F1008C, R5F1008D, R5F1008E, R5F1018A, R5F1018C, R5F1018D, R5F1018E	○	○	-	○
	30pin	R5F100AA, R5F100AC, R5F100AD, R5F100AE, R5F100AF, R5F100AG, R5F101AA, R5F101AC, R5F101AD, R5F101AE, R5F101AF, R5F101AG	○	○	-	○
	32pin	R5F100BA, R5F100BC, R5F100BD, R5F100BE, R5F100BF, R5F100BG, R5F101BA, R5F101BC, R5F101BD, R5F101BE, R5F101BF, R5F101BG	○	○	-	○
	36pin	R5F100CA, R5F100CC, R5F100CD, R5F100CE, R5F100CF, R5F100CG, R5F101CA, R5F101CC, R5F101CD, R5F101CE, R5F101CF, R5F101CG	○	○	-	○
	40pin	R5F100EA, R5F100EC, R5F100ED, R5F100EE, R5F100EF, R5F100EG, R5F100EH, R5F101EA, R5F101EC, R5F101ED, R5F101EE, R5F101EF, R5F101EG, R5F101EH	○	○	-	○
	44pin	R5F100FA, R5F100FC, R5F100FD, R5F100FE, R5F100FF, R5F100FG, R5F100FH, R5F100FJ, R5F100FK, R5F100FL, R5F101FA, R5F101FC, R5F101FD, R5F101FE, R5F101FF, R5F101FG, R5F101FH, R5F101FJ, R5F101FK, R5F101FL	○	○	-	○
	48pin	R5F100GA, R5F100GC, R5F100GD, R5F100GE, R5F100GF, R5F100GG, R5F100GH, R5F100GJ, R5F100GK, R5F100GL, R5F101GA, R5F101GC, R5F101GD, R5F101GE, R5F101GF, R5F101GG, R5F101GH, R5F101GJ, R5F101GK, R5F101GL	○	○	-	○
	52pin	R5F100JC, R5F100JD, R5F100JE, R5F100JF, R5F100JG, R5F100JH, R5F100JJ, R5F100JK, R5F100JL, R5F101JC, R5F101JD, R5F101JE, R5F101JF, R5F101JG, R5F101JH, R5F101JJ, R5F101JK, R5F101JL	○	○	-	○

Table 2-3. Supported devices

○: Support -: Not support

Group (HW Manual number)	PIN	Device name	CS+	e ² studio	AP4	Applifiers3
RL78/G13 Group (R01UH0146EJ0330)	64pin	R5F100LC, R5F100LD, R5F100LE, R5F100LF, R5F100LG, R5F100LH, R5F100LJ, R5F100LK, R5F100LL, R5F101LC, R5F101LD, R5F101LE, R5F101LF, R5F101LG, R5F101LH, R5F101LJ, R5F101LK, R5F101LL	○	○	-	○
	80pin	R5F100MF, R5F100MG, R5F100MH, R5F100MJ, R5F100MK, R5F100ML, R5F101MF, R5F101MG, R5F101MH, R5F101MJ, R5F101MK, R5F101ML	○	○	-	○
	100pin	R5F100PF, R5F100PG, R5F100PH, R5F100PJ, R5F100PK, R5F100PL, R5F101PF, R5F101PG, R5F101PH, R5F101PJ, R5F101PK, R5F101PL	○	○	-	○
	128pin	R5F100SH, R5F100SJ, R5F100SK, R5F100SL, R5F101SH, R5F101SJ, R5F101SK, R5F101SL	○	○	-	○
RL78/G13A Group (R01UH0856JJ0050)	44pin	R5F140FK, R5F140FL	○	○	-	○
	48pin	R5F140GK, R5F140GL	○	○	-	○
	64pin	R5F140LK, R5F140LL	○	○	-	○
	100pin	R5F140PK, R5F140PL	○	○	-	○
RL78/G14 Group (R01UH0186EJ0330)	30pin	R5F104AA, R5F104AC, R5F104AD, R5F104AE, R5F104AF, R5F104AG	○	○	-	○
	32pin	R5F104BA, R5F104BC, R5F104BD, R5F104BE, R5F104BF, R5F104BG	○	○	-	○
	36pin	R5F104CA, R5F104CC, R5F104CD, R5F104CE, R5F104CF, R5F104CG	○	○	-	○
	40pin	R5F104EA, R5F104EC, R5F104ED, R5F104EE, R5F104EF, R5F104EG, R5F104EH	○	○	-	○
	44pin	R5F104FA, R5F104FC, R5F104FD, R5F104FE, R5F104FF, R5F104FG, R5F104FH, R5F104FJ	○	○	-	○
	48pin	R5F104GA, R5F104GC, R5F104GD, R5F104GE, R5F104GF, R5F104GG, R5F104GH, R5F104GJ, R5F104GK, R5F104GL	○	○	-	○
	52pin	R5F104JC, R5F104JD, R5F104JE, R5F104JF, R5F104JG, R5F104JH, R5F104JJ	○	○	-	○
	64pin	R5F104LC, R5F104LD, R5F104LE, R5F104LF, R5F104LG, R5F104LH, R5F104LJ, R5F104LK, R5F104LL	○	○	-	○
	80pin	R5F104MF, R5F104MG, R5F104MH, R5F104MJ, R5F104MK, R5F104ML	○	○	-	○
	100pin	R5F104PF, R5F104PG, R5F104PH, R5F104PJ, R5F104PK, R5F104PL	○	○	-	○
RL78/G1A Group (R01UH0305EJ0200)	20pin	R5F10E8A, R5F10E8C, R5F10E8D, R5F10E8E	○	○	-	○
	24pin	R5F10EBA, R5F10EBC, R5F10EBD, R5F10EBE	○	○	-	○
	30pin	R5F10EGA, R5F10EGC, R5F10EGD, R5F10EGE	○	○	-	○
	64pin	R5F10ELC, R5F10ELD, R5F10ELE	○	○	-	○
RL78/G1C Group (R01UH0348EJ0100)	32pin	R5F10JBC, R5F10KBC	○	○	○	-
	48pin	R5F10JGC, R5F10KGC	○	○	○	-

Table 2-4. Supported devices

○: Support -: Not support

Group (HW Manual number)	PIN	Device name	CS+	e ² studio	AP4	Applifiers ³
RL78/G1D Group (R01UH0515EJ0100)	48pin	R5F11AGG, R5F11AGH, R5F11AGJ	○	○	○	-
RL78/G1E Group (R01UH0353EJ0101)	64pin	R5F10FLC, R5F10FLD, R5F10FLE	○	○	○	-
	80pin	R5F10FMC, R5F10FMD, R5F10FME	○	○	○	-
RL78/G1F Group (R01UH0516EJ0100)	24pin	R5F11B7C, R5F11B7E	○	○	○	-
	32pin	R5F11BBC, R5F11BBE	○	○	○	-
	36pin	R5F11BCC, R5F11BCE	○	○	○	-
	48pin	R5F11BGC, R5F11BGE	○	○	○	-
	64pin	R5F11BLC, R5F11BLE	○	○	○	-
RL78/G1G Group (R01UH0499EJ0100)	30pin	R5F11EA8, R5F11EAA	○	○	○	-
	32pin	R5F11EB8, R5F11EBA	○	○	○	-
	44pin	R5F11EF8, R5F11EFA	○	○	○	-
RL78/G1H Group (R01UH0575EJ0100)	64pin	R5F11FLJ, R5F11FLK, R5F11FLL	○	○	○	-
RL78/H1D Group (R01UH0756JJ0080)	48pin	R5F11NGG, R5F11NGF	○	○	○	-
	64pin	R5F11NLG, R5F11PLG, R5F11NLF, R5F11PLF	○	○	○	-
	80pin	R5F11RMG, R5F11NMG, R5F11NMF, R5F11NME	○	○	○	-
RL78/I1A Group (R01UH0169EJ0210)	20pin	R5F1076C	○	○	-	○
	30pin	R5F107AC, R5F107AE	○	○	-	○
	38pin	R5F107DE	○	○	-	○
RL78/I1B Group (R01UH0407EJ0100)	80pin	R5F10MME, R5F10MMG	○	○	○	-
	100pin	R5F10MPE, R5F10MPG	○	○	○	-
RL78/I1C Group (R01UH0587JJ0051)	64pin	R5F10NLE, R5F10NLG, R5F11TLE, R5F11TLG	○	○	○	-
	80pin	R5F10NME, R5F10NMG, R5F10NMJ	○	○	○	-
	100pin	R5F10NPJ	○	○	○	-
RL78/I1D Group (R01UH0474JJ0100)	20pin	R5F11768, R5F1176A	○	○	○	-
	24pin	R5F11778, R5F1177A	○	○	○	-
	30pin	R5F117A8, R5F117AA, R5F117AC	○	○	○	-
	32pin	R5F117BA, R5F117BC	○	○	○	-
	48pin	R5F117GA, R5F117GC	○	○	○	-

Table 2-5. Supported devices

○: Support -: Not support

Group (HW Manual number)	PIN	Device name	CS+	e ² studio	AP4	Applifiers3
RL78/L1E Group (R01UH0524JJ0100)	32pin	R5F11CBC	○	○	○	-
	36pin	R5F11CCC	○	○	○	-
RL78/L12 Group (R01UH0330EJ0200)	32pin	R5F10RBC, R5F10RBA, R5F10RB8	○	○	-	○
	44pin	R5F10RFC, R5F10RFA, R5F10RF8	○	○	-	○
	48pin	R5F10RGC, R5F10RGA, R5F10RG8	○	○	-	○
	52pin	R5F10RJC, R5F10RJA, R5F10RJ8	○	○	-	○
	64pin	R5F10RLC, R5F10RLA	○	○	-	○
RL78/L13 Group (R01UH0382EJ0100)	64pin	R5F10WLA, R5F10WLC, R5F10WLD, R5F10WLE, R5F10WLF, R5F10WLG	○	○	○	-
	80pin	R5F10WMA, R5F10WMC, R5F10WMD, R5F10WME, R5F10WMF, R5F10WMG	○	○	○	-
RL78/L1A Group (R01UH0636EJ0100)	80pin	R5F11MMD, R5F11MME, R5F11MMF	○	○	○	-
	100pin	R5F11MPE, R5F11MPF, R5F11MPG	○	○	○	-
RL78/L1C Group (R01UH0409EJ0100)	80pin	R5F110MJ, R5F110MH, R5F110MG, R5F110MF, R5F110ME, R5F111MJ, R5F111MH, R5F111MG, R5F111MF, R5F111ME	○	○	○	-
	100pin	R5F110PJ, R5F110PH, R5F110PG, R5F110PF, R5F110PE, R5F111PJ, R5F111PH, R5F111PG, R5F111PF, R5F111PE	○	○	○	-
RL78/D1A Group (R01UH0317EJ0003)	48pin	R5F10CGB, R5F10CGC, R5F10CGD, R5F10DGC, R5F10DGD, R5F10DGE	-	○	-	○
	64pin	R5F10CLD, R5F10DLD, R5F10DLE	-	○	-	○
	80pin	R5F10CMD, R5F10CME, R5F10DMD, R5F10DME, R5F10DMF, R5F10DMG, R5F10DMJ	-	○	-	○
	100pin	R5F10DPE, R5F10DPF, R5F10DPG, R5F10DPJ, R5F10TPJ	-	○	-	○

3. Changes

Describes the changes in this release of the Code Generator for RL78.

3.1 List of Changes

Table 3-1. List of Points for Change 1/2

○: Applicable, /: Not applicable

No	Description	Group													
		RL78/D1A	RL78/G10	RL78/G11	RL78/G12	RL78/G13, G13A	RL78/G14	RL78/G1A	RL78/G1C	RL78/G1D	RL78/G1E	RL78/G1F	RL78/G1G	RL78/G1H	RL78/H1D
1	Supports e ² studio 64-bit version	○	○	○	○	○	○	○	○	○	○	○	○	○	○

Table 3-2. List of Points for Change 2/2

○: Applicable, /: Not applicable

No	Description	Group													
		RL78/F12	RL78/F13	RL78/F14	RL78/F15	RL78/F1E	RL78/I1A	RL78/I1B	RL78/I1C	RL78/I1D	RL78/I1E	RL78/L12	RL78/L13	RL78/L1A	RL78/L1C
1	Supports e ² studio 64-bit version	○	○	○	○	○	○	○	○	○	○	○	○	○	○

3.2 Details of Changes

3.2.1 Supports e² studio 64-bit version

The Code Generator can be used in e² studio 2020-04 (64-bit).

4. History of Corrections Announced in Renesas Tool New

This section is a summary of corrections announced in Renesas Tool News.

Issue Date	Document No.	Description	Device Concerned	Fixed version
May 21, 2012	120521/tn2	With generating codes for the R5F1007x and R5F1017x MCUs, RL78/G13 group	RL78/G13	CS+ V1.00.06
Aug. 01, 2012	120801/tn3	Problems arising in Applilet3 for RL78/G13 and Applilet3 for RL78/G14	RL78/G13, RL78/G14	CS+ V1.00.06
Sep. 01, 2012	120901/tn1	With using the code generator for the RL78/G12 group	RL78/G12	CS+ V1.00.06
Feb. 01, 2013	130201/tn1	With using the code generator for the RL78/G14 group of MCUs	RL78/G14	CS+ V2.00.00
Jul. 01, 2013	130701/tn1	When edited source codes disappear	RL78/F12, RL78/F13, RL78/F14, RL78/F15, RL78/G10, RL78/G12, RL78/G13, RL78/G14, RL78/G1A, RL78/G1C, RL78/G1D, RL78/G1E, RL78/G1F, RL78/G1G, RL78/G1H, RL78/I1A, RL78/I1D, RL78/I1E, RL78/L12, RL78/L13, RL78/L1C	CS+ V2.11.00
		When the port cannot be set properly	RL78/G1A	CS+ V2.00.01
Aug. 01, 2013	130801/tn1	With using the code generator for the RL78/G12 group of MCUs	RL78/G12	CS+ V2.00.01
Oct. 16, 2013	131016/tn1	2. When a RL78/G13 product in a 100-pin package is selected	RL78/G13	CS+ V2.03.00
		3. With the key input interrupt setting	RL78/L12	CS+ V2.03.00
		4. With A/D converter operation setting	RL78/G1A	CS+ V2.03.00
		5. When the timer KB20 is in use	RL78/L13	CS+ V2.03.00

Issue Date	Document No.	Description	Device Concerned	Fixed version
Apr. 16, 2014	140416/tn5	With selecting the 20-pin, 30-pin, or 32-pin package for the RL78/F13 or RL78/F14 group	RL78/F13, RL78/F14	CS+ V2.04.00
		With using the remote control carrier wave mask signal in the RL78/L12 or RL78/L13 group	RL78/L12, RL78/L13	CS+ V2.04.00
		With processing to reflect the pin configurator when the A/D converter is set in the RL78/G12 group	RL78/G12	CS+ V2.04.00
		With the case when ports that are not available in the MCU are displayed in the RL78/G14 group	RL78/G14	CS+ V2.04.00
Jul. 01, 2014	140701/tn1	With setting port 2	RL78/L13	CS+ V2.07.00
		With setting an interval timer	RL78/G10, RL78/G12, RL78/G13, RL78/G14, RL78/G1A, RL78/G1C, RL78/L12, RL78/L13, RL78/L1C, RL78/I1A	CS+ V2.07.00
Aug. 16, 2014	140816/tn1	With setting of P20 and P21 of port2	RL78/L1C	CS+ V2.05.00
		With setting of port1	RL78/G14	CS+ V2.05.00
Nov, 1, 2014	141101/tn2	1. Point for Caution on Settings for CPU Stack Pointer Monitoring	RL78/F13	CS+ V2.07.00
		2. Point for Caution on Writing to the Serial Flag Clear Trigger Register (SIR) When Using 3-wire Serial (CSI) Transfer	RL78/F14	CS+ V2.07.00
Dec. 16, 2014	141216/tn3	1. Code Generated for Comparator Settings	RL78/I1A	CS+ V2.07.00
		2. DTC Settings	RL78/F13, RL78/F14	CS+ V2.07.00
		3. Setting the Voltage Detection Circuit to "Interrupt Mode"	RL78/L12, RL78/I1A, RL78/G1A, RL78/F13, RL78/F14	CS+ V2.07.00
		4. Saving Projects with Settings for the A/D Convertor	RL78/L1C	CS+ V2.07.00
		5. Reflection of Pin Configurations in Generated Code	RL78/G12, RL78/ G13, RL78/G14	CS+ V2.07.00

Issue Date	Document No.	Description	Device Concerned	Fixed version
Jul. 16, 2015	150716/tn2	1. Clock Generation Circuit (PLL Circuit Operation)	RL78/F13, RL78/F14, RL78/G1C, RL78/L1C	CS+ V2.11.00 AP4 V1.10.00 Applilet3 V1.10.00
		2. Setting P40 of Port 4	RL78/F12, RL78/F13, RL78/F14, RL78/G10, RL78/G12, RL78/G13, RL78/G14, RL78/G1A, RL78/G1C, RL78/G1E, RL78/G1F, RL78/G1G, RL78/I1A, RL78/I1D, RL78/L1C, RL78/L12, RL78/L13	CS+ V2.11.00 AP4 V1.10.00 Applilet3 V1.10.00
		3. Code Generated for UART0 and UARTF	RL78/F12	CS+ V2.11.00 Applilet3 V1.10.00
Nov. 16, 2015	151116/tn2	1. Indication of Channels of Serial Interface IICA	RL78/G14	CS+ V2.11.00 Applilet3 V1.10.00
		2. Procedure for Setting the PLL Clock	RL78/F13, RL78/F14, RL78/F15	CS+ V2.11.00 Applilet3 V1.10.00
Jan. 16, 2016	160116/tn5	Transfer of data with a length of 10 or more bits through an element of a serial array unit configured as a CSI or data with a length of 16 bits through an element configured as a UART	RL78/F12, RL78/F13, RL78/F14, RL78/F15, RL78/D1A	CS+ V2.11.00 Applilet3 V1.10.00
Feb. 16, 2016	160216/tn5	1. Using the error interrupt of serial array unit 4 as UART4 or DALI4	RL78/I1A	CS+ V2.11.00 Applilet3 V1.10.00
		2. Using serial array unit 4 as DALI4	RL78/I1A	CS+ V2.11.00 Applilet3 V1.10.00
Mar. 16, 2016	160316/tn1	Pin settings for the IICA serial interface when setting the PIOR to change the assignment of pin functions	RL78/G12	CS+ V2.11.00 Applilet3 V1.10.00

Issue Date	Document No.	Description	Device Concerned	Fixed version
Jun. 16, 2016	R20TS003 8EJ0100	Scan Mode of A/D Converter	RL78/F12, RL78/F13, RL78/F14, RL78/F15, RL78/G1A	CS+ V2.12.00 Applilet3 V1.11.00
Aug. 01, 2016	R20TS004 5EJ0100	Peripheral I/O redirection register 0 (PIOR0)	RL78/G1F	CS+ V2.12.00 AP4 V1.11.00
Mar. 1, 2017	R20TS013 9EJ0100	1. Input of Ports P10 and P11	RL78/G13 (20/24/25pin product)	CS+ V2.14.00 Applilet3 V1.13.00
		2. Port Settings Related to Reset Processing	RL78/F12 (20pin product)	CS+ V2.14.00 Applilet3 V1.13.00
Dec. 16, 2017	R20TS024 4EJ0100	When Continuous Transfer Mode is Selected in the CSI Configuration	RL78/D1A, RL78/F12, RL78/F13, RL78/F14, RL78/F15, RL78/L12	CS+ V2.16.00
Mar. 16, 2018	R20TS029 0EJ0100	When Opening a Project for RL78/G11 Created by a Previous Version of Code Generator	RL78/G11 (20-pin R5F1056A)	CS+ V2.16.00 AP4 V1.15.00 Applilet3 V1.15.00
May. 16, 2018	R20TS031 3EJ0100	Writing to Port-Related Registers for Unused Pins	RL78/I1D	CS+ V2.16.00 AP4 V1.15.00
Nov. 16, 2018	R20TS037 0EJ0100	When setting the Serial UART4	RL78/I1A	CS+ V2.17.00 Applilet3 V1.16.00
Jun. 1, 2019	R20TS04 32EJ0100	1. PLL clock setting of clock generator	RL78/F13, RL78/F14, RL78/F15	CS+ V2.18.00 Applilet3 V1.17.00
		2. RTC operation clock setting of clock generator	RL78/F13, RL78/F14, RL78/F15	CS+ V2.18.00 Applilet3 V1.17.00
			RL78/D1A	CS+ V2.19.00 Applilet3 V1.18.00

Issue Date	Document No.	Description	Device Concerned	Fixed version
2019/08/01	R20TS045 9JJ0100	1. When using IICA0 or IICA1 as a Single Master System	RL78/G10, RL78/G11, RL78/G12, RL78/G13, RL78/G14, RL78/F12, RL78/F13, RL78/F14, RL78/F15	CS+ V2.19.00 AP4 V1.18.00 Applilet3 V1.18.00
			RL78/G1A, RL78/G1C, RL78/G1D, RL78/G1F, RL78/G1H, RL78/H1D, RL78/I1A, RL78/I1B, RL78/I1C, RL78/L12, RL78/L13, RL78/L1A, RL78/L1C	Not supported
		2. When using the R_ADC_Set_ADChannel() function in the A/D converter	RL78/D1A, RL78/G1A, RL78/G1F, RL78/I1D	CS+ V2.19.00 AP4 V1.18.00 Applilet3 V1.18.00
2019/09/16	R20TS047 2JJ0100	1. When using the data flash library	RL78/D1A, RL78/G11, RL78/G12, RL78/G13, RL78/G14, RL78/F12, RL78/F13, RL78/F14, RL78/F15	CS+ V2.19.00 AP4 V1.18.00 Applilet3 V1.18.00

5. Restrictions

This section describes the restriction regarding the Code Generator for RL78.

5.1 List of Restrictions

Table 5-1. List of Points of Restriction 1/2

○: Applicable, /: Not applicable

No	Description	Group													
		RL78/D1A	RL78/G10	RL78/G11	RL78/G12	RL78/G13, G13A	RL78/G14	RL78/G1A	RL78/G1C	RL78/G1D	RL78/G1E	RL78/G1F	RL78/G1G	RL78/G1H	RL78/H1D
1	Timer array unit input clock sauce	/	/	/	/	/	/	/	/	/	/	/	/	/	/
2	24-pin device TAU0 channel 1 setting restriction	/	/	/	/	/	/	/	/	/	/	○	/	/	/
3	Real-time clock API function	/	/	/	/	/	/	/	/	/	/	○	/	○	/
4	Unit for 'Gain setting' of $\Delta\Sigma$ A/D CONVERTER	/	/	/	/	/	/	/	/	/	/	/	/	/	○
5	Restrictions on CSI continuous transfer mode	○	/	/	/	/	/	○	○	○	○	○	○	○	○
6	Incorrect clock mode selection (SELPLL) of R_CGC_Set_ClockMode() function	/	/	/	/	/	/	/	/	/	/	/	/	/	/
7	Incorrect function description in data lash library	/	/	○	○	○	○	/	/	/	/	/	/	/	/
8	Operation clock when fSUB and fIL are selected in TAU input pulse interval measurement	/	/	/	/	○	○	/	/	/	/	/	/	/	/
9	64-bit environment restrictions	○	/	/	/	/	/	/	/	/	/	/	/	/	/

Table 5-2. List of Points of Restriction 2/2

○: Applicable, /: Not applicable

No	Description	Group													
		RL78/F12	RL78/F13	RL78/F14	RL78/F15	RL78/F1E	RL78/1A	RL78/1B	RL78/1C	RL78/1D	RL78/1E	RL78/L12	RL78/L13	RL78/L1A	RL78/L1C
1	Timer array unit input clock sauce	○	○	○	/	/	/	/	/	/	/	/	/	/	/
2	24-pin device TAU0 channel 1 setting restriction	/	/	/	/	/	/	/	/	/	/	/	/	/	/
3	Real-time clock API function	/	/	/	/	/	/	/	/	○	/	/	/	/	/
4	Unit for 'Gain setting' of $\Delta\Sigma$ A/D CONVERTER	/	/	/	/	/	/	/	/	/	/	/	/	/	/
5	Restrictions on CSI continuous transfer mode	/	/	/	/	/	○	○	○	○	○	○	○	○	○
6	Incorrect clock mode selection (SELPLL) of R_CGC_Set_ClockMode() function	/	/	/	/	○	/	/	/	/	/	/	/	/	/
7	Incorrect function description in data lash library	○	○	○	○	/	/	/	/	○	/	/	/	/	/
8	Operation clock when fSUB and fIL are selected in TAU input pulse interval measurement	○	/	/	/	○	/	/	/	/	/	/	/	/	/
9	64-bit environment restrictions	/	/	/	/	/	/	/	/	/	/	/	/	/	/

5.2 Details for Restriction

5.2.1 Timer array unit input clock source

When the clock source of a timer input is set as a RTC1HZ output by setup of a timer array unit, a setup about the output of the RTC1HZ terminal of a real-time clock becomes invalid. The code which outputs RTC1HZ then is not generated.

[Workaround] When you set to a RTC1HZ signal by setup of a timer array unit, please choose a setup which uses a real-time clock and add the code which outputs RTC1HZ.

5.2.2 24-pin device TAU0 channel 1 setting restriction

In the 24-pin device, interval timer is only selectable for the TAU0 channel 1 setting.

[Workaround] There is no workaround.
In the 32-pin device, other timer functions besides "Interval timer" are selectable for the TAU0 channel 1 setting. Refer to the setting to make a correction.

5.2.3 Real-time clock API function

An unnecessary wait time code is output in the R_RTC_Set_AlarmOn().

```
/* Change the waiting time according to the system */
for (w_count = 0U; w_count < RTC_WAITTIME_2FRTC; w_count++)
{
    NOP();
}
```

[Workaround] There is no workaround.
I Delete the wait time code in the R_RTC_Set_AlarmOn () function after generating the code.

5.2.4 Unit for 'Gain setting' of $\Delta\Sigma$ A/D CONVERTER

The unit of Multiplexer 0/1/2/3(Internal)/3(external) are 'db' but it should be 'Gain'.

The screenshot shows the configuration window for the $\Delta\Sigma$ A/D converter. The 'PGA0 setting' tab is active. Under 'Gain setting', both 'GSET01' and 'GSET02' are set to '1' with a unit of 'db'. The 'Offset adjustment setting' shows a value of '16' and '0 (mV)'. A diagram on the right illustrates the internal circuitry, including two input channels (PGA00P and PGA00N), gain stages (GSET01, GSET02), an offset adjuster, and an ADC. The total gain is labeled as G_{TOTAL}.

[Workaround] Please interpret 'db' as 'Gain' when use GSET01 and/or GSET02.

5.2.5 Restrictions on CSI continuous transfer mode

When CSI is used in continuous transfer mode, 2 bytes are received even if 1 is specified in the function argument.

[Workaround] Change the code in the red frame below. If code generation is executed again after changing the code, the code will be overwritten and deleted, so be caution.

[R_CSIn_Receive() function] case with CS100

Before:

```
MD_STATUS R_CS100_Receive(uint8_t * const rx_buf, uint16_t rx_num)
{
    MD_STATUS status = MD_OK;

    if (rx_num < 1U)
    {
        status = MD_ARGERROR;
    }
    else
    {
        SMRO0 |= _0001_SAU_BUFFER_EMPTY;
        g_cs100_rx_length = rx_num; /* receive data length */
        g_cs100_rx_count = 0U; /* receive data count */
        gp_cs100_rx_address = rx_buf; /* receive buffer pointer */
        SIO00 = 0xFFU; /* start receive by dummy write */
    }

    return (status);
}
```

After:

```
MD_STATUS R_CS100_Receive(uint8_t * const rx_buf, uint16_t rx_num)
{
    MD_STATUS status = MD_OK;

    if (rx_num < 1U)
    {
        status = MD_ARGERROR;
    }
    else
    {
        if (1U == rx_num)
        {
            SMRO0 &= ~_0001_SAU_BUFFER_EMPTY;
        }
        else
        {
            SMRO0 |= _0001_SAU_BUFFER_EMPTY;
        }
        g_cs100_rx_length = rx_num; /* receive data length */
        g_cs100_rx_count = 0U; /* receive data count */
        gp_cs100_rx_address = rx_buf; /* receive buffer pointer */
        SIO00 = 0xFFU; /* start receive by dummy write */
    }

    return (status);
}
```

[R_CSIn_Send_Receive() function] case with CS100

Before:

```

MD_STATUS R_CS100_Send_Receive(uint8_t * const tx_buf, uint16_t tx_num, uint8_t * const rx_buf)
{
    MD_STATUS status = MD_OK;

    if (tx_num < 1U)
    {
        status = MD_ARGERROR;
    }
    else
    {
        g_cs100_send_length = tx_num;    /* send data length */
        g_cs100_tx_count = tx_num;       /* send data count */
        gp_cs100_tx_address = tx_buf;    /* send buffer pointer */
        gp_cs100_rx_address = rx_buf;    /* receive buffer pointer */
        SMRO0 |= _0001_SAU_BUFFER_EMPTY;
        CSIMK00 = 1U;                    /* disable INTCS100 interrupt */

        if (0U != gp_cs100_tx_address)
        {
            S1000 = *gp_cs100_tx_address; /* started by writing data to SDR[7:0] */
            gp_cs100_tx_address++;
        }
        else
        {
            S1000 = 0xFFU;
        }

        g_cs100_tx_count--;
        CSIMK00 = 0U;                    /* enable INTCS100 interrupt */
    }

    return (status);
}

```

After:

```

MD_STATUS R_CS100_Send_Receive(uint8_t * const tx_buf, uint16_t tx_num, uint8_t * const rx_buf)
{
    MD_STATUS status = MD_OK;

    if (tx_num < 1U)
    {
        status = MD_ARGERROR;
    }
    else
    {
        g_cs100_send_length = tx_num;    /* send data length */
        g_cs100_tx_count = tx_num;       /* send data count */
        gp_cs100_tx_address = tx_buf;    /* send buffer pointer */
        gp_cs100_rx_address = rx_buf;    /* receive buffer pointer */
        if ( 1U == tx_num )
        {
            SMRO0 &= ~_0001_SAU_BUFFER_EMPTY;
        }
        else
        {
            SMRO0 |= _0001_SAU_BUFFER_EMPTY;
        }

        CSIMK00 = 1U;                    /* disable INTCS100 interrupt */

        if (0U != gp_cs100_tx_address)
        {
            S1000 = *gp_cs100_tx_address; /* started by writing data to SDR[7:0] */
            gp_cs100_tx_address++;
        }
        else
        {
            S1000 = 0xFFU;
        }

        g_cs100_tx_count--;
        CSIMK00 = 0U;                    /* enable INTCS100 interrupt */
    }

    return (status);
}

```

5.2.6 Incorrect clock mode selection (SELPLL) of R_CGC_Set_ClockMode() function

There is an erroneous in the judgment on writing to the SELPLL bit used when switching between the main system clock (fMAIN) and PLL clock (fPLL).

```
MD_STATUS R_CGC_Set_ClockMode(clock_mode_t mode)
{
    (Omitted)
    if (mode != old_mode)
    {
        switch (mode)
        {
            case HIOCLK:

                (Omitted)
                if (_00_CGC_CLK_MODE_FMAIN != (PLLSTS &_00_CGC_CLK_MODE_FMAIN))
                {
                    SELPLL = 0U;    /* clock through mode (fMAIN) */
                }
            }
        }
    }
}
```

[Workaround] Change the code in the red frame to "&_08_CGC_CLK_MODE_PLL".
If code generation is executed again after changing the code, the code will be overwritten and deleted, so be caution.

5.2.7 Incorrect function description in data lash library

There is an erroneous in the description of the R_FDL_BlankCheck () function and the R_FDL_Iverify () function. The description in Code Generator RL78 API Reference (P740-741) is the correct explanation. Please refer to it.

[Workaround] The code is not affected.


5.2.8 Operation clock when fSUB and fIL are selected in TAU input pulse interval measurement

When input pulse interval measurement is specified with TAU and fSUB and fIL are selected, the division ratio is fixed to $f_{clk}/2^8$. Due to the fixed operation clock, the intended detection accuracy may not be achieved in the safety function frequency detection.

[Workaround] After code generation, change the operating clock (fMCK) of the timer mode register from CK00 to CK01. If code generation is executed again after changing the code, the code will be overwritten and deleted, so be caution.

5.2.9 64-bit environment restrictions

After loading project (e² studio project or AP3 project) which is saved on 32-bit environment in 64-bit environment, TAU0 channel1 input selection (refer to the red box in the figure below) can't be kept.



[Workaround] Custom should confirm this GUI setting after loading project in such a case.

6. Cautions

This section describes points for caution regarding the Code Generator for RL78.

6.1 List for Cautions

Table 6-1. List of Points for Caution 1/2

○: Applicable, /: Not applicable

No	Description	Group													
		RL78/D1A	RL78/G10	RL78/G11	RL78/G12	RL78/G13, G13A	RL78/G14	RL78/G1A	RL78/G1C	RL78/G1D	RL78/G1E	RL78/G1F	RL78/G1G	RL78/G1H	RL78/H1D
1	Online Help (Applilet3, AP4)	○	○	○	○	○	○	○	○	○	○	○	○	○	○
2	Coding rule of MISRA-C.	○	○	○	○	○	○	○	○	○	○	○	○	○	○
3	High-speed on-chip oscillator frequency select register	○	○	○	○	○	○	○	○	○	○	○	○	○	○
4	Internal low-speed or internal high-speed oscillator trimming	○	○	○	○	○	○	○	○	○	○	○	○	○	○
5	Serial array unit	/	/	/	/	/	/	/	/	/	/	/	/	/	/
6	Flash memory CRC operation function (high-speed CRC)	○	○	○	○	○	○	○	○	○	○	○	○	○	○
7	Port mode select register (PMS)	○	○	/	/	○	/	○	○	○	○	○	○	○	○
8	LIN-bus function of UART	○	○	○	○	○	○	○	○	○	○	○	○	○	○
9	Extension code, wakeup function and multimaster of serial interface IICA or IIC0	○	○	○	○	○	○	○	○	○	○	○	○	○	○
10	CAN controllers	/	/	/	/	/	/	/	/	/	/	/	/	/	/
11	Safety Functions	○	○	○	○	○	○	○	○	○	○	○	○	○	○
12	USB	/	/	/	/	/	/	/	/	/	/	/	/	/	/
13	RI78V4 project	/	/	/	/	/	/	/	/	/	/	/	/	/	/
14	DTC function (CS+ for CA,CX)	○	/	/	/	○	/	/	/	/	/	/	/	/	/
15	High Speed DTC chain transfer	/	/	/	/	/	/	/	/	/	/	/	/	/	/
16	Fast Mode Plus setting in IICA slave	○	○	○	○	○	○	○	○	○	○	○	○	○	○
17	high-speed on-chip oscillator (CS+ for CA,CX)	/	/	○	○	○	○	/	/	/	/	/	/	/	/
18	Pin Configurator (CS+ for CA,CX)	/	/	○	○	○	○	/	/	/	/	/	/	/	/
19	Version notation of RL78/G13A generation file.	/	/	/	/	○	/	/	/	/	/	/	/	/	/

Notes: 1. These version numbers are stated in the file headers of the source code which is generated by the code generator.

Table 6-2. List of Points for Caution 1/2

○: Applicable, /: Not applicable

No	Description	Group													
		RL78/F12	RL78/F13	RL78/F14	RL78/F15	RL78/F1E	RL78/1A	RL78/1B	RL78/1C	RL78/1D	RL78/1E	RL78/L12	RL78/L13	RL78/L1A	RL78/L1C
1	Online Help (Applilet3, AP4)	○	○	○	○	○	○	○	○	○	○	○	○	○	○
2	Coding rule of MISRA-C.	○	○	○	○	○	○	○	○	○	○	○	○	○	○
3	High-speed on-chip oscillator frequency select register	○	○	○	○	○	/	○	○	○	○	○	○	○	○
4	Internal low-speed or internal high-speed oscillator trimming	○	○	○	○	○	○	○	○	○	○	○	○	○	○
5	Serial array unit	/	/	/	/	/	○	/	/	/	/	/	/	/	/
6	Flash memory CRC operation function (high-speed CRC)	○	○	○	○	○	○	○	○	○	○	○	○	○	○
7	Port mode select register (PMS)	/	○	○	○	○	○	○	○	○	○	/	○	○	○
8	LIN-bus function of UART	○	○	○	○	○	○	○	○	○	○	○	○	○	○
9	Extension code, wakeup function and multimaster of serial interface IICA or IIC0	○	○	○	○	○	○	○	○	○	○	○	○	○	○
10	CAN controllers	/	○	○	○	○	/	/	/	/	/	/	/	/	/
11	Safety Functions	○	○	○	○	○	○	○	○	○	○	○	○	○	○
12	USB	/	/	/	/	/	/	/	/	/	/	/	/	/	○
13	RI78V4 project	/	/	/	/	/	/	/	/	/	/	/	/	/	/
14	DTC function (CS+ for CA,CX)	/	○	○	○	○	/	/	/	/	/	/	/	○	/
15	High Speed DTC chain transfer	/	○	○	○	/	/	/	/	/	/	/	/	/	/
16	Fast Mode Plus setting in IICA slave	○	○	○	○	○	○	○	○	○	○	○	○	○	○
17	high-speed on-chip oscillator (CS+ for CA,CX)	○	○	○	/	/	○	/	/	/	/	○	/	/	/
18	Pin Configurator (CS+ for CA,CX)	○	○	○	○	/	○	/	/	/	/	○	/	/	/
19	Version notation of RL78/G13A generation file.	/	/	/	/	/	/	/	/	/	/	/	/	/	/

6.2 Details for Cautions

6.2.1 Online Help (Applilet3, AP4)

Applilet3 and AP4 do not support online help.

6.2.2 Coding rule of MISRA-C

Compliance with the MISRA-C (Guidelines for the Use of the C Language in Vehicle Based Software) coding convention is not supported for source code output by the code generator.

6.2.3 High-speed on-chip oscillator frequency select register

Code generator is not equivalent to a setup of high-speed on-chip oscillator frequency select register.

6.2.4 Internal low-speed or internal high-speed oscillator trimming

Code generator is not equivalent to a setup of internal low-speed or internal high-speed oscillator trimming register.

6.2.5 Serial array unit

Code generator is not equivalent to a setup of single-wire UART mode and DMX512 communication.

6.2.6 Flash memory CRC operation function (high-speed CRC)

Code generator does not correspond to a flash memory CRC operation function (high-speed CRC). Please refer to application note r01an0736.

<https://www.renesas.com/search/keyword-search.html#genre=document&q=r01an0736>

6.2.7 Port mode select register (PMS)

Code generator does not correspond to a port mode select register (PMS).

6.2.8 LIN-bus function of UART

The code generator is not supporting the LIN-bus functions of serial interface UART0, UART2, UART3, UART6 or UARTF.

6.2.9 Extension code, multimaster, wakeup function of serial interface IICA or IIC0

The code generator is not supporting the extension code, multimaster, wakeup function of serial interface IIC.

6.2.10 CAN controllers

The code generator is not supporting the CAN Controllers.

6.2.11 Safety Functions

The code generator is not supporting the USB host, USB function.

6.2.12 USB

The code generator is not supporting the USB host, USB function.

6.2.13 RI78V4 project



The Code generator can't be used in a project of RI78V4. But code generator is shown to a project of RI78V4. Even if a code is generated, RI78V4 will be an unsupported purpose build error.

6.2.14 DTC function (CS+ for CA,CX)

When DTC is used, the following warning message is displayed and an object file is not generated.
CC78K0R warning W0837: Output assembler source file , not object file.

[Workaround]

Set up the following individual option of building.



6.2.15 High Speed DTC chain transfer

Although there are chain transfer setting items of High Speed DTC, code corresponding to chain transfer is not supported.

Normal Speed		High Speed	
DTC setting		DTCH0	
High Speed Activation Source			
<input checked="" type="checkbox"/> Control data0 (DTCH0)	<input type="checkbox"/> Chain transfer	Activation sources	INT0
<input type="checkbox"/> Control data1 (DTCH1)		Activation sources	INT1

[Workaround] It cannot be used for chain transfer.

6.2.16 Fast Mode Plus setting in IICA slave

If the Fast Mode Plus is set when using the IICA slave, IICA Low level range setting register (IICWLn, n= channel number), and IICA High level range setting register (IICWHLn) are not set correctly.

[Workaround] There is no workaround.

After doing code generator, please rewrite the numerical value of the register setting of IICWLn, IICWHn in the R_IICAn_Create function. I depend on a system for the numerical value. Please change device UM to reference.

6.2.17 High-speed on-chip oscillator (CS+ for CA,CX)

When a high-speed on-chip oscillator clock is set up by CubeSuite+ RL78, 78K0R, and 78K0 code generator V2.01.00 or earlier, If it is read by CubeSuite+V2.03.00, a clock frequency setup of a high-speed on-chip oscillator may not be right.

[Workaround] Re-set up the frequency right in that case.

6.2.18 Pin Configurator (CS+ for CA,CX)

There is a pin which is not reflected even if it performs reflection to pin configurator from code generator. Even if it sets up using a code generator PIOR function, it is not reflected to pin configurator.

[Workaround] Edit terminal information with pin configurator.

6.2.19 Version notation of RL78/G13A generation file.

The device name output in the version of the file generated by RL78/G13A is output as "RL78/G13" instead of "RL78/G13A".

```

□/*****
* File Name      : r_main.c
* Version       : CodeGenerator for RL78/G13 V2.05.04.02 [20 Nov 2019]
* Device(s)    : R5F140PL
* Tool-Chain   : CCRL
* Description   : This file implements main function.
* Creation Date: 2019/11/27
*****/

```

Revision History

Rev.	Date	Description	
		Page	Summary
1.00	Oct 8, 2019	-	First edition issued
1.01	Jan 20, 2020	6	Updated "2. Supported devices" for Jan 20, 2020 release
		9	Updated "3. Changes" for Jan 20, 2020 release
		23	Update "4. History of Corrections Announced in Renesas Tool New" for Jan 20, 2020 release
		25	Update "5. Restrictions" for Jan 20, 2020 release
		31	Update "6. Cautions" for Jan 20, 2020 release
1.02	Apr 20.2020	3	Updated "1.1 Product version" for Apr.20. 2020 release
		4	Added e ² studio 64-bit environment to "1.2.2 Development Tools"
		10	Updated "3. Changes" for Apr.20. 2020 release
		16	Updated "5. Restrictions" for Apr.20. 2020 release

General Precautions in the Handling of Microprocessing Unit and Microcontroller Unit Products

The following usage notes are applicable to all Microprocessing unit and Microcontroller unit products from Renesas. For detailed usage notes on the products covered by this document, refer to the relevant sections of the document as well as any technical updates that have been issued for the products.

1. Precaution against Electrostatic Discharge (ESD)

A strong electrical field, when exposed to a CMOS device, can cause destruction of the gate oxide and ultimately degrade the device operation. Steps must be taken to stop the generation of static electricity as much as possible, and quickly dissipate it when it occurs. Environmental control must be adequate. When it is dry, a humidifier should be used. This is recommended to avoid using insulators that can easily build up static electricity. Semiconductor devices must be stored and transported in an anti-static container, static shielding bag or conductive material. All test and measurement tools including work benches and floors must be grounded. The operator must also be grounded using a wrist strap. Semiconductor devices must not be touched with bare hands. Similar precautions must be taken for printed circuit boards with mounted semiconductor devices.

2. Processing at power-on

The state of the product is undefined at the time when power is supplied. The states of internal circuits in the LSI are indeterminate and the states of register settings and pins are undefined at the time when power is supplied. In a finished product where the reset signal is applied to the external reset pin, the states of pins are not guaranteed from the time when power is supplied until the reset process is completed. In a similar way, the states of pins in a product that is reset by an on-chip power-on reset function are not guaranteed from the time when power is supplied until the power reaches the level at which resetting is specified.

3. Input of signal during power-off state

Do not input signals or an I/O pull-up power supply while the device is powered off. The current injection that results from input of such a signal or I/O pull-up power supply may cause malfunction and the abnormal current that passes in the device at this time may cause degradation of internal elements. Follow the guideline for input signal during power-off state as described in your product documentation.

4. Handling of unused pins

Handle unused pins in accordance with the directions given under handling of unused pins in the manual. The input pins of CMOS products are generally in the high-impedance state. In operation with an unused pin in the open-circuit state, extra electromagnetic noise is induced in the vicinity of the LSI, an associated shoot-through current flows internally, and malfunctions occur due to the false recognition of the pin state as an input signal become possible.

5. Clock signals

After applying a reset, only release the reset line after the operating clock signal becomes stable. When switching the clock signal during program execution, wait until the target clock signal is stabilized. When the clock signal is generated with an external resonator or from an external oscillator during a reset, ensure that the reset line is only released after full stabilization of the clock signal. Additionally, when switching to a clock signal produced with an external resonator or by an external oscillator while program execution is in progress, wait until the target clock signal is stable.

6. Voltage application waveform at input pin

Waveform distortion due to input noise or a reflected wave may cause malfunction. If the input of the CMOS device stays in the area between V_{IL} (Max.) and V_{IH} (Min.) due to noise, for example, the device may malfunction. Take care to prevent chattering noise from entering the device when the input level is fixed, and also in the transition period when the input level passes through the area between V_{IL} (Max.) and V_{IH} (Min.).

7. Prohibition of access to reserved addresses

Access to reserved addresses is prohibited. The reserved addresses are provided for possible future expansion of functions. Do not access these addresses as the correct operation of the LSI is not guaranteed.

8. Differences between products

Before changing from one product to another, for example to a product with a different part number, confirm that the change will not lead to problems. The characteristics of a microprocessing unit or microcontroller unit products in the same group but having a different part number might differ in terms of internal memory capacity, layout pattern, and other factors, which can affect the ranges of electrical characteristics, such as characteristic values, operating margins, immunity to noise, and amount of radiated noise. When changing to a product with a different part number, implement a system-evaluation test for the given product.

Notice

1. Descriptions of circuits, software and other related information in this document are provided only to illustrate the operation of semiconductor products and application examples. You are fully responsible for the incorporation or any other use of the circuits, software, and information in the design of your product or system. Renesas Electronics disclaims any and all liability for any losses and damages incurred by you or third parties arising from the use of these circuits, software, or information.
2. Renesas Electronics hereby expressly disclaims any warranties against and liability for infringement or any other claims involving patents, copyrights, or other intellectual property rights of third parties, by or arising from the use of Renesas Electronics products or technical information described in this document, including but not limited to, the product data, drawings, charts, programs, algorithms, and application examples.
3. No license, express, implied or otherwise, is granted hereby under any patents, copyrights or other intellectual property rights of Renesas Electronics or others.
4. You shall not alter, modify, copy, or reverse engineer any Renesas Electronics product, whether in whole or in part. Renesas Electronics disclaims any and all liability for any losses or damages incurred by you or third parties arising from such alteration, modification, copying or reverse engineering.
5. Renesas Electronics products are classified according to the following two quality grades: "Standard" and "High Quality". The intended applications for each Renesas Electronics product depends on the product's quality grade, as indicated below.
"Standard": Computers; office equipment; communications equipment; test and measurement equipment; audio and visual equipment; home electronic appliances; machine tools; personal electronic equipment; industrial robots; etc.
"High Quality": Transportation equipment (automobiles, trains, ships, etc.); traffic control (traffic lights); large-scale communication equipment; key financial terminal systems; safety control equipment; etc.
Unless expressly designated as a high reliability product or a product for harsh environments in a Renesas Electronics data sheet or other Renesas Electronics document, Renesas Electronics products are not intended or authorized for use in products or systems that may pose a direct threat to human life or bodily injury (artificial life support devices or systems; surgical implantations; etc.), or may cause serious property damage (space system; undersea repeaters; nuclear power control systems; aircraft control systems; key plant systems; military equipment; etc.). Renesas Electronics disclaims any and all liability for any damages or losses incurred by you or any third parties arising from the use of any Renesas Electronics product that is inconsistent with any Renesas Electronics data sheet, user's manual or other Renesas Electronics document.
6. When using Renesas Electronics products, refer to the latest product information (data sheets, user's manuals, application notes, "General Notes for Handling and Using Semiconductor Devices" in the reliability handbook, etc.), and ensure that usage conditions are within the ranges specified by Renesas Electronics with respect to maximum ratings, operating power supply voltage range, heat dissipation characteristics, installation, etc. Renesas Electronics disclaims any and all liability for any malfunctions, failure or accident arising out of the use of Renesas Electronics products outside of such specified ranges.
7. Although Renesas Electronics endeavors to improve the quality and reliability of Renesas Electronics products, semiconductor products have specific characteristics, such as the occurrence of failure at a certain rate and malfunctions under certain use conditions. Unless designated as a high reliability product or a product for harsh environments in a Renesas Electronics data sheet or other Renesas Electronics document, Renesas Electronics products are not subject to radiation resistance design. You are responsible for implementing safety measures to guard against the possibility of bodily injury, injury or damage caused by fire, and/or danger to the public in the event of a failure or malfunction of Renesas Electronics products, such as safety design for hardware and software, including but not limited to redundancy, fire control and malfunction prevention, appropriate treatment for aging degradation or any other appropriate measures. Because the evaluation of microcomputer software alone is very difficult and impractical, you are responsible for evaluating the safety of the final products or systems manufactured by you.
8. Please contact a Renesas Electronics sales office for details as to environmental matters such as the environmental compatibility of each Renesas Electronics product. You are responsible for carefully and sufficiently investigating applicable laws and regulations that regulate the inclusion or use of controlled substances, including without limitation, the EU RoHS Directive, and using Renesas Electronics products in compliance with all these applicable laws and regulations. Renesas Electronics disclaims any and all liability for damages or losses occurring as a result of your noncompliance with applicable laws and regulations.
9. Renesas Electronics products and technologies shall not be used for or incorporated into any products or systems whose manufacture, use, or sale is prohibited under any applicable domestic or foreign laws or regulations. You shall comply with any applicable export control laws and regulations promulgated and administered by the governments of any countries asserting jurisdiction over the parties or transactions.
10. It is the responsibility of the buyer or distributor of Renesas Electronics products, or any other party who distributes, disposes of, or otherwise sells or transfers the product to a third party, to notify such third party in advance of the contents and conditions set forth in this document.
11. This document shall not be reprinted, reproduced or duplicated in any form, in whole or in part, without prior written consent of Renesas Electronics.
12. Please contact a Renesas Electronics sales office if you have any questions regarding the information contained in this document or Renesas Electronics products.

(Note1) "Renesas Electronics" as used in this document means Renesas Electronics Corporation and also includes its directly or indirectly controlled subsidiaries.

(Note2) "Renesas Electronics product(s)" means any product developed or manufactured by or for Renesas Electronics.

(Rev.4.0-1 November 2017)

Corporate Headquarters

TOYOSU FORESIA, 3-2-24 Toyosu,
Koto-ku, Tokyo 135-0061, Japan
www.renesas.com

Contact information

For further information on a product, technology, the most up-to-date version of a document, or your nearest sales office, please visit:
www.renesas.com/contact/.

Trademarks

Renesas and the Renesas logo are trademarks of Renesas Electronics Corporation. All trademarks and registered trademarks are the property of their respective owners.