

# **Product Change Notice (PCN)**

Subject: Product Improvement – Design Change for the Listed Renesas ISL854102\*, ISL85410\* and ISL85418\* Products Publication Date: 3/20/2019 Effective Date: 6/20/2019

#### **Revision Description:**

Initial Release

### **Description of Change:**

This notice is to advise our customers of a design revision for the Renesas Electronics America products listed below. The update improves the transition between PWM and PFM operating modes.

#### Products impacted by the change are:

ISL854102FRZ	ISL85410FRZ-T	ISL85410FRZ-TKR5632	ISL85418FRZ-T7A
ISL854102FRZ-T	ISL85410FRZ-T7A	ISL85410FRZ-TR5835	
ISL854102FRZ-T7A	ISL85410FRZ-T7AR5194	ISL85418FRZ	
ISL85410FRZ	ISL85410FRZ-TKR5194	ISL85418FRZ-T	

#### Reason for Change:

Under some conditions, the ISL8541\* may not transition from PWM to PFM mode. This update adds additional hysteresis to the PWM-PFM comparator to ensure a smooth and consistent transition between these two operating modes.

#### Impact on fit, form, function, quality & reliability:

The change will have no other impact on the form, fit, function, quality, reliability and environmental compliance of the devices.

#### **Product Identification:**

There will be no change in the external marking of the packaged parts. Product affected by this change is identifiable via Renesas Electronics America Inc. internal traceability system.

Qualification status: Complete, see attached Sample availability: 3/20/2019 Device material declaration: Available upon request

Questions or requests pertaining to this change notice, including additional data or samples, must be sent to Intersil within 30 days of the publication date.

For additional information regarding this notice, please contact your regional change coordinator (below)						
Americas: PCN-US@Renesas.COM	Europe: PCN-EU@Renesas.COM	Japan: PCN-JP@Renesas.COM	Asia Pac: PCN-APAC@Renesas.COM			



## Appendix A - Qualification Results

Qualification Results							
Stress	Test Method	Product	Sample Size	# of Lots	Result		
High Temperature Operating Life (HTOL) 125°C, 1000 hours	JESD22-A108	ISL85410FRZ-T	80	1	Pass		
Electrical Characterization <sup>1</sup>	-	ISL85410FRZ-T	-	-	Pass		
Human Body Model (HBM)	JS-001	ISL85410FRZ-T	3	1	2,500v		
Charged Device Model (CDM)	JS-002	ISL85410FRZ-T	3	1	1,000v		
Latch-up (LU)	JESD78	ISL85410FRZ-T	6	1	Pass		

1. Electrical characterization over temperature was completed in accordance with REA internal procedures. Bench validation was also performed to verify the product meets published specifications.