

# **Product Advisory (PA)**

Subject: Datasheet errata update for the listed HXT\* parts

Publication Date: 7/21/2021 Effective Date: 7/21/2021

## **Revision Description:**

Initial Release

### **Description of Change:**

This notice is to inform you that the datasheets for the listed HXT\* parts have been updated to capture the following errata:

- "GDPD, DPDx, uLDIS and LDIS must be always set to zero."
- "BAx must be always set to ≥ 3."
- "LDIS is not functional in Analog modes" for HXT8204-DNG and HXT8212-DNG.

#### **Affected Product List:**

HXT8201-DNT	HXT8204-DNG
HXT8204-DNT	HXT8212-DNG
HXT8 <sub>212</sub> -DNT	

#### **Reason for Change:**

Setting GDPD, DPDx, uLDIS or LDIS to "1" to power down the driver and laser, or setting BAx < "3" can result in laser bias drop over time.

#### Impact on Fit, Form, Function, Quality & Reliability:

No impact on Fit and Form. DPD and GDPD functions are removed by not setting to 1. No impact to Quality and Reliability.

Product Identification: Not Applicable Qualification Status: Not Applicable Sample Availability Date: 7/21/2021

**Device Material Declaration:** Available upon request

Questions or requests pertaining to this change notice, including additional data or samples, must be sent to Renesas within 30 days of the publication date.

For additional information regarding this notice, please contact idt-pcn@lm.renesas.com