

To all our customers

Regarding the change of names mentioned in the document, such as Mitsubishi Electric and Mitsubishi XX, to Renesas Technology Corp.

The semiconductor operations of Hitachi and Mitsubishi Electric were transferred to Renesas Technology Corporation on April 1st 2003. These operations include microcomputer, logic, analog and discrete devices, and memory chips other than DRAMs (flash memory, SRAMs etc.) Accordingly, although Mitsubishi Electric, Mitsubishi Electric Corporation, Mitsubishi Semiconductors, and other Mitsubishi brand names are mentioned in the document, these names have in fact all been changed to Renesas Technology Corp. Thank you for your understanding. Except for our corporate trademark, logo and corporate statement, no changes whatsoever have been made to the contents of the document, and these changes do not constitute any alteration to the contents of the document itself.

Note : Mitsubishi Electric will continue the business operations of high frequency & optical devices and power devices.

Renesas Technology Corp.
Customer Support Dept.
April 1, 2003

M16C Family

Concept of the Power Control

1.0 Abstract

This application notes explains about low-power operations using Wait Mode and Stop Mode.

2.0 Introduction

The explanation of this issue is applied to the following condition:

Applicable MCU: M16C Family

3.0 Contents

3.1 Outline

In portable systems such as mobile phones or PDAs, the key issues are reducing power consumption and extending the life of the battery. The M16C Family offers a unique chip architecture and superior internal layout/wiring, resulting in greatly reduced MCU power consumption. Effective use of the internal peripheral functions and MCU modes is the key to fully benefiting from these advanced power-saving features.

We provided the following application examples for all users to fully understand the advanced low-power consumption operations of the M16C Family and how to apply these features in their systems.

3.2 Power Saving Using Operation Modes

MCU consumption current decreases in the following order:

Normal Operation Mode > Wait Mode > Stop Mode

1. Normal Operation Mode

The MCU operates with a system clock BCLK, generated by either the main clock or sub-clock. The internal peripherals operate with individually configured clocks.

2. Wait Mode

The CPU stops its operation in this mode but oscillators are not affected.

This mode is initiated by the WAIT instruction and the MCU returns to the normal operation mode upon receipt of an interrupt request or hardware reset.

3. Stop Mode

All oscillators stop in this mode. As a result, not only the CPU but also all internal peripherals stop operating.

This stop mode is initiated by setting the all clock stop control bit to "1". The MCU returns to the normal operation mode upon receiving an interrupt request or a hardware reset.

3.3 Power Saving By Peripheral Functions

Programmable I/O Port

When the MCU is initiated in the wait or stop mode, the programmable I/O ports will hold their prior states. If the output port is set for an active state, a current will flow through the port. If the input port is applied with the intermediate voltage or is left the floating state, a penetration current may flow to the port.

To prevent the current flow:

For an output port, output a level that current does not flow, creating an in-active condition. For an input port, pull-up the pin externally to fix the level. For more details, refer to [Chapter 3.5 CMOS Logic Circuit for constructing Programmable I/O Port](#).

External Address Bus/External Data Bus

Ports P0 to P5 become the address bus, data bus, and control signal I/O pins in the memory expansion and microprocessor modes. The bus holds its state from the last access just before the MCU is switched to the wait or stop mode. This means that, depending on state of the bus, current may flow to the pins.

To prevent the current flow, after setting the MCU to the single-chip mode, which sets the pins used as the bus to programmable I/O ports, set the ports to the state that current does not flow. For more details, refer to [Chapter 3.6 Power Saving in Memory Expansion and Microprocessor Modes](#).

A-D Converter

Current flows to the VREF pin constantly. To prevent the current flow, set the Vref connection bit to "0".

D-A Converter

The D-A converter also holds its prior state when the MCU moves to the wait/stop mode. Disable the D-A output (D-A output enable bit = "0"), which sets the D-A output pin to a programmable I/O port. In addition, the value set to the D-A register must be one that current does not flow.

Other Internal Peripherals

You can also reduce power consumption by setting output pins of other internal peripherals to an in-active condition. If the level of an output pin of an internal peripheral cannot be controlled, disable the peripheral, which sets the pin to a programmable I/O port. Then output a level that current does not flow, creating an in-active condition.

The level of the input pins of the internal peripherals must be fixed externally.

External Clock

When using an external clock as the main clock, set the main clock stop bit to "1". This will stop operation of the XOUT pin and therefore reduce the consumption current. (When using an external clock, note that the clock is always input regardless of the state of the main clock stop bit.)

3.4 Confirming Your Power Savings

To maintain an effective power saving condition in the wait/stop mode, please check the following items and hold the respective pins stable.

Pins in use..

Input ports:

Confirm that the input port is inputting a stable output from the peripheral device (IC, etc.). If the power from the peripheral device is shut down and the input voltage of the port becomes unstable, that causes a penetration current to flow through the port.

Output ports:

Make sure the output port is outputting an identical level with the peripheral device and is not outputting "H" while the power from the peripheral device is shut down. If the port outputs a different level from the device or outputs "H" to the device that is turned off, that causes a current to flow through the port.

Unused pins..

Connect unused pin to Vss through a resistor and set the pin to input, or leave the pin open and set the pin to output an "L" level.

How to confirm pin states (recommended methods)

(1) Is the input port inputting a fixed voltage level? Is the output port outputting a fixed voltage level?

Check each port using a measurement device.

(2) Is the port or peripheral device outputting a proper "L" level?

Pull up the pin and measure the pin level. If you can measure "L" level in this condition, the pin is outputting a proper "L" level.

(3) Is the port or peripheral device outputting a proper "H" level?

Pull down the pin and measure the pin level. If you can measure "H" level in this condition, the pin is outputting a proper "H" level.

3.5 CMOS Logic Circuit for constructing Programmable I/O Port

The programmable I/O port of the M16C Family adopts a CMOS logic architecture consisting of two switch elements, PMOS and NMOS elements (see Fig. 3.5.1).

Normally, when either the PMOS or NMOS switch is ON, the other element (i.e. NMOS or PMOS, respectively) is OFF, which prevents the flow of a penetration current. However, when the intermediate voltage level is input to the port, it causes both the PMOS and NMOS switches to be set to ON (see Fig. 3.5.2).

In this situation, a current flows through the PMOS and NMOS elements, which we call the penetration current.




Figure3.5.1 CMOS Logic




Figure3.5.2 PMOS-NMOS Operations

3.6 Power Saving in the Memory Expansion and Microprocessor Modes

The bus holds its state from the last access even after the MCU is switched to the wait or stop mode, making it difficult to set a certain voltage level to the pins when you set the MCU to the wait or stop mode.

On the other hand, once the processor mode is switched to the single-chip mode, the pins used as the bus will become programmable I/O ports, enabling you to easily set any voltage level to the pins by software.

Procedure

1. Set the processor mode of the MCU to the single-chip mode.
2. Set each programmable I/O port, previously used as the bus, to hold a fixed voltage level, with software.
3. Set the MCU to the wait or stop mode.

Note 1: In the memory expansion mode, place the above-mentioned program in the internal ROM. In the microprocessor mode, transfer the program to an internal RAM area and execute it there.

Note 2: Perform Step 2 for the programmable I/O ports only after switching to the single-chip mode.

Setup Example: M16C/60 Series

The following is an example program for setting the MCU to the wait or stop mode in the memory expansion mode.

```

/*----- PROCESSER MODE SET -----*/
PRCR.bit.PRC1 = TRUE;          /* Enable writing to processor mode registers 0 and 1 */
PM0.all = 0;                  /* Memory expansion mode --> Single-chip mode */
PRCR.bit.PRC1 = FALSE;       /* Disable writing to processor mode registers 0 and 1 */
*/

/*----- PORT DATA SET -----*/
P0.all = DT_STOP_P0;         /* Port data control in low power consumption mode */
P1.all = DT_STOP_P1;         /* Port data control in low power consumption mode */
P2.all = DT_STOP_P2;         /* Port data control in low power consumption mode */
P3.all = DT_STOP_P3;         /* Port data control in low power consumption mode */
P4.all = DT_STOP_P4;         /* Port data control in low power consumption mode */
P5.all = DT_STOP_P5;         /* Port data control in low power consumption mode */
P6.all = DT_STOP_P6;         /* Port data control in low power consumption mode */
P7.all = DT_STOP_P7;         /* Port data control in low power consumption mode */
P8.all = DT_STOP_P8;         /* Port data control in low power consumption mode */
P9.all = DT_STOP_P9;         /* Port data control in low power consumption mode */
P10.all = DT_STOP_P10;       /* Port data control in low power consumption mode */

/*----- PORT DIRCTION SET -----*/
PD0.all = DIR_STOP_P0; /* Port direction control in low power consumption mode */
PD1.all = DIR_STOP_P1; /* Port direction control in low power consumption mode */
PD2.all = DIR_STOP_P2; /* Port direction control in low power consumption mode */
PD3.all = DIR_STOP_P3; /* Port direction control in low power consumption mode */
PD4.all = DIR_STOP_P4; /* Port direction control in low power consumption mode */
PD5.all = DIR_STOP_P5; /* Port direction control in low power consumption mode */
PD6.all = DIR_STOP_P6; /* Port direction control in low power consumption mode */
PD7.all = DIR_STOP_P7; /* Port direction control in low power consumption mode */
PD8.all = DIR_STOP_P8; /* Port direction control in low power consumption mode */
PRCR.bit.PRC2 = TRUE; /* Enable writing to port P9 direction register */
PD9.all = DIR_STOP_P9; /* Port direction control in low power consumption mode */
PD10.all = DIR_STOP_P10; /* Port direction control in low power consumption mode */

/*----- DA SET -----*/
DACON.bit.DA0E = FALSE; /* Disable D-A output */
DACON.bit.DA1E = FALSE; /* Disable D-A output */
DA0 = 0; /* DA0 0 [V] */
DA1 = 0; /* DA0 0 [V] */

```

Keep safety first in your circuit designs!

- Mitsubishi Electric Corporation puts the maximum effort into making semiconductor products better and more reliable, but there is always the possibility that trouble may occur with them. Trouble with semiconductors may lead to personal injury, fire or property damage. Remember to give due consideration to safety when making your circuit designs, with appropriate measures such as (i) placement of substitutive, auxiliary circuits, (ii) use of non-flammable material or (iii) prevention against any malfunction or mishap.

Notes regarding these materials

- These materials are intended as a reference to assist our customers in the selection of the Mitsubishi semiconductor product best suited to the customer's application; they do not convey any license under any intellectual property rights, or any other rights, belonging to Mitsubishi Electric Corporation or a third party.
- Mitsubishi Electric Corporation assumes no responsibility for any damage, or infringement of any third-party's rights, originating in the use of any product data, diagrams, charts, programs, algorithms, or circuit application examples contained in these materials.
- All information contained in these materials, including product data, diagrams, charts, programs and algorithms represents information on products at the time of publication of these materials, and are subject to change by Mitsubishi Electric Corporation without notice due to product improvements or other reasons. It is therefore recommended that customers contact Mitsubishi Electric Corporation or an authorized Mitsubishi Semiconductor product distributor for the latest product information before purchasing a product listed herein.

The information described here may contain technical inaccuracies or typographical errors. Mitsubishi Electric Corporation assumes no responsibility for any damage, liability, or other loss rising from these inaccuracies or errors.

Please also pay attention to information published by Mitsubishi Electric Corporation by various means, including the Mitsubishi Semiconductor home page (<http://www.mitsubishichips.com>).

- When using any or all of the information contained in these materials, including product data, diagrams, charts, programs, and algorithms, please be sure to evaluate all information as a total system before making a final decision on the applicability of the information and products. Mitsubishi Electric Corporation assumes no responsibility for any damage, liability or other loss resulting from the information contained herein.
- Mitsubishi Electric Corporation semiconductors are not designed or manufactured for use in a device or system that is used under circumstances in which human life is potentially at stake. Please contact Mitsubishi Electric Corporation or an authorized Mitsubishi Semiconductor product distributor when considering the use of a product contained herein for any specific purposes, such as apparatus or systems for transportation, vehicular, medical, aerospace, nuclear, or undersea repeater use.
- The prior written approval of Mitsubishi Electric Corporation is necessary to reprint or reproduce in whole or in part these materials.
- If these products or technologies are subject to the Japanese export control restrictions, they must be exported under a license from the Japanese government and cannot be imported into a country other than the approved destination.
Any diversion or reexport contrary to the export control laws and regulations of Japan and/or the country of destination is prohibited.
- Please contact Mitsubishi Electric Corporation or an authorized Mitsubishi Semiconductor product distributor for further details on these materials or the products contained therein.