

FEATURES:

- Phase-Lock Loop Clock Distribution
- 10MHz to 200MHz operating frequency
- Distributes one clock input to one bank of five and one bank of four outputs
- Separate output enable for each output bank
- Output Skew < 250ps
- Low jitter <200 ps cycle-to-cycle
- IDT23S09E-1 for Standard Drive
- IDT23S09E-1H for High Drive
- No external RC network required
- Operates at 3.3V VDD
- Spread spectrum compatible
- Available in SOIC and TSSOP packages


DESCRIPTION:

The IDT23S09E is a high-speed phase-lock loop (PLL) clock buffer, designed to address high-speed clock distribution applications. The zero delay is achieved by aligning the phase between the incoming clock and the output clock, operable within the range of 10 to 200MHz.

The IDT23S09E is a 16-pin version of the IDT23S05E. The IDT23S09E accepts one reference input, and drives two banks of four low skew clocks. The -1H version of this device operates up to 200MHz frequency and has higher drive than the -1 device. All parts have on-chip PLLs which lock to an input clock on the REF pin. The PLL feedback is on-chip and is obtained from the CLKOUT pad. In the absence of an input clock, the IDT23S09E enters power down. In this mode, the device will draw less than 12 μ A for Commercial Temperature range and less than 25 μ A for Industrial temperature range, and the outputs are tri-stated.

The IDT23S09E is characterized for both Industrial and Commercial operation.

FUNCTIONAL BLOCK DIAGRAM




The IDT logo is a registered trademark of Integrated Device Technology, Inc.

COMMERCIAL AND INDUSTRIAL TEMPERATURE RANGES

MAY 2010

PIN CONFIGURATION



ABSOLUTE MAXIMUM RATINGS⁽¹⁾

Symbol	Rating	Max.	Unit
V _{DD}	Supply Voltage Range	-0.5 to +4.6	V
V _I ⁽²⁾	Input Voltage Range (REF)	-0.5 to +5.5	V
V _I	Input Voltage Range (except REF)	-0.5 to V _{DD} +0.5	V
I _{IK} (V _I < 0)	Input Clamp Current	-50	mA
I _O (V _O = 0 to V _{DD})	Continuous Output Current	±50	mA
V _{DD} or GND	Continuous Current	±100	mA
T _A = 55°C (in still air) ⁽³⁾	Maximum Power Dissipation	0.7	W
T _{STG}	Storage Temperature Range	-65 to +150	°C
Operating Temperature	Commercial Temperature Range	0 to +70	°C
Operating Temperature	Industrial Temperature Range	-40 to +85	°C

NOTES:

1. Stresses greater than those listed under ABSOLUTE MAXIMUM RATINGS may cause permanent damage to the device. This is a stress rating only and functional operation of the device at these or any other conditions above those indicated in the operational sections of this specification is not implied. Exposure to absolute maximum rating conditions for extended periods may affect reliability.
2. The input and output negative-voltage ratings may be exceeded if the input and output clamp-current ratings are observed.
3. The maximum package power dissipation is calculated using a junction temperature of 150°C and a board trace length of 750 mils.

APPLICATIONS:

- SDRAM
- Telecom
- Datacom
- PC Motherboards/Workstations
- Critical Path Delay Designs

PIN DESCRIPTION

Pin Name	Pin Number	Type	Functional Description
REF ⁽¹⁾	1	IN	Input reference clock, 5 Volt tolerant input
CLKA1 ⁽²⁾	2	Out	Output clock for bank A
CLKA2 ⁽²⁾	3	Out	Output clock for bank A
V _{DD}	4, 13	PWR	3.3V Supply
GND	5, 12	GND	Ground
CLKB1 ⁽²⁾	6	Out	Output clock for bank B
CLKB2 ⁽²⁾	7	Out	Output clock for bank B
S2 ⁽³⁾	8	IN	Select input Bit 2
S1 ⁽³⁾	9	IN	Select input Bit 1
CLKB3 ⁽²⁾	10	Out	Output clock for bank B
CLKB4 ⁽²⁾	11	Out	Output clock for bank B
CLKA3 ⁽²⁾	14	Out	Output clock for bank A
CLKA4 ⁽²⁾	15	Out	Output clock for bank A
CLKOUT ⁽²⁾	16	Out	Output clock, internal feedback on this pin

NOTES:

1. Weak pull down.
2. Weak pull down on all outputs.
3. Weak pull ups on these inputs.

FUNCTION TABLE⁽¹⁾

S2	S1	CLKA	CLKB	CLKOUT ⁽²⁾	Output Source	PLL Shut Down
L	L	Tri-State	Tri-State	Driven	PLL	N
L	H	Driven	Tri-State	Driven	PLL	N
H	L	Driven	Driven	Driven	REF	Y
H	H	Driven	Driven	Driven	PLL	N

NOTES:

1. H = HIGH Voltage Level.
- L = LOW Voltage Level
2. This output is driven and has an internal feedback for the PLL. The load on this output can be adjusted to change the skew between the REF and the output.

DC ELECTRICAL CHARACTERISTICS - COMMERCIAL

Symbol	Parameter	Conditions		Min.	Max.	Unit
V _{IL}	Input LOW Voltage Level			—	0.8	V
V _{IH}	Input HIGH Voltage Level			2	—	V
I _{IL}	Input LOW Current	V _{IN} = 0V		—	50	μA
I _{IH}	Input HIGH Current	V _{IN} = V _{DD}		—	100	μA
V _{OL}	Output LOW Voltage	Standard Drive	I _{OL} = 8mA	—	0.4	V
		High Drive	I _{OL} = 12mA (-1H)			
V _{OH}	Output HIGH Voltage	Standard Drive	I _{OH} = -8mA	2.4	—	V
		High Drive	I _{OH} = -12mA (-1H)			
I _{DD_PD}	Power Down Current	REF = 0MHz (S2 = S1 = H)		—	12	μA
I _{DD}	Supply Current	Unloaded Outputs at 66.66MHz, SEL inputs at V _{DD} or GND		—	32	mA

OPERATING CONDITIONS - COMMERCIAL

Symbol	Parameter	Min.	Max.	Unit
V _{DD}	Supply Voltage	3	3.6	V
T _A	Operating Temperature (Ambient Temperature)	0	70	°C
C _L	Load Capacitance < 100MHz	—	30	pF
	Load Capacitance 100MHz - 200MHz	—	10	
C _{IN}	Input Capacitance	—	7	pF

SWITCHING CHARACTERISTICS (23S09E-1) - COMMERCIAL^(1,2)

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
t ₁	Output Frequency	10pF Load	10	—	200	MHz
		30pF Load	10	—	100	
	Duty Cycle = t ₂ ÷ t ₁	Measured at 1.4V, F _{OUT} = 66.66MHz	40	50	60	%
t ₃	Rise Time	Measured between 0.8V and 2V	—	—	2.5	ns
t ₄	Fall Time	Measured between 0.8V and 2V	—	—	2.5	ns
t ₅	Output to Output Skew	All outputs equally loaded	—	—	250	ps
t _{6A}	Delay, REF Rising Edge to CLKOUT Rising Edge ⁽²⁾	Measured at V _{DD} /2	—	0	±350	ps
t _{6B}	Delay, REF Rising Edge to CLKOUT Rising Edge ⁽²⁾	Measured at V _{DD} /2 in PLL bypass mode (IDT23S09E only)	1	5	8.7	ns
t ₇	Device-to-Device Skew	Measured at V _{DD} /2 on the CLKOUT pins of devices	—	0	700	ps
t ₈	Cycle-to-Cycle Jitter	Measured at 66.66MHz, loaded outputs	—	—	200	ps
t _{LOCK}	PLL Lock Time	Stable power supply, valid clock presented on REF pin	—	—	1	ms

NOTES:

1. REF Input has a threshold voltage of V_{DD}/2.
2. All parameters specified with loaded outputs.

SWITCHING CHARACTERISTICS (23S09E-1H) - COMMERCIAL^(1,2)

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit	
t_1	Output Frequency	10pF Load	10	—	200	MHz	
		30pF Load	10	—	100		
Duty Cycle = $t_2 \div t_1$		Measured at 1.4V, $F_{OUT} = 66.66\text{MHz}$	40	50	60	%	
Duty Cycle = $t_2 \div t_1$		Measured at 1.4V, $F_{OUT} < 50\text{MHz}$	45	50	55	%	
t_3	Rise Time	Measured between 0.8V and 2V	—	—	1.5	ns	
t_4	Fall Time	Measured between 0.8V and 2V	—	—	1.5	ns	
t_5	Output to Output Skew	All outputs equally loaded	—	—	250	ps	
t_{6A}	Delay, REF Rising Edge to CLKOUT Rising Edge	Measured at $V_{DD}/2$	—	0	± 350	ps	
t_{6B}	Delay, REF Rising Edge to CLKOUT Rising Edge	Measured at $V_{DD}/2$ in PLL bypass mode (IDT23S09E only)	1	5	8.7	ns	
t_7	Device-to-Device Skew	Measured at $V_{DD}/2$ on the CLKOUT pins of devices	—	0	700	ps	
t_8	Output Slew Rate	Measured between 0.8V and 2V using Test Circuit 2	1	—	—	V/ns	
t_9	Cycle-to-Cycle Jitter	Measured at 66.66MHz, loaded outputs	—	—	200	ps	
t_{LOCK}	PLL Lock Time	Stable power supply, valid clock presented on REF pin	—	—	1	ms	

NOTES:

1. REF Input has a threshold voltage of $V_{DD}/2$.
2. All parameters specified with loaded outputs.

DC ELECTRICAL CHARACTERISTICS - INDUSTRIAL

Symbol	Parameter	Conditions		Min.	Max.	Unit
V_{IL}	Input LOW Voltage Level			—	0.8	V
V_{IH}	Input HIGH Voltage Level			2	—	V
I_{IL}	Input LOW Current	$V_{IN} = 0V$		—	50	μA
I_{IH}	Input HIGH Current	$V_{IN} = V_{DD}$		—	100	μA
V_{OL}	Output LOW Voltage	Standard Drive	$I_{OL} = 8\text{mA}$	—	0.4	V
		High Drive	$I_{OL} = 12\text{mA} (-1\text{H})$			
V_{OH}	Output HIGH Voltage	Standard Drive	$I_{OH} = -8\text{mA}$	2.4	—	V
		High Drive	$I_{OH} = -12\text{mA} (-1\text{H})$			
I_{DD_PD}	Power Down Current	$REF = 0\text{MHz}$ ($S_2 = S_1 = H$)		—	25	μA
I_{DD}	Supply Current	Unloaded Outputs at 66.66MHz, SEL inputs at V_{DD} or GND		—	35	mA

OPERATING CONDITIONS - INDUSTRIAL

Symbol	Parameter	Min.	Max.	Unit
V_{DD}	Supply Voltage	3	3.6	V
T_A	Operating Temperature (Ambient Temperature)	-40	+85	$^{\circ}\text{C}$
C_L	Load Capacitance < 100MHz	—	30	pF
	Load Capacitance 100MHz - 200MHz	—	10	
C_{IN}	Input Capacitance	—	7	pF

SWITCHING CHARACTERISTICS (23S09E-1) - INDUSTRIAL^(1,2)

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
t_1	Output Frequency	10pF Load	10	—	200	MHz
		30pF Load	10	—	100	
Duty Cycle = $t_2 \div t_1$		Measured at 1.4V, $F_{OUT} = 66.66\text{MHz}$	40	50	60	%
t_3	Rise Time	Measured between 0.8V and 2V	—	—	2.5	ns
t_4	Fall Time	Measured between 0.8V and 2V	—	—	2.5	ns
t_5	Output to Output Skew	All outputs equally loaded	—	—	250	ps
t_{6A}	Delay, REF Rising Edge to CLKOUT Rising Edge	Measured at $V_{DD}/2$	—	0	± 350	ps
t_{6B}	Delay, REF Rising Edge to CLKOUT Rising Edge	Measured at $V_{DD}/2$ in PLL bypass mode (IDT23S09E only)	1	5	8.7	ns
t_7	Device-to-Device Skew	Measured at $V_{DD}/2$ on the CLKOUT pins of devices	—	0	700	ps
t_8	Cycle-to-Cycle Jitter	Measured at 66.66MHz, loaded outputs	—	—	200	ps
t_{LOCK}	PLL Lock Time	Stable power supply, valid clock presented on REF pin	—	—	1	ms

NOTES:

1. REF Input has a threshold voltage of $V_{DD}/2$.
2. All parameters specified with loaded outputs.

SWITCHING CHARACTERISTICS (23S09E-1H) - INDUSTRIAL^(1,2)

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit	
t_1	Output Frequency	10pF Load	10	—	200	MHz	
		30pF Load	10	—	100		
Duty Cycle = $t_2 \div t_1$		Measured at 1.4V, $F_{OUT} = 66.66\text{MHz}$	40	50	60	%	
Duty Cycle = $t_2 \div t_1$		Measured at 1.4V, $F_{OUT} < 50\text{MHz}$	45	50	55	%	
t_3	Rise Time	Measured between 0.8V and 2V	—	—	1.5	ns	
t_4	Fall Time	Measured between 0.8V and 2V	—	—	1.5	ns	
t_5	Output to Output Skew	All outputs equally loaded	—	—	250	ps	
t_{6A}	Delay, REF Rising Edge to CLKOUT Rising Edge	Measured at $V_{DD}/2$	—	0	± 350	ps	
t_{6B}	Delay, REF Rising Edge to CLKOUT Rising Edge	Measured at $V_{DD}/2$ in PLL bypass mode (IDT23S09E only)	1	5	8.7	ns	
t_7	Device-to-Device Skew	Measured at $V_{DD}/2$ on the CLKOUT pins of devices	—	0	700	ps	
t_8	Output Slew Rate	Measured between 0.8V and 2V using Test Circuit 2	1	—	—	V/ns	
t_9	Cycle-to-Cycle Jitter	Measured at 66.66MHz, loaded outputs	—	—	200	ps	
t_{LOCK}	PLL Lock Time	Stable power supply, valid clock presented on REF pin	—	—	1	ms	

NOTES:

1. REF Input has a threshold voltage of $V_{DD}/2$.
2. All parameters specified with loaded outputs.

ZERO DELAY AND SKEW CONTROL



All outputs should be uniformly loaded in order to achieve Zero I/O Delay. Since the CLKOUT pin is the internal feedback for the PLL, its relative loading can affect and adjust the input/output delay.

For designs utilizing zero I/O Delay, all outputs including CLKOUT must be equally loaded. Even if the output is not used, it must have a capacitive load equal to that on the other outputs in order to obtain true zero I/O Delay. For zero output-to-output skew, all outputs must be loaded equally.


SPREAD SPECTRUM COMPATIBLE

Many systems being designed now use a technology called Spread Spectrum Frequency Timing Generation. This product is designed not to filter off the Spread Spectrum feature of the reference input, assuming it exists. When a zero delay buffer is not designed to pass the Spread Spectrum feature through, the result is a significant amount of tracking skew, which may cause problems in systems requiring synchronization.


TEST CIRCUITS

Test Circuit 1 (all Parameters Except t_8)Test Circuit 2 (t_8 , Output Slew Rate On -1H Devices)


SWITCHING WAVEFORMS




Duty Cycle Timing




Output to Output Skew



All Outputs Rise/Fall Time




Input to Output Propagation Delay



Device to Device Skew

ORDERING INFORMATION



Part / Order Number	Shipping Packaging	Package	Temperature
23S09E-1DCG	Tubes	16-pin SOIC	0° to +70° C
23S09E-1DCG8	Tape and Reel	16-pin SOIC	0° to +70° C
23S09E-1DCGI	Tubes	16-pin SOIC	-40° to +85°C
23S09E-1DCGI8	Tape and Reel	16-pin SOIC	-40° to +85°C
23S09E-1HDCG	Tubes	16-pin SOIC	0° to +70° C
23S09E-1HDCG8	Tape and Reel	16-pin SOIC	0° to +70° C
23S09E-1HDCGI	Tubes	16-pin SOIC	-40° to +85°C
23S09E-1HDCGI8	Tape and Reel	16-pin SOIC	-40° to +85°C
23S09E-1HPGG	Tubes	16-pin TSSOP	0° to +70° C
23S09E-1HPGG8	Tape and Reel	16-pin TSSOP	0° to +70° C
23S09E-1HPGGI	Tubes	16-pin TSSOP	-40° to +85°C
23S09E-1HPGGI8	Tape and Reel	16-pin TSSOP	-40° to +85°C

IMPORTANT NOTICE AND DISCLAIMER

RENESAS ELECTRONICS CORPORATION AND ITS SUBSIDIARIES ("RENESAS") PROVIDES TECHNICAL SPECIFICATIONS AND RELIABILITY DATA (INCLUDING DATASHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, WITHOUT LIMITATION, ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR NON-INFRINGEMENT OF THIRD-PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for developers who are designing with Renesas products. You are solely responsible for (1) selecting the appropriate products for your application, (2) designing, validating, and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, or other requirements. These resources are subject to change without notice. Renesas grants you permission to use these resources only to develop an application that uses Renesas products. Other reproduction or use of these resources is strictly prohibited. No license is granted to any other Renesas intellectual property or to any third-party intellectual property. Renesas disclaims responsibility for, and you will fully indemnify Renesas and its representatives against, any claims, damages, costs, losses, or liabilities arising from your use of these resources. Renesas' products are provided only subject to Renesas' Terms and Conditions of Sale or other applicable terms agreed to in writing. No use of any Renesas resources expands or otherwise alters any applicable warranties or warranty disclaimers for these products.

(Disclaimer Rev.1.01)

Corporate Headquarters

TOYOSU FORESIA, 3-2-24 Toyosu,
Koto-ku, Tokyo 135-0061, Japan
www.renesas.com

Trademarks

Renesas and the Renesas logo are trademarks of Renesas Electronics Corporation. All trademarks and registered trademarks are the property of their respective owners.

Contact Information

For further information on a product, technology, the most up-to-date version of a document, or your nearest sales office, please visit www.renesas.com/contact-us/.