

552-02

Low Skew 2-Input MUX and 1 to 8 Clock Buffer

Description

The 552-02 is a low skew, single-input to eight-output clock buffer. The device offers a dual input with pin select for switching between two clock sources. For a low skew 1 to 4 buffer, see the [553](#).

Renesas makes many non-PLL and PLL-based low skew output devices as well as Zero Delay Buffers to synchronize clocks. Contact Renesas for all of your clocking needs.

Features

- Low skew outputs: 50ps maximum
- Packaged in 16-pin TSSOP, Pb-free
- Low power CMOS technology
- Operating voltages of 2.5V to 5V
- Output Enable pin tri-states outputs
- 5V tolerant input clocks
- Input/Output clock frequency up to 200MHz
- Input clock multiplexer simplifies clock selection
- Industrial temperature




Figure 1. Block Diagram

Contents

- 1. Pin Information3
 - 1.1 Pin Assignments3
 - 1.2 Input Source Select.....3
 - 1.3 Pin Descriptions.....3
- 2. External Components.....4
- 3. Specifications4
 - 3.1 Absolute Maximum Ratings.....4
 - 3.2 Recommended Operating Conditions.....4
 - 3.3 DC Electrical Specifications5
 - 3.4 AC Electrical Specifications.....6
- 4. Package Outline Drawings7
- 5. Ordering Information.....7
- 6. Revision History7

Figures

- Figure 1. Block Diagram.....1
- Figure 2. 16-Pin TSSOP Pin Assignments – Top View.....3

1. Pin Information

1.1 Pin Assignments




Figure 2. 16-TSSOP Pin Assignments – Top View

1.2 Input Source Select

SELA	Input
0	INB
1	INA

1.3 Pin Descriptions

Pin Number	Pin Name	Pin Type	Description
1	OE	Input	Output Enable. Tri-states outputs when low. Internal pull-up resistor.
2	VDD	Power	Connect to +2.5V, +3.3V or +5.0V. Must be the same as pin 15.
3	Q0	Output	Clock Output 0.
4	Q1	Output	Clock Output 1.
5	Q2	Output	Clock Output 2.
6	Q3	Output	Clock Output 3.
7	GND	Power	Connect to ground.
8	INB	Input	Clock Input B. 5.0V tolerant.
9	INA	Input	Clock Input A. 5.0V tolerant.
10	GND	Power	Connect to ground.
11	Q4	Output	Clock Output 4.
12	Q5	Output	Clock Output 5.
13	Q6	Output	Clock Output 6.
14	Q7	Output	Clock Output 7.
15	VDD	Power	Connect to +2.5V, +3.3V or +5.0V. Must be the same as pin 2.
16	SELA	Input	Selects either INA or INB. Internal pull-up resistor.

2. External Components

A minimum number of external components are required for proper operation. Decoupling capacitors of 0.01 μ F should be connected between V_{DD} on pin 2 and GND on pin 7, and between V_{DD} on pin 15 and GND on pin 10, as close to the device as possible. A 33 Ω series terminating resistor should be used on each clock output if the trace is longer than 1-inch.

To achieve the low output skews that the 552-02 is capable of, careful attention must be paid to board layout. Essentially, all 8 outputs must have identical terminations, identical loads, and identical trace geometries. If they do not, the output skew will be degraded. For example, using a 30 Ω series termination on one output (with 33 Ω on the others) will cause at least 15ps of skew.

3. Specifications

3.1 Absolute Maximum Ratings

Caution: Do not operate at or near the maximum ratings listed for extended periods of time. Exposure to such conditions can adversely impact product reliability and result in failures not covered by warranty.

Parameter	Symbol	Minimum	Maximum	Unit
Supply Voltage, V_{DD}	-	-	7	V
SELA, OE and all Outputs	-	-0.5	$V_{DD} + 0.5$	V
INA and INB	-	0.5	5.5	V
Ambient Operating Temperature	T_{JMAX}	-40	+85	$^{\circ}$ C
Storage Temperature	T_{ST}	-65	+150	$^{\circ}$ C
Junction Temperature	$V_{ESDHB M}$	-	175	$^{\circ}$ C
Soldering Temperature	V_{ESDCDM}	-	260	$^{\circ}$ C

3.2 Recommended Operating Conditions

Parameter	Minimum	Maximum	Unit
Ambient Operating Temperature	-40	+85	$^{\circ}$ C
Power Supply Voltage (measured in respect GND)	+2.375	+5.25	V

3.3 DC Electrical Specifications

VDD = 2.5V ±5%; T_A = -40°C to +85°C, unless otherwise specified.

Parameter	Symbol	Conditions	Minimum	Typical	Maximum	Unit
Operating Voltage	V _{DD}	-	2.375	-	2.625	V
Input High Voltage, INA, INB ^[1]	V _{IH}	-	V _{DD} /2 + 0.5	-	5.5	V
Input Low Voltage, INA, INB ^[1]	V _{IL}	-	-	-	V _{DD} /2 - 0.5	V
Input High Voltage, OE, SELA	V _{IH}	-	1.8	-	V _{DD}	V
Input Low Voltage, OE, SELA	V _{IL}	-	-	-	0.7	V
Output High Voltage	V _{OH}	I _{OH} = -16mA	2	-	-	V
Output Low Voltage	V _{OL}	I _{OL} = 16mA	-	-	0.4	V
Operating Supply Current	I _{DD}	No load, 135MHz	-	35	-	mA
Short Circuit Current	I _{OS}	Each output	-	60	-	mA

1. Nominal switching threshold is V_{DD}/2.

VDD = 3.3V ±5%; T_A = -40°C to +85°C, unless otherwise specified.

Parameter	Symbol	Conditions	Minimum	Typical	Maximum	Unit
Operating Voltage	V _{DD}	-	3.135	-	3.465	V
Input High Voltage, INA, INB ^[1]	V _{IH}	-	V _{DD} /2 + 0.7	-	5.5	V
Input Low Voltage, INA, INB ^[1]	V _{IL}	-	-	-	V _{DD} /2 - 0.7	V
Input High Voltage, OE, SELA	V _{IH}	-	2	-	V _{DD}	V
Input Low Voltage, OE, SELA	V _{IL}	-	-	-	0.8	V
Output High Voltage	V _{OH}	I _{OH} = -25mA	2.4	-	-	V
Output Low Voltage	V _{OL}	I _{OL} = 25mA	-	-	0.4	V
Output High Voltage (CMOS Level)	V _{OH}	I _{OH} = -12mA	V _{DD} - 0.4	-	-	V
Operating Supply Current	I _{DD}	No load, 135MHz	-	50	-	mA
Short Circuit Current	I _{OS}	Each output	-	80	-	mA

1. Nominal switching threshold is V_{DD}/2.

VDD = 5.0V ±5%; T_A = -40°C to +85°C, unless otherwise specified.

Parameter	Symbol	Conditions	Minimum	Typical	Maximum	Unit
Operating Voltage	V _{DD}	-	4.75	-	5.25	V
Input High Voltage, INA, INB ^[1]	V _{IH}	-	V _{DD} /2 + 1	-	5.5	V
Input Low Voltage, INA, INB ^[1]	V _{IL}	-	-	-	V _{DD} /2 - 1	V
Input High Voltage, OE, SELA	V _{IH}	-	2	-	V _{DD}	V
Input Low Voltage, OE, SELA	V _{IL}	-	-	-	0.8	V
Output High Voltage	V _{OH}	I _{OH} = -35mA	2.4	-	-	V
Output Low Voltage	V _{OL}	I _{OL} = 35mA	-	-	0.4	V
Output High Voltage (CMOS Level)	V _{OH}	I _{OH} = -12mA	V _{DD} - 0.4	-	-	V
Operating Supply Current	I _{DD}	No load, 135MHz	-	85	-	mA
Short Circuit Current	I _{OS}	Each output	-	100	-	mA

1. Nominal switching threshold is V_{DD}/2.

3.4 AC Electrical Specifications

VDD = 2.5V ±5%; T_A = -40°C to +85°C, unless otherwise specified.

Parameter	Symbol	Conditions	Minimum	Typical	Maximum	Unit
Input Frequency	-	-	0	-	200	MHz
Output Rise Time	t _{OR}	0.8V to 2.0V, C _L = 15pF	-	1.0	1.5	ns
Output Fall Time	t _{OF}	2.0V to 0.8V, C _L = 15pF	-	1.0	1.5	ns
Propagation Delay ^[1]	-	-	-	3.5	-	ns
Output to Output Skew ^[2]	-	Rising edges at V _{DD} /2	-	0	50	ps
Input A to Input B Skew ^[3]	-	-	-	0	50	ps

1. With rail-to-rail input clock.
2. Between any two outputs with equal loading.
3. Propagation delay matching through the part.
4. Duty cycle on outputs will match incoming clock duty cycle. Consult Renesas for tight duty cycle clock generators.

VDD = 3.3V ±5%; T_A = -40°C to +85°C, unless otherwise specified.

Parameter	Symbol	Conditions	Minimum	Typical	Maximum	Unit
Input Frequency	-	-	0	-	200	MHz
Output Rise Time	t _{OR}	0.8V to 2.0V, C _L = 15pF	-	0.6	1.0	ns
Output Fall Time	t _{OF}	2.0V to 0.8V, C _L = 15pF	-	0.6	1.0	ns
Propagation Delay ^[1]	-	-	2.0	3.0	5.5	ns
Output to Output Skew ^[2]	-	Rising edges at V _{DD} /2	-	0	50	ps
Input A to Input B Skew ^[3]	-	-	-	0	50	ps
Part-to-Part Skew	-	-	-	-	3.5	ns

1. With rail-to-rail input clock.
2. Between any two outputs with equal loading.
3. Propagation delay matching through the part.
4. Duty cycle on outputs will match incoming clock duty cycle. Consult Renesas for tight duty cycle clock generators.

VDD = 5.0V ±5%; T_A = -40°C to +85°C, unless otherwise specified.

Parameter	Symbol	Conditions	Minimum	Typical	Maximum	Unit
Input Frequency	-	-	0	-	200	MHz
Output Rise Time	t _{OR}	0.8V to 2.0V, C _L = 15pF	-	0.3	0.7	ns
Output Fall Time	t _{OF}	2.0V to 0.8V, C _L = 15pF	-	0.3	0.7	ns
Propagation Delay ^[1]	-	-	-	2.8	-	ns
Output to Output Skew ^[2]	-	Rising edges at V _{DD} /2	-	0	50	ps
Input A to Input B Skew ^[3]	-	-	-	0	50	ps

1. With rail-to-rail input clock.
2. Between any two outputs with equal loading.
3. Propagation delay matching through the part.
4. Duty cycle on outputs will match incoming clock duty cycle. Consult Renesas for tight duty cycle clock generators.

4. Package Outline Drawings



The package outline drawings are located at the end of this document and are accessible from the Renesas website. The package information is the most current data available and is subject to change without revision of this document.

5. Ordering Information

Part Number	Marking	Package Description	Carrier Type	Temperature Range
552G-02I	552G-02I	16-TSSOP , 4.4mm Body, 0.65 Pitch	Tubes	-40°C to +85°C
552G-02IT	552G-02I	16-TSSOP , 4.4mm Body, 0.65 Pitch	Tape and Reel	-40°C to +85°C
552G-02ILN	552G02IN	16-TSSOP , 4.4mm Body, 0.65 Pitch	Tubes	-40°C to +85°C
552G-02ILNT	552G02IN	16-TSSOP , 4.4mm Body, 0.65 Pitch	Tape and Reel	-40°C to +85°C


6. Revision History

Revision	Date	Description
1.09	Feb 25, 2025	Reformatted to Renesas template.
-	Feb 17, 2006	Formerly Revision H version of IDT branded datasheet.



NOTE:

1. ALL DIMENSIONS ARE IN MILLIMETERS



LAND PATTERN DIMENSIONS

NOTE:
1. ALL DIMENSIONS ARE IN MILLIMETERS

Package Revision History		
Date Created	Rev No.	Description
Jan 26, 2018	Rev 00	Revised from PSC-4056-02 PGG16

IMPORTANT NOTICE AND DISCLAIMER

RENESAS ELECTRONICS CORPORATION AND ITS SUBSIDIARIES ("RENESAS") PROVIDES TECHNICAL SPECIFICATIONS AND RELIABILITY DATA (INCLUDING DATASHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, WITHOUT LIMITATION, ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR NON-INFRINGEMENT OF THIRD-PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for developers who are designing with Renesas products. You are solely responsible for (1) selecting the appropriate products for your application, (2) designing, validating, and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, or other requirements. These resources are subject to change without notice. Renesas grants you permission to use these resources only to develop an application that uses Renesas products. Other reproduction or use of these resources is strictly prohibited. No license is granted to any other Renesas intellectual property or to any third-party intellectual property. Renesas disclaims responsibility for, and you will fully indemnify Renesas and its representatives against, any claims, damages, costs, losses, or liabilities arising from your use of these resources. Renesas' products are provided only subject to Renesas' Terms and Conditions of Sale or other applicable terms agreed to in writing. No use of any Renesas resources expands or otherwise alters any applicable warranties or warranty disclaimers for these products.

(Disclaimer Rev.1.01)

Corporate Headquarters

TOYOSU FORESIA, 3-2-24 Toyosu,
Koto-ku, Tokyo 135-0061, Japan
www.renesas.com

Contact Information

For further information on a product, technology, the most up-to-date version of a document, or your nearest sales office, please visit www.renesas.com/contact-us/.

Trademarks

Renesas and the Renesas logo are trademarks of Renesas Electronics Corporation. All trademarks and registered trademarks are the property of their respective owners.