# Old Company Name in Catalogs and Other Documents

On April 1<sup>st</sup>, 2010, NEC Electronics Corporation merged with Renesas Technology Corporation, and Renesas Electronics Corporation took over all the business of both companies. Therefore, although the old company name remains in this document, it is a valid Renesas Electronics document. We appreciate your understanding.

Renesas Electronics website: http://www.renesas.com

April 1<sup>st</sup>, 2010 Renesas Electronics Corporation

Issued by: Renesas Electronics Corporation (http://www.renesas.com)

Send any inquiries to http://www.renesas.com/inquiry.

### Mask ROM number

# RENESAS TECHNOLOGY-CHIP 16-BIT MICROCOMPUTER M30290M8-XXXHP MASK ROM CONFIRMATION FORM

Date: Section head Supervisor signature signature

Note : Please complete all items marked\*

		Company	TEL		e e	Submitted by	Supervisor	
*	Customer	name		(	)	anc atur		
Customer	Date issued	Date:			lssu sign			

### \*1. Check sheet

Renesas processes the mask files generated by the mask file generation utilities out of those held on the floppy disks you give in to us, and forms them into masks. Hence, we assume liability provided that there is any discrepancy between the contents of these mask files and the ROM data to be burned into products we produce. Check thoroughly the contents of the mask files you give in.

Prepare 3.5 inches 2HD (IBM format) floppy disks. And store only one mask file in a floppy disk.

Microcomputer type No.:		3029	90M8	8-XX	XH	Ρ		
File code:								(hex)
Mask file name:								.MSK (alpha-numeric 8-digit)

#### \*2. Mark specification

The mark specification differs according to the type of package. After entering the mark specification on the separate mark specification sheet (for each package), attach that sheet to this masking check sheet for submission to Renesas.

For the M30290M8-XXXHP, submit the 80P6Q mark specification sheet.

#### \*3. Usage Conditions

For our reference when of testing our products, please reply to the following questions about the usage of the products you ordered.

- (1) Which kind of oscillation circuit is used?
  - □ XIN-XOUT oscillator
- □ XCIN-XCOUT oscillator
- On chip oscillator
- PLL frequency synthesizer
- (2) Which kind of XIN-XOUT oscillation circuit is used?
  - □ Ceramic resonator □ Quartz-crystal oscillator
  - □ External clock input
- Other (

What frequency do you use?

f(Xin) =		MHz
----------	--	-----

)

)

# RENESAS TECHNOLOGY-CHIP 16-BIT MICROCOMPUTER M30290M8-XXXHP MASK ROM CONFIRMATION FORM

- (3) Which kind of XCIN-XCOUT oscillation circuit is used?
  - Ceramic resonator
     Quartz-crystal oscillator
  - External clock input
    Other (

What frequency do you use?

		•		,											
		f(Xo	сın) =				k	Ηz							
(4)		-	-	g supply ating vo	-	-	-								
	2.7 3	3.0	3.3	3.6	3.9	4.2	4.5		5.0		5.5				
	I	1	1	1	1	I	1		1						
											(\	()			
(5)	<ul><li>(5) Which operating ambient temperature do you use?</li><li>(Circle the operating temperature range of use)</li></ul>														
	-40 -	-30	-20	-10	0	10	20	30	40	50	60	70	80	85	
		_												(°C)	
	I	I	I	I	I	I	I	I	I	I	I	I			
(6)	Do vo	ou us	e l²C	(Inter I	C) bus	function	on?								
• •	, 		ot use	-	,		se								
			1 450				00								
(7)	Do yo	ou us	e IE (	Inter E	quipmo	ent) bu	is func	tion?							
		No	ot use			🗆 U	se								

- (8) Which Voltage Detection function do you use?
  - □ Not use □ Use Vdet4
  - □ Use Vdet3

Thank you cooperation.

\*4. Special item (Indicate none if there is not specified item)