SUMITOMO BAKELITE CO₄LTD.

SAFETY DATA SHEET

1. Product and company identification

Chemical description Epoxy Molding Compound

Name of the chemical SUMIKON® EME-G700H Type A

Other means of identification

SDS number P003136
Recommended use and Limitations on use

Recommended use For Semiconductors. **Limitations on use** For industrial use only.

Name, address and telephone of manufacturer, importer or supplier

SUMITOMO BAKELITE CO.,LTD.

Tennoz Park Side Bldg.

5-8, Higashi-Shinagawa 2-Chome Shinagawa-ku, Tokyo 140-0002, Japan

Phone: +81-3-5462-4038 e-mail: ukqa@sumibe.co.jp

EMERGENCY CONTACTS:

SUMITOMO PLASTICS AMERICA, INC. Phone: +1-408-243-8402 (U.S.A.) CHEMTREC (24hours everyday) Phone: +1-800-424-9300 (U.S.A.)

SUMITOMO BAKELITE SINGAPORE PTE.LTD. Phone: +65-6752-6431 (Singapore) N.V. SUMITOMO BAKELITE EUROPE S.A. Phone: +32-9295-0167 (Belgium) SUMITOMO BAKELITE (SUZHOU) CO.,LTD. Phone: +86-512-67613850 (China) SUMITOMO BAKELITE (TAIWAN) CO.,LTD. Phone: +886-7-787-1285 (Taiwan) SUMITOMO BAKELITE (SINGAPORE) CO., LTD. MALAYSIA Branch Office.

Phone: +60-3-7660-8022 (Malaysia)

.....

2. Hazards identification

Hazard classification

Physical hazards Not classified.
Health hazards Not classified.
Environmental hazards Not classified.

*Hazards not stated here are "Not classified", "Not applicable" or "Classification not possible".

Label elements

Symbols None.
Signal word None.
Hazard statement None.

Precautionary statement

Prevention Do not handle until all safety precautions have been read and understood. Use personal

protective equipment as required.

Response IF exposed or concerned: Get medical advice/attention.

Storage Store in accordance with local/regional/national/international regulation.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards None known.

3. Composition/information on ingredients

Substance or mixtureMixtureMaterial name: SUMIKON® EME-G700H Type A4018 Version No.: 04 Revision date: 17-08-2020

Chemical properties	CAS Number	Concentration (%)
Epoxy resin	Trade Secret	5 - 10
Phenol Resin	Trade Secret	1 - 5
Silica(Amorphous) A	60676-86-0	70 - 80
Silica(Amorphous) B	7631-86-9	5 - 10
Carbon Black	1333-86-4	0.1 - 1

Composition comments

The range of Concentration is greater than or equal to the lower limit but less than the upper limit. Disclosure of composition information is based on the interpretation of the Regulation of Labeling and Hazard Communication of Hazardous Chemicals.

4. First aid measures

First aid measures for different exposure routes

Inhalation Move to fresh air.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists. Eye contact Do not rub eyes. Rinse with water. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth.

Get medical attention if symptoms occur.

Most important symptoms

and effects

Irritation of eyes and mucous membranes. Dusts may irritate the respiratory tract, skin and eyes.

Personal protection for first-aid responders

First aid personnel must wear protective gloves/protective clothing/eye protection/face protection.

IF exposed or concerned: Get medical advice/attention.

Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves.

Notes to physician Treat symptomatically. Symptoms may be delayed.

5. Fire-fighting measures

Extinguishing media Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Extinguishing media to avoid

Specific hazards during fire

fighting

Development of hazardous combustion gases or vapours possible in the event of fire.

Do not use water jet as an extinguisher, as this will spread the fire.

Special fire fighting

General fire hazards

procedures

Protection of fire-fighters

Move containers from fire area if you can do so without risk.

Wear suitable protective equipment. Use personal protective mask and fight fire from upwind, to avoid fumes upon combustion.

No unusual fire or explosion hazards noted.

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials.

6. Accidental release measures

Personal precautions Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of

low areas. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. For personal

protection, see section 8 of the SDS.

Environmental precautions Spill cleanup methods

Avoid discharge into drains, water courses or onto the ground.

Avoid the generation of dusts during clean-up. Collect dust using a vacuum cleaner equipped with HEPA filter. Prevent entry into waterways, sewer, basements or confined areas. Stop the flow of

material, if this is without risk.

Large Spills: Wet down with water and dike for later disposal. Shovel the material into waste

container. Following product recovery, flush area with water.

Small Spills: Sweep up or vacuum up spillage and collect in suitable container for disposal. For

waste disposal, see section 13.

Material name: SUMIKON® EME-G700H Type A SDS TATWAN

7. Handling and storage

Handling

Technical measures No specific recommendations.

Local and general

ventilation

Provide appropriate exhaust ventilation at places where dust is formed.

Precautions Minimise dust generation and accumulation.

Safe handling advice Avoid prolonged exposure.

Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Storage

Technical measures No specific recommendations.

Suitable storage conditions

Keep container tightly closed. Store in a well-ventilated place. Guard against dust accumulation of

this material.

Store away from incompatible materials (see Section 10 of the SDS). Keep dry and cool below 5°C

for quality.

Incompatible materials Strong oxidising agents. For further information, please refer to section 10 of the SDS.

Safe packaging materials Store in original tightly closed container.

8. Exposure controls/personal protection

Occupational exposure limits

OELs. (Standards on Workplace Atmosphere of Dangerous and Hazardous Materials)

 Components
 Type
 Value

 Carbon Black (CAS 1333-86-4)
 STEL
 7 mg/m3

 TWA
 3.5 mg/m3

Exposure limits

US. ACGIH Threshold Limit Values

ComponentsTypeValueFormCarbon Black (CAS
1333-86-4)TWA3 mg/m3Inhalable fraction.

Biological limit valuesNo biological exposure limits noted for the ingredient(s).

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. If material is ground, cut, or used in any operation which may generate dusts, use appropriate local exhaust

ventilation to keep exposures below the recommended exposure limits.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection For prolonged or repeated skin contact use suitable protective gloves. Use protective gloves as

required.

Other Use personal protective equipment as required.

Respiratory protection Wear respirator with dust filter.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

Wedi appropriate tremai protective doming, when necessary.

General hygieneAlways observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to

remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Solid.

Form Not available.

Material name: SUMIKON® EME-G700H Type A

SDS TAIWAN

Colour Not available.

Odour Epoxy.

Odour threshold Not available. Melting point/freezing point Not available. Not available. рH Not available.

Boiling point, initial boiling point, and boiling range

Flammability (solid, gas) Not available. Flash point Not available. **Decomposition temperature** Not available. **Auto-ignition temperature** Not available.

Upper/lower flammability or explosive limits **Flammability limit - lower** Not available.

(%)

Flammability limit -

upper (%)

Not available.

Explosive limit - lower (

%)

Not available.

Explosive limit – upper

(%)

Not available.

Vapour pressure Not available. Vapour density Not available. **Density** Not available.

Solubility(ies)

Not available. Solubility (water) **Partition coefficient** Not available. (n-octanol/water)

Not available. **Evaporation rate**

Other data

Explosive properties Not explosive. **Oxidising properties** Not oxidising. Specific gravity 1.8 - 2.2

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Stable under recommended storage conditions. Stability

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Contact with

incompatible materials. Keep away from heat, moisture and sunlight for quality.

Incompatible materials Strong oxidising agents. Strong acids, alkalies and oxidizing agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Dust may irritate respiratory system. Prolonged inhalation may be harmful.

Skin contact Dust or powder may irritate the skin.

Eye contact Dust may irritate the eyes.

Ingestion Expected to be a low ingestion hazard.

Material name: SUMIKON® EME-G700H Type A 4018 Version No.: 04 Revision date: 17-08-2020

Irritation of eyes and mucous membranes. Dusts may irritate the respiratory tract, skin and eyes Symptoms

Information on toxicological effects

Acute toxicity

Components Test Results Species

Carbon Black (CAS 1333-86-4)

Acute Oral

LD50 Rat > 8000 mg/kg *

Silica(Amorphous) A (CAS 60676-86-0)

Acute

Oral

LD50 Rat > 22500 mg/kg *

Silica(Amorphous) B (CAS 7631-86-9)

Acute Oral

LD50 Rat >= 22500 mg/kg

Routes of exposure Inhalation. Skin contact. Eye contact.

Respiratory or skin sensitisation

Respiratory sensitisation Not available.

Skin sensitisation This product is not expected to cause skin sensitisation.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Risk of cancer cannot be excluded with prolonged exposure.

ACGIH Carcinogens

Carbon Black (CAS 1333-86-4) A3 Confirmed animal carcinogen with unknown relevance to

IARC Monographs. Overall Evaluation of Carcinogenicity

Carbon Black (CAS 1333-86-4) 2B Possibly carcinogenic to humans.

Silica(Amorphous) A (CAS 60676-86-0) 3 Not classifiable as to carcinogenicity to humans. Silica(Amorphous) B (CAS 7631-86-9) 3 Not classifiable as to carcinogenicity to humans.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity

- single exposure

Not available.

Specific target organ toxicity

- repeated exposure

Not available.

Aspiration hazard Not available.

Chronic toxicity or long-term

Prolonged inhalation may be harmful.

toxicity

Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

There are no data on the ecotoxicity of this product.

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

Bioaccumulation Not available.

Mobility in soil No data available for this product.

Other hazardous effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site.

Material name: SUMIKON® EME-G700H Type A SDS TATWAN **Disposal considerations**

Residual waste Dispose in accordance with local regulations.

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Local disposal regulations

Collect and reclaim or dispose in sealed containers at licensed waste disposal site.

14. Transport information

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Specific precautions Keep cool below 5°C.

Keep containers tightly closed. And avoid leaks, spills or collapse of cargo to avoid damage to

containers.

15. Regulatory information

Applicable regulations This safety data sheet was prepared in accordance with the Rules on Hazardous Communication of

Dangerous Materials and Toxic Materials. All components are on the Taiwan's existing chemicals

inventory list.

Methods and Facilities Standards for the Storage, Clearance and Disposal of Industrial Waste

Not listed.

Standards of Permissible Exposure Limits of Airborne Hazardous Substances in Workplace

Carbon Black (CAS 1333-86-4)

GHS Classification List: GHS implementation phase 1, 2 and 3 (CLA No. 0980145063, 0990146707, and

1020146801)

Carbon Black (CAS 1333-86-4) CARBON BLACK (Priority Management Chemicals: Priority 2)

Taiwan Controlled Chemical

Not listed.

Priority Management Chemical List (Regulations on Handling Priority Managed Chemicals), as amended

Carbon Black (CAS 1333-86-4) Listed.

Regulation of Labeling and Hazard Communication of Dangerous and Toxic Substances: Dangerous Materials Classification

Not listed.

Regulation of Labeling and Hazard Communication of Dangerous and Toxic Substances: Toxic Materials Classification

Not listed.

International regulations

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Montreal Protocol

Not applicable.

Kyoto Protocol

Not applicable.

Basel Convention

Not applicable.

Material name: SUMIKON® EME-G700H Type A SDS TATWAN 4018 Version No.: 04 Revision date: 17-08-2020

16. Other information

References •ACGIH (2017)

•EPA: AQUIRE database

•NLM: Hazardous Substances Data Base HSDB® - Hazardous Substances Data Bank

•IARC (vol. 1~117)

•Taiwan. Dangerous Materials (Rules on Hazard Communication of Dangerous Materials and Toxic Materials)

•Taiwan. OELs. (Standards of Permissible Exposure Limits of Airborne Hazardous Substances in Workplace)

• Taiwan. Toxic Chemical Substances (TCS) (List of Toxic Chemical Substances announced by the Environmental Protection Administration)

•Taiwan. CNS15030 Z1051: Classification and Labeling of Chemicals

•UN. Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

ST/SG/AC.10/30/Rev.4

• Japan. GHS Classifications of Regulated Chemicals (NITE)

Disclaimer SUMITOMO BAKELITE CO., LTD. cannot anticipate all conditions under which this information and

its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use.

 Issue date
 19-03-2013

 Revision date
 17-08-2020

Material name: SUMIKON® EME-G700H Type A 4018 Version No.: 04 Revision date: 17-08-2020