

SDS (Safety Data Sheet) 安全資料表

一、Product and Company information 物品與廠商資料

無鉛焊錫球 (SAC405)
Lead-Free Solder Sphere (SAC405)
半導體工程
Semiconductor Engineering
恆碩科技股份有限公司
ACCURUS SCIENTIFIC CO., LTD.
中華民國台灣 717 台南市仁德區文賢路一段 508~51 號
No.508-51, Section 1, Wen-Sien Road, Rende District, Tainan City 717, Taiwan (R.O.C.)
06-3661288
+886-6-3661288
06-2660474
+886-6-2660474
06-3661288
+886-6-3661288

二、Hazards identification information 危害辨識資料

Hazard classification of the product 物品危害分類: 健康危害-特定標的器官系統毒性物質-重複暴露-二級。 Specific target organ systemic toxicity following repeated exposure. (Hazard category 2) Label content標示內容 Label Format: Health Hazards 象徵符號:健康危害 Signal words: Warning 警示語:警告 Hazard statements: May cause damage to organ. 危害警告訊息:長期或重複暴露可能對器官造成傷害。 Precautionary statements:危害防範措施: 1. 如遇意外或覺得不適,立即洽詢醫療。 Get medical attention/advice if you feel unwell. 2. 使用本產品時,不得吃東西、喝水或抽菸。 Do not eat, drink or smoke when using this product. 3. 處置後徹底清洗雙手。 Wash hands thoroughly after handling. Other hazards其他危害: -----

三、Ingredients identification information 成分辨識資料

Pure material 純物質 ■ Mixture 混合物			
Chemical property 化學性質			
Chinese and English names of The hazardous ingredients 危害物質成分之中英文名稱	Concentration or concentration ranges (% of contents) 濃度或濃度範圍(成分百分比)	CAS No.	
錫/Tin	95-96	07440-31-5	
銀/Silver	3.8-4.2	07440-22-4	
銅/Copper	0.3-0.7	07440-50-8	

□ Pure material 純物質 ■ Mixture 混合物

四、First-aid Measures 急救措施

	-	The first aid man	sures for different exposure routes 不同暴露途徑之急救方法		
			•		
Immediately m			至新鮮空氣處並依需要維持其呼吸暢通。		
			we the patient to the ventilation and hold his breathing unimpeded.		
	2.	若呼吸停止, 方			
Inhalation		Offering the artificial respiration if patient stop breathing or dyspnea.			
吸入	3.	保持患者温暖			
	4	Keep the patient	warm and rest.		
	4.	立即就醫。	· · · · · · · · · · · · · · · · · · ·		
	1		vice immediately.		
	1.	以大量的清水			
alain a anto at	2		e water to wash.		
skin contact 皮膚接觸	2.		學品再立即用肥皂及水清洗皮膚。		
皮 屑 按 触	2	The chemicals v 如仍有刺激感	vashed out and use the soap and water wash the skin.		
	з.				
ave contect	1.		e of stimulating, Please seek medical advice immediately.		
eye contact 眼睛接觸	1.		民晴或緊閉眼睛。		
叱明好的	2		tient knead or close the eyes.		
	۷.		b並立即沖洗,連續沖洗至就醫為止。		
	Carefully open the eyelid and use water wash, Continuously wash it to seeking medical advice. 3. 儘速就醫。 Seek medical advice immediately				
Ingestion	1.	Seek medical advice immediately. 勿餵食任何東西及催吐(除非醫療人員指示)。			
食入	1.	勿嚴食任何東西及准任(除非醫療入員指示)。 Don't queasy and feed the food (Unless medical instructions of personnel).			
R · C	2.	立即就醫。			
	2.	エロ 祝 茜 。 Seek medical advice immediately.			
			 銀中毒、銅中毒及末梢神經疾病。 		
		t symptoms and	silver poison × copper poison and nerve ending illness.		
hazardous effects 最重要症狀及危害效應			2. 刺激感及過量吸入熱蒸氣會造成肺水腫。		
		至效應	Excitement and excessive inhale hot vapor can cause lung edema.		
The protection of first-aiders		irst-aiders	應配戴防毒面罩或氧氣筒及防護衣。		
對急救人員之			Must wear the gas masks or oxygen mask and protective clothing.		
		-	1. 患者吞食時,考慮洗胃。		
			The patient considers gastric lavage when eating.		
Notes to phys		5	2. 銀及其無機化合物為神經毒物,可能引起末梢神經疾病。		
對醫師之提示	對醫師之提示		Silver and inorganic compound is the neural poisonous substance, can		
			cause nerve ending disease.		
			5		

五、Fire Fighting Measures 滅火措施

	水、泡沫、乾粉及二氧化碳滅火劑。
適用滅火劑	Water, Foam, Powder and CO2 extinguisher.
Suitable fire extinguishing media	無相關資料可查。
滅火時可能遭遇之特殊危害	No relevant information for inquiring.

encountered during fire-fighting	不適用。 Not application.
Specific fire-fighting methods	氧氟筒及防護衣。
消防人員之特殊防護設備	Oxygen cylinder and protective clothing.

六、Accidental release measures 洩漏處理方法

Personal precautions	避免吸入銲錫煙氣或粉塵。
個人應注意事項	Avoid sucking the solder gas or powder.
Environmental precautions	勿使洩露區域擴大。
環境注意事項	Don't let the area of leakage be expanded.
Methods for cleaning up	冷卻後可進行回收。
清理方法	Recoverable after cooling.

七、Safe handling and storage measures 安全處置與儲存方法

Handling 處置	依廢棄物處理法規處理。		
Handing 处且	According to the refuse disposal ordinance disposal.		
	1. 储存於適當的容器內並做標識。		
	Store in the appropriate container and do identification.		
	2. 置於陰涼、乾燥及通風良好區,避免高溫。		
Store and the to	Put on the shade, drying and ventilate the good place, and avoid the high temperature.		
Storage:儲存 3. 遠離氧化劑如氯氣、酸與過氧化氫等。			
	Far away the oxidant (ex: chlorine, acid and hydrogen peroxide).		
	4. 貯藏溫度:<30℃		
	Custody Temperature : <30°C		

八、Exposure controls measures 暴露預防措施

Engineering control:工程控制				
Control parameters 控制参數				
Element of The hazardous ingredients 元素中英文名稱	8 hours time weighted average exposure limits 八小時日時量 平均容許濃度 TWA	Short-term exposure limits 超時間時量 平均容許濃度 STEL	maximum exposure limits 最高容許濃度 CEILING	biological standards 生物指標 BEIs
錫/Tin	2 mg/m^3	4 mg/m^3		
銀/Silver	0.01 mg/m^3	0.03 mg/m^3		
銅/Copper	銅/Copper 0.2 mg/m ³			
Personal protective equipment 個人防護設備				
respiratory protection 呼吸防護	 ▶ 一般使用:配戴口罩。 General: Wear the gauze mask. ▶ 緊急狀況:粉塵或煙霧超過容許濃度時,應配戴防粉塵及煙霧的防毒面具。 Emergency: Dust or smog exceeds permitting the concentration, need wear avoid dust and smog gas mask. 			
hand protection		橡膠或塑膠的防護手套。		
手部防護 Rubber or plastic protective gloves. eye protection 配戴安全眼鏡及/或面罩(當有粉塵飄散或熱金屬噴濺時)。 Put on the safe glasses and/or mask (If there is dust fly about or hot metal splashing).			ut or hot metal	
skin and body protectio 皮膚及身體防護		應穿戴工作衣及防護手套以避免灼燙傷。 Need wear the smock and protective gloves avoid badly burned.		
Hygiene measures 衛生措施		工作後,吃東西、喝飲料或抽煙前應洗手。 wash hands before eating, drinking the beverage or smoking.		

九、Physical and chemical properties 物理及化學性質

Appearance (physical state, color, etc.) 外觀(物質狀態、顏色等)	物質狀態:固態 Physical state: solid 形 狀:球狀 Form: sphere 顏 色:銀灰色 Color: silver			
Odor	無氣味			
氣味	No smell			
Odor threshold 嗅覺閾值				
Melting point 熔點	218±1℃			
PH value PH 值				
Boiling point/boiling range 沸點/沸點範圍				
Flammability (solid, gas) 易燃性(固體、氣體)	不易燃 No Flammability.			
Flash point 閃火點		°F		°C
Test method 測試方法	Open cup 開杯		Close cup 閉杯	
Decomposition temperature 分解溫度				
Auto ignition temperature 自燃溫度				
Explosion limits 爆炸界限				
Vapor pressure 蒸氣壓				
Vapor density 蒸氣密度				
Density 密度	7.4 ± 0.2 g/cm ³			
Solubility 溶解度				
Partition coefficient(n-octanol/water, 辛醇/水分配係數(log Kow)				
Evaporation rate 揮發速率				

十、Stability and reactivity 安定性及反應性

Stability 安定性:	
Possible hazardous reactions occurring under specific conditions 特殊狀況下可能之危害反應	金屬錫與松節油接觸會產生火災和爆炸。 This metal tin and turpentine contact will result fire and explode.
應避免之狀況	 500℃以上高溫作業,會散出具有毒性的錫氧化物。 Above 500℃ high-temperature work, will produce the contain toxic tin oxides. 約末狀態於空氣中會氧化。 Powder state will be oxidized in the air.

十一、Toxicological information 毒性資料

Routes of exposure 暴露途徑	
Symptoms 症狀	
Acute toxicity 急毒性	可能造成眼睛、鼻子、喉、皮膚的刺激。 Possible induce eye, nose, throat and skin provoke.
lierm toxicity	與皮膚接觸可能使某些人產生皮膚炎或過敏。 Contacts with the skin some people will produce atopic dermatitis.

十二、Ecological information 生態資料

Ecotoxicity 生態毒性	
Persistence and degradability 持久性及降解性	
Bioaccumulative potential 生物蓄積性	
Mobility in soil 土壤中之流動性	
Other adverse effects 其他不良效應	

十三、Waste disposal measures:廢棄處置方法

Methods of waste disposal	可回收再利用或依廢棄物處理法處理。
廢棄處置方法	Utilizing recoverably or according to the refuse disposal ordinance disposal.

十四、Transport information 運送資料

United Nations number(UN No) 聯合國編號	
UN Proper shipping name 聯合國運輸名稱	
Transport hazard class(es) 運輸危害分類	KEEP TIGHTLY CLOSED IATA: NOT RESTRICTED
Packing group 包裝類別	
Marine pollutant(Yes/No) 海洋污染物(是/否)	□ Yes 是 ■ No 否
Specific transport measures and precautionary conditions 特殊運送方法及注意事項	

十五、Regulatory information 法規資料

	1.	職業安全衛生法
		Occupational Safety and Health Act
Applicable regulations	2.	職業安全衛生設施規則
適用法規		Labor safety and Health Act
	3.	危害性化學品標示及通識規則
		Regulations for the Labeling and Hazard Communication of Hazardous Chemicals

4.	勞工作業場所容許暴露標準
	Standards of Permissible Exposure Limits of Airborne Hazardous Substances in
	Workplace
5.	道路交通安全規則
	Road traffic safety code.
6.	事業廢棄物貯存清除處理方法及設施標準
	Methods and Facilities Standards for the Storage, Clearance and Disposal of Industrial
	Waste

十六、Other information 其他資料

,		
一.項目八:TWA & STEL 為純原料之控制參數		
Item 8: TWA & STEL is raw material control parameters.		
二. 上述資料中符號""代表目前查無相關資料。		
The symbol in materials described above "" Representative now no relevant		
information. 三. 免責聲明 Disclaimer:		
原科技		
無法控制的方法得到的結果,恆碩科技恕不負責。自行決定把本品用在本文中提		
及的生產方法上,及採取本文中提及的措施來防止產品在貯存和使用過程中可發		
生的損失和人身傷害都是用戶自己的責任。鑒於此,恆碩科技明確聲明對所有因		
銷售恆碩產品或者特定場合下使用恆碩產品而出現的所有問題,包括針對某一特		
殊用途的可商品化和適用性的問題,均不承擔責任。恆碩科技明確聲明對任何必		
然的或者意外的損失包括利潤方面的損失都不承擔責任。		
The data contained herein are furnished for information only and are believed to be reliable.		
However, ACCURUS Corporation does not assume responsibility for any results obtained by persons		
over whose methods ACCURUS Corporation has no control. It is the user's responsibility to		
determine the suitability of ACCURUS's products or any production methods mentioned herein for a		
particular purpose, and to adopt such precautions as may be advisable for the protection of property		
and persons against any hazards that may be involved in the handling and use of any of ACCURUS		
Corporation's products. In light of the foregoing, ACCURUS Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular		
purpose, arising from sale or use of ACCURUS Corporation's products. ACCURUS Corporation		
on		
on st		