
PRODUCT CHANGE NOTICE

**Manufacturing Site Change for
Assembly of the Listed
Intersil *R5254 Ceramic
Dual-In-Line Packaged
Products**

**Refer to:
PCN11045**

Date: April 29, 2011

April 29, 2011

To: Our Valued Intersil Customer

Subject: **Manufacturing Site Change for Assembly of the Listed Intersil *R5254 Ceramic Dual-In-Line Packaged Products – Amkor (ATP) Muntinlupa City, Philippines**

This notice is to inform you that Intersil is qualifying the Amkor (ATP) facility for performing assembly of the listed R5254* Ceramic Dual-In-Line (Frit Seal Cerdip) packaged products. This action will provide the capability and capacities for Intersil to meet customer's delivery requirements. The product and site-specific qualification activities are in progress and expected to complete during the next three months.

Products affected:

HA7-5147R5254	ICM7218AIJIR5254	ICM7218CIJIR5254
HI1-0303R5254	ICM7218BIJIR5254	ICM7218DIJIR5254

The Amkor (ATP) facility is ISO 9001:2008, TS 16949:2009, ISO 14001:2004, and currently listed as a QML Class Q certified assembly/test location. The ATP facility is currently Intersil qualified for performing assembly operations for various package styles. There will be no change to the POD (package outline drawing), bond wire material, seal glass, package body, package lid, or lead frame. The die attach and final plating (lead finish) shall be as indicated in the table below. The material set and plating combinations for Ceramic Dual-In-Line (Frit Seal Cerdip) assembly are as follows:

Material	Current	ATP
Die Attach	QMI 2419 (Ag Glass)	QMI 3555 (Ag Glass)
Bond Wire	1.25 mil Aluminum (Al)	1.25 mil Aluminum (Al)
Seal Glass	KC800 / LS2010	KC800 / LS2010
Final Plating	Pb-free Solder Dip (SnAgCu)	Matte Tin (Sn)

The assembly qualification plan is designed using MIL-PRF-38535, JEDEC, and other applicable industry standards to confirm there is no impact to form, fit, function, or interchangeability of the product. A summary of the qualification plan is included. The remainder of the manufacturing operations (wafer fabrication, package level electrical testing, shipment, etc.) will continue to be processed to previously established conditions and systems.

Product affected by this change is identifiable via Intersil's internal traceability system. In addition, product assembled at ATP may also be identified by the assembly site code (country of assembly) when marked on the devices. The site code for product assembled at ATP is "L".

Intersil will take all necessary actions to conform to agreed upon customer requirements and to ensure the continued high quality and reliability of Intersil products being supplied. Customers may expect to receive product assembled at either the current or the newly qualified sites beginning *ninety* days from the date of this notification or earlier with approval.

If you have concerns with this change notice, Intersil must hear from you promptly. Please contact the nearest Intersil Sales Office or call the Intersil Corporate line at 1-888-468-3774, in the United States, or 1-321-724-7143 outside of the United States.

Regards,

Jon Brewster

Jon Brewster
Intersil Corporation

PCN11045

CC: J. Touvell D. Decrosta D. Foster J. Broline S. Ang

PCN11045 – Qualification Plan

Reliability Test	5962-8513101XA	5962-8954801PA	7705202EA	HA7-5147R5254
	28 LEAD CERDIP - Silver Glass	8 LEAD CERDIP - Silver Glass	16 LEAD CERDIP - Silver Glass	8 LEAD CERDIP - Silver Glass
Subgroup B1	ss=3 from 1 lot	ss=3 from 1 lot	ss=3 from 1 lot	
	Resistance to Solvents. MIL-PRF-38535 Group B Test Method 2015.	Resistance to Solvents. MIL-PRF-38535 Group B Test Method 2015.	Resistance to Solvents. MIL-PRF-38535 Group B Test Method 2015	
Subgroup B2	ss=3 from 1 lot	ss=3 from 1 lot	ss=3 from 1 lot	
	Die Shear Test or Stud Pull. MIL-PRF-38535 Group B Test Method 2019 or 2027	Die Shear Test or Stud Pull. MIL-PRF-38535 Group B Test Method 2019 or 2027	Die Shear Test or Stud Pull. MIL-PRF-38535 Group B Test Method 2019 or 2027	
	ss=4 from 1 lot	ss=4 from 1 lot	ss=4 from 1 lot	
	Wire Bond strength. MIL-PRF-38535 Group B Test Method 2011. 22 wires from 4 devices	Wire Bond strength. MIL-PRF-38535 Group B Test Method 2011. 22 wires from 4 devices	Wire Bond strength. MIL-PRF-38535 Group B Test Method 2011. 22 wires from 4 devices	
Subgroup B3	ss=22 from 1 lot	ss=22 from 1 lot	ss=22 from 1 lot	ss=22 from 1 lot
	Solderability Lead Finish. MIL-PRF-38535 Group B Test Method 2003	Solderability Lead Finish. MIL-PRF-38535 Group B Test Method 2003.	Solderability Lead Finish. MIL-PRF-38535 Group B Test Method 2003	Solderability Lead Finish. MIL-PRF-38535 Group B Test Method 2003.

PCN11045 – Qualification Plan – cont.

Reliability Test	5962-8513101XA	5962-8954801PA	7705202EA
	28 LEAD CERDIP - Silver Glass	8 LEAD CERDIP - Silver Glass	16 LEAD CERDIP - Silver Glass
Subgroup D1	ss=15 from 1 lot	ss=15 from 1 lot	ss=15 from 1 lot
	a) Physical Dimensions	a) Physical Dimensions	a) Physical Dimensions
Subgroup D2	ss=15 from 1 lot	ss=15 from 1 lot	ss=15 from 1 lot
	a) Lead Integrity	a) Lead Integrity	a) Lead Integrity
	b) Seal Test (Fine & Gross Leak)	b) Seal Test (Fine & Gross Leak)	b) Seal Test (Fine & Gross Leak)
Subgroup D3	ss=15 from 1 lot	ss=15 from 1 lot	ss=15 from 1 lot
	a) Thermal Shock	a) Thermal Shock	a) Thermal Shock
	b) Temp Cycle (100)	b) Temp Cycle (100)	b) Temp Cycle (100)
	c) Moisture Resist	c) Moisture Resist	c) Moisture Resist
	d) Visual Inspection	d) Visual Inspection	d) Visual Inspection
	e) Seal Test (Fine & Gross Leak)	e) Seal Test (Fine & Gross Leak)	e) Seal Test (Fine & Gross Leak)
Subgroup D4	ss=15 from 1 lot	ss=15 from 1 lot	ss=15 from 1 lot
	a) Mechanical Shock	a) Mechanical Shock	a) Mechanical Shock
	b) Vibration	b) Vibration	b) Vibration
	c) Constant Acc.	c) Constant Acc.	c) Constant Acc.
	d) Seal Test (Fine & Gross Leak)	d) Seal Test (Fine & Gross Leak)	d) Seal Test (Fine & Gross Leak)
	e) Visual Inspection	e) Visual Inspection	e) Visual Inspection
Subgroup D5	ss=15 from 1 lot	ss=15 from 1 lot	ss=15 from 1 lot
	a) Salt Atmosphere	a) Salt Atmosphere	a) Salt Atmosphere
	b) Visual Inspection	b) Visual Inspection	b) Visual Inspection
	c) Seal Test (Fine & Gross Leak)	c) Seal Test (Fine & Gross Leak)	c) Seal Test (Fine & Gross Leak)
Subgroup D6	ss=3 from 1 lot	ss=3 from 1 lot	ss=3 from 1 lot
	Internal Water Vapor	Internal Water Vapor	Internal Water Vapor
Subgroup D7	ss=15 from 1 lot	ss=15 from 1 lot	ss=15 from 1 lot
	Adhesion of Lead Finish	Adhesion of Lead Finish	Adhesion of Lead Finish
Subgroup D8	ss=5 from 1 lot	ss=5 from 1 lot	ss=5 from 1 lot
	Lid Torque	Lid Torque	Lid Torque