[Notes]

RX Driver Package,

R20TS0666EJ0100 Rev.1.00 Feb. 16, 2021

RX Family RTC Module Using Firmware Integration Technology

Overview

When using the RX Driver Package and RX Family RTC Module Using Firmware Integration Technology (referred to as RTC FIT module hereafter), note the following point.

- 1. Notes on output of RTCOUT pin when the R_RTC_Open function is called
- 1. Notes on output of RTCOUT pin when the R RTC Open function is called
- 1.1 Applicable Products
 - (1) RX Family RTC Module Using Firmware Integration Technology

The relevant revisions and documents are as shown in "Table 1.1, RTC FIT Module Applicable Products".

Revision of the RTC FIT module	Document number	
Rev.2.71	R01AN1817EJ0271	
Rev.2.72	R01AN1817EJ0272	
Rev.2.73	R01AN1817EJ0273	
Rev.2.74	R01AN1817EJ0274	
Rev.2.75	R01AN1817EJ0275	
Rev.2.76	R01AN1817EJ0276	
Rev.2.77	R01AN1817EJ0277	
Rev.2.78	R01AN1817EJ0278	
Rev.2.79	R01AN1817EJ0279	
Rev 2.80	R014N1817F I0280	

Table 1.1 RTC FIT Module Applicable Products

These notes also apply to the following RX Driver Package products which include the above RTC FIT module*1.

1: The RTC FIT module is included as r rtc rx v.**.zip (*.** is the revision number).

(2) RX Driver Package

The product name and revision of the relevant RX Driver Package products and the revision of the included RTC FIT module are as shown in "Table 1.2, Products Which Include the RTC FIT Module".

Table 1.2 Products Which Include the RTC FIT Module

Product name of the RX Driver	Revision of the RX Driver	Document number	Revision of the included RTC FIT
Package	Package	Document number	module
RX family	Rev.1.13	R01AN3859EJ0113	Rev.2.71
RX Driver Package Ver.1.13			
RX family	Rev.1.14	R01AN4191EJ0114	Rev.2.72
RX Driver Package Ver.1.14			
RX family	Rev.1.15	R01AN4372EJ0115	Rev.2.72
RX Driver Package Ver.1.15			
RX family	Rev.1.16	R01AN4471EJ0116	Rev.2.72
RX Driver Package Ver.1.16			
RX family	Rev.1.17	R01AN4572EJ0117	Rev.2.73
RX Driver Package Ver.1.17			
RX family	Rev.1.18	R01AN4659EJ0118	Rev.2.73
RX Driver Package Ver.1.18			
RX family	Rev.1.19	R01AN4677EJ0119	Rev.2.74
RX Driver Package Ver.1.19			
RX family	Rev.1.20	R01AN4794EJ0120	Rev.2.75
RX Driver Package Ver.1.20			
RX family	Rev.1.21	R01AN4843EJ0121	Rev.2.76
RX Driver Package Ver.1.21			
RX family	Rev.1.22	R01AN4873EJ0122	Rev.2.77
RX Driver Package Ver.1.22			
RX family	Rev.1.23	R01AN4976EJ0123	Rev.2.77
RX Driver Package Ver.1.23			
RX family	Rev.1.24	R01AN5267EJ0124	Rev.2.77
RX Driver Package Ver.1.24			
RX family	Rev.1.25	R01AN5371EJ0125	Rev.2.78
RX Driver Package Ver.1.25			
RX family	Rev.1.26	R01AN5401EJ0126	Rev.2.78
RX Driver Package Ver.1.26			
RX family	Rev.1.27	R01AN5600EJ0127	Rev.2.79
RX Driver Package Ver.1.27			
RX family	Rev.1.28	*1	Rev.2.80
RX Driver Package Ver.1.28			

^{*1:} RX family RX Driver Package Ver.1.28 has not yet been released as of February 16, 2021.

1.2 Applicable MCUs

RX110, RX111, RX113, RX130, RX230, RX231, RX23W, RX64M, RX651, RX65N, RX71M, RX72M and RX72N groups

1.3 Description

When an R_RTC_Open function is called, the RTCOUT pin might output 1 Hz even when the RTCOUT pin is set to output 64 Hz.

1.4 Conditions

The output of RTCOUT pin becomes 1 Hz when an R_RTC_Open function is called while output_freq stores RTC_OUTPUT_64_HZ and set_time stores true, where output_freq and set_time are members of a structure variable rtc_init_t.

```
rtc err t ret;
rtc init t rtc init;
tm t rtc curr time =
{
20,
59,
23,
31,
7,
115,
1,
0,
0,
};
/* Initialize rtc init */
rtc init.output freq = RTC OUTPUT 64 HZ;
rtc init.periodic freq = RTC PERIODIC 2 SEC;
rtc init.periodic priority = 8;
rtc init.set time = true;
rtc init.p callback = rtc callback;
ret = R RTC Open(&rtc init, &rtc curr time);
```

1.5 Workaround

In the RTC FIT module source code r_rtc_rx_hw.c, modify the processing of the rtc_enable_ints function. The details of the modification are as follows. Modify the blue part to the red part.

Before modification:

```
void rtc_enable_ints (void)
{

   /* Enable RTC interrupts (PIE, CIE and AIE), not ICU yet */
   RTC.RCR1.BYTE = RTC_INT_ENABLE;
   /* WAIT_LOOP */
   while (RTC_INT_ENABLE != RTC.RCR1.BYTE)
   {
        /* Confirm that it has changed */
        R_BSP_NOP();
   }

   return;
}
```

After modification:

```
void rtc_enable_ints (void)
{

   /* Enable RTC interrupts (PIE, CIE and AIE), not ICU yet */
   RTC.RCR1.BYTE |= RTC_INT_ENABLE;
   /* WAIT_LOOP */
   while (RTC_INT_ENABLE != (RTC.RCR1.BYTE & RTC_INT_ENABLE))
   {
        /* Confirm that it has changed */
        R_BSP_NOP();
   }

   return;
}
```

1.6 Permanent Measure

(1) RTC FIT module

This problem will be fixed in Rev.2.81, which will be the next release.

(2) RX Driver Package

The RTC FIT module Rev.2.81 modified in accord with this note will be included in Ver.1.29 of the RX Family RX Driver Package, which will be the hereafter release.

Revision History

		Description	
Rev.	Date	Page	Summary
1.00	Feb.16.21	-	First edition issued

Renesas Electronics has used reasonable care in preparing the information included in this document, but Renesas Electronics does not warrant that such information is error free. Renesas Electronics assumes no liability whatsoever for any damages incurred by you resulting from errors in or omissions from the information included herein.

The past news contents have been based on information at the time of publication. Now changed or invalid information may be included.

The URL in the Tool News also may be subject to change or become invalid without prior notice.

Corporate Headquarters

TOYOSU FORESIA, 3- 2- 24 Toyosu, Koto-ku, Tokyo 135- 0061, Japan www.renesas.com

Trademarks

Renesas and the Renesas logo are trademarks of Renesas Electronics Corporation. All trademarks and registered trademarks are the property of their respective owners.

Contact information

For further information on a product, technology, the most up-to-date version of a document, or your nearest sales office, please visit: www.renesas.com/contact/

 $\hbox{@ 2021 Renesas Electronics Corporation.}$ All rights reserved.

TS Colophon 4.2